

ASN1C

ASN.1 Compiler
Version 6.5
C# Common Runtime Classes
Reference Manual

The software described in this document is furnished under a license agreement and may be used only in accordance with the terms of this agreement.

Copyright Notice

Copyright ©1997–2012 Objective Systems, Inc. All rights reserved.

This document may be distributed in any form, electronic or otherwise, provided that it is distributed in its entirety and that the copyright and this notice are included.

Author's Contact Information

Comments, suggestions, and inquiries regarding ASN1C may be submitted via electronic mail to info@obj-sys.com.

Contents

1	ASN1C C# Runtime Library	1
2	Namespace Documentation	3
2.1	Package Com.Objsys.Asn1.Runtime	3
2.1.1	Detailed Description	4
3	Class Documentation	5
3.1	Asn18BitCharString Class Reference	5
3.1.1	Detailed Description	5
3.1.2	Constructor & Destructor Documentation	6
3.1.2.1	Asn18BitCharString	6
3.1.2.2	Asn18BitCharString	6
3.1.3	Member Function Documentation	6
3.1.3.1	Decode	6
3.1.3.2	Decode	6
3.1.3.3	Decode	7
3.1.3.4	Encode	7
3.1.3.5	Encode	7
3.1.3.6	Encode	8
3.1.3.7	Encode	8
3.1.3.8	Encode	8
3.1.3.9	Encode	8
3.1.4	Member Data Documentation	9
3.1.4.1	BITSPERCHAR_A	9
3.1.4.2	BITSPERCHAR_U	9
3.2	Asn1BigInteger Class Reference	10
3.2.1	Detailed Description	10
3.2.2	Constructor & Destructor Documentation	10
3.2.2.1	Asn1BigInteger	10

3.2.2.2	Asn1BigInteger	11
3.2.2.3	Asn1BigInteger	11
3.2.2.4	Asn1BigInteger	11
3.2.3	Member Function Documentation	11
3.2.3.1	Decode	11
3.2.3.2	Decode	11
3.2.3.3	DecodeValue	12
3.2.3.4	DecodeXER	12
3.2.3.5	DecodeXML	12
3.2.3.6	Encode	12
3.2.3.7	Encode	13
3.2.3.8	Encode	13
3.2.3.9	Encode	13
3.2.3.10	Encode	13
3.2.3.11	Encode	14
3.2.3.12	EncodeValue	14
3.2.3.13	Equals	14
3.2.3.14	Equals	14
3.2.3.15	GetHashCode	15
3.2.3.16	ToString	15
3.2.4	Member Data Documentation	15
3.2.4.1	_TAG	15
3.2.4.2	mValue	15
3.3	Asn1BitString Class Reference	16
3.3.1	Detailed Description	17
3.3.2	Member Enumeration Documentation	17
3.3.2.1	StringFormat	17
3.3.3	Constructor & Destructor Documentation	17
3.3.3.1	Asn1BitString	17
3.3.3.2	Asn1BitString	17
3.3.3.3	Asn1BitString	17
3.3.3.4	Asn1BitString	18
3.3.3.5	Asn1BitString	18
3.3.4	Member Function Documentation	18
3.3.4.1	Clear	18
3.3.4.2	Decode	18
3.3.4.3	Decode	18

3.3.4.4	Decode	19
3.3.4.5	Decode	19
3.3.4.6	DecodeXER	19
3.3.4.7	DecodeXML	19
3.3.4.8	Encode	19
3.3.4.9	Encode	20
3.3.4.10	Encode	20
3.3.4.11	Encode	20
3.3.4.12	Encode	21
3.3.4.13	Encode	21
3.3.4.14	Encode	21
3.3.4.15	Encode	21
3.3.4.16	Encode	22
3.3.4.17	Encode	22
3.3.4.18	Encode	22
3.3.4.19	Equals	22
3.3.4.20	Equals	23
3.3.4.21	Get	23
3.3.4.22	GetHashCode	23
3.3.4.23	IsNamedBitStr	23
3.3.4.24	Set	24
3.3.4.25	Set	24
3.3.4.26	ToBoolArray	24
3.3.4.27	ToHexString	24
3.3.4.28	ToString	24
3.3.5	Member Data Documentation	24
3.3.5.1	_TAG	24
3.3.5.2	mStringFormat	25
3.3.5.3	mValue	25
3.3.5.4	numbits	25
3.3.5.5	trimZeroBits	25
3.3.6	Property Documentation	25
3.3.6.1	Length	25
3.3.6.2	this	25
3.4	Asn1BMPString Class Reference	26
3.4.1	Detailed Description	26
3.4.2	Constructor & Destructor Documentation	26

3.4.2.1	Asn1BMPString	26
3.4.2.2	Asn1BMPString	26
3.4.3	Member Function Documentation	27
3.4.3.1	Decode	27
3.4.3.2	Decode	27
3.4.3.3	Decode	27
3.4.3.4	Decode	27
3.4.3.5	Encode	28
3.4.3.6	Encode	28
3.4.3.7	Encode	28
3.4.3.8	Encode	29
3.4.3.9	Encode	29
3.4.3.10	Encode	29
3.4.3.11	Encode	30
3.4.3.12	Encode	30
3.4.4	Member Data Documentation	30
3.4.4.1	_TAG	30
3.4.4.2	BITSPERCHAR	30
3.5	Asn1Boolean Class Reference	31
3.5.1	Detailed Description	31
3.5.2	Constructor & Destructor Documentation	31
3.5.2.1	Asn1Boolean	31
3.5.2.2	Asn1Boolean	32
3.5.3	Member Function Documentation	32
3.5.3.1	Decode	32
3.5.3.2	Decode	32
3.5.3.3	DecodeXER	32
3.5.3.4	DecodeXML	33
3.5.3.5	Encode	33
3.5.3.6	Encode	33
3.5.3.7	Encode	34
3.5.3.8	Encode	34
3.5.3.9	Encode	34
3.5.3.10	Encode	34
3.5.3.11	Encode	34
3.5.3.12	Encode	35
3.5.3.13	EncodeAttribute	35

3.5.3.14	Equals	35
3.5.3.15	Equals	35
3.5.3.16	GetHashCode	36
3.5.3.17	setTrueEncodedByte	36
3.5.3.18	ToString	36
3.5.4	Member Data Documentation	36
3.5.4.1	_TAG	36
3.5.4.2	FALSE_VALUE	36
3.5.4.3	mValue	36
3.5.4.4	TRUE_VALUE	36
3.6	Asn1CharRange Class Reference	37
3.6.1	Detailed Description	37
3.6.2	Constructor & Destructor Documentation	37
3.6.2.1	Asn1CharRange	37
3.6.3	Member Function Documentation	38
3.6.3.1	GetCharAtIndex	38
3.6.3.2	GetCharIndex	38
3.6.3.3	validate	38
3.6.4	Member Data Documentation	39
3.6.4.1	mLower	39
3.6.4.2	mUpper	39
3.6.5	Property Documentation	39
3.6.5.1	MaxValue	39
3.7	Asn1CharSet Class Reference	40
3.7.1	Detailed Description	40
3.7.2	Constructor & Destructor Documentation	40
3.7.2.1	Asn1CharSet	40
3.7.3	Member Function Documentation	40
3.7.3.1	GetCharAtIndex	40
3.7.3.2	GetCharIndex	41
3.7.3.3	GetNumBitsPerChar	41
3.7.3.4	validate	41
3.7.4	Member Data Documentation	42
3.7.4.1	mABitsPerChar	42
3.7.4.2	mUBitsPerChar	42
3.7.5	Property Documentation	42
3.7.5.1	MaxValue	42

3.8	Asn1CharString Class Reference	43
3.8.1	Detailed Description	43
3.8.2	Constructor & Destructor Documentation	44
3.8.2.1	Asn1CharString	44
3.8.2.2	Asn1CharString	44
3.8.3	Member Function Documentation	44
3.8.3.1	Decode	44
3.8.3.2	Decode	44
3.8.3.3	Decode	45
3.8.3.4	DecodeXER	45
3.8.3.5	DecodeXML	45
3.8.3.6	Encode	45
3.8.3.7	Encode	46
3.8.3.8	Encode	46
3.8.3.9	Encode	46
3.8.3.10	Encode	47
3.8.3.11	Equals	47
3.8.3.12	Equals	47
3.8.3.13	GetHashCode	47
3.8.3.14	ToString	48
3.8.3.15	validate	48
3.8.4	Member Data Documentation	48
3.8.4.1	mStringBuffer	48
3.8.4.2	mValue	48
3.8.5	Property Documentation	48
3.8.5.1	Length	48
3.9	Asn1Choice Class Reference	49
3.9.1	Detailed Description	49
3.9.2	Constructor & Destructor Documentation	49
3.9.2.1	Asn1Choice	49
3.9.3	Member Function Documentation	49
3.9.3.1	Equals	49
3.9.3.2	GetElement	50
3.9.3.3	GetHashCode	50
3.9.3.4	SetElement	50
3.9.4	Member Data Documentation	50
3.9.4.1	choiceID	50

3.9.4.2	element	50
3.9.5	Property Documentation	50
3.9.5.1	ChoiceID	50
3.9.5.2	ElemName	51
3.10	Asn1ChoiceExt Class Reference	52
3.10.1	Detailed Description	52
3.10.2	Member Function Documentation	52
3.10.2.1	Decode	52
3.10.2.2	Decode	52
3.10.2.3	Encode	53
3.10.2.4	Encode	53
3.10.2.5	Encode	53
3.10.2.6	Encode	53
3.10.3	Member Data Documentation	53
3.10.3.1	choiceIndex	53
3.11	Asn1ConsVioException Class Reference	54
3.11.1	Detailed Description	54
3.11.2	Constructor & Destructor Documentation	54
3.11.2.1	Asn1ConsVioException	54
3.11.2.2	Asn1ConsVioException	54
3.11.2.3	Asn1ConsVioException	54
3.12	Asn1DecodeBuffer Class Reference	55
3.12.1	Detailed Description	55
3.12.2	Member Function Documentation	56
3.12.2.1	AddCaptureBuffer	56
3.12.2.2	Capture	56
3.12.2.3	DecodeIntValue	56
3.12.2.4	DecodeOIDContents	56
3.12.2.5	DecodeRelOIDContents	56
3.12.2.6	GetInputStream	57
3.12.2.7	HexDump	57
3.12.2.8	Init	57
3.12.2.9	Mark	57
3.12.2.10	Read	57
3.12.2.11	Read	57
3.12.2.12	Read	58
3.12.2.13	Read2Bytes	58

3.12.2.14	Read4Bytes	58
3.12.2.15	ReadByte	59
3.12.2.16	RemoveCaptureBuffer	59
3.12.2.17	Reset	59
3.12.2.18	SetInputStream	59
3.12.2.19	Skip	59
3.12.3	Member Data Documentation	59
3.12.3.1	mByteCount	59
3.12.4	Property Documentation	60
3.12.4.1	ByteCount	60
3.12.4.2	LazyOpenTypeDecode	60
3.13	Asn1DiscreteCharSet Class Reference	61
3.13.1	Detailed Description	61
3.13.2	Constructor & Destructor Documentation	61
3.13.2.1	Asn1DiscreteCharSet	61
3.13.2.2	Asn1DiscreteCharSet	61
3.13.3	Member Function Documentation	61
3.13.3.1	GetCharAtIndex	61
3.13.3.2	GetCharIndex	62
3.13.3.3	helpValidate	62
3.13.3.4	validate	62
3.13.4	Property Documentation	63
3.13.4.1	MaxValue	63
3.14	Asn1EncodeBuffer Class Reference	64
3.14.1	Detailed Description	64
3.14.2	Member Function Documentation	64
3.14.2.1	BinDump	64
3.14.2.2	BinDump	65
3.14.2.3	CheckSize	65
3.14.2.4	Copy	65
3.14.2.5	Copy	65
3.14.2.6	HexDump	65
3.14.2.7	HexDump	65
3.14.2.8	InitBuffer	66
3.14.2.9	Reset	66
3.14.2.10	Write	66
3.14.3	Member Data Documentation	66

3.14.3.1	mByteIndex	66
3.14.3.2	mData	66
3.14.3.3	mSizeIncrement	66
3.14.3.4	SIZE_INCREMENT	66
3.14.4	Property Documentation	66
3.14.4.1	MsgCopy	66
3.14.4.2	MsgLength	67
3.15	Asn1EndOfBufferException Class Reference	68
3.15.1	Detailed Description	68
3.15.2	Constructor & Destructor Documentation	68
3.15.2.1	Asn1EndOfBufferException	68
3.16	Asn1Enumerated Class Reference	69
3.16.1	Detailed Description	69
3.16.2	Constructor & Destructor Documentation	69
3.16.2.1	Asn1Enumerated	69
3.16.2.2	Asn1Enumerated	70
3.16.3	Member Function Documentation	70
3.16.3.1	Decode	70
3.16.3.2	Decode	70
3.16.3.3	DecodeXER	70
3.16.3.4	DecodeXML	71
3.16.3.5	Encode	71
3.16.3.6	Encode	71
3.16.3.7	Encode	71
3.16.3.8	Encode	72
3.16.3.9	Encode	72
3.16.3.10	Encode	72
3.16.3.11	Encode	72
3.16.3.12	Encode	72
3.16.3.13	Equals	73
3.16.3.14	Equals	73
3.16.3.15	GetHashCode	73
3.16.3.16	ParseValue	73
3.16.3.17	ToString	74
3.16.4	Member Data Documentation	74
3.16.4.1	_TAG	74
3.16.4.2	mValue	74

3.16.4.3	UNDEFINED	74
3.17	Asn1Exception Class Reference	75
3.17.1	Detailed Description	75
3.17.2	Constructor & Destructor Documentation	75
3.17.2.1	Asn1Exception	75
3.17.2.2	Asn1Exception	75
3.17.2.3	Asn1Exception	75
3.18	Asn1GeneralizedTime Class Reference	76
3.18.1	Detailed Description	76
3.18.2	Constructor & Destructor Documentation	76
3.18.2.1	Asn1GeneralizedTime	76
3.18.2.2	Asn1GeneralizedTime	76
3.18.2.3	Asn1GeneralizedTime	77
3.18.2.4	Asn1GeneralizedTime	77
3.18.3	Member Function Documentation	77
3.18.3.1	CompareTo	77
3.18.3.2	CompileString	77
3.18.3.3	Decode	77
3.18.3.4	Encode	78
3.18.3.5	Encode	78
3.18.3.6	ParseString	78
3.18.4	Member Data Documentation	79
3.18.4.1	_TAG	79
3.18.5	Property Documentation	79
3.18.5.1	Century	79
3.19	Asn1GeneralString Class Reference	80
3.19.1	Detailed Description	80
3.19.2	Constructor & Destructor Documentation	80
3.19.2.1	Asn1GeneralString	80
3.19.2.2	Asn1GeneralString	80
3.19.3	Member Function Documentation	80
3.19.3.1	Decode	80
3.19.3.2	Encode	81
3.19.3.3	Encode	81
3.19.4	Member Data Documentation	81
3.19.4.1	_TAG	81
3.20	Asn1GraphicString Class Reference	82

3.20.1	Detailed Description	82
3.20.2	Constructor & Destructor Documentation	82
3.20.2.1	Asn1GraphicString	82
3.20.2.2	Asn1GraphicString	82
3.20.3	Member Function Documentation	82
3.20.3.1	Decode	82
3.20.3.2	Encode	83
3.20.3.3	Encode	83
3.20.4	Member Data Documentation	83
3.20.4.1	_TAG	83
3.21	Asn1IA5String Class Reference	84
3.21.1	Detailed Description	84
3.21.2	Constructor & Destructor Documentation	84
3.21.2.1	Asn1IA5String	84
3.21.2.2	Asn1IA5String	84
3.21.3	Member Function Documentation	84
3.21.3.1	Decode	84
3.21.3.2	Encode	85
3.21.3.3	Encode	85
3.21.4	Member Data Documentation	85
3.21.4.1	_TAG	85
3.22	Asn1InputStream Interface Reference	86
3.22.1	Detailed Description	86
3.22.2	Member Function Documentation	86
3.22.2.1	Available	86
3.22.2.2	Close	86
3.22.2.3	Mark	86
3.22.2.4	MarkSupported	86
3.22.2.5	Reset	87
3.22.2.6	Skip	87
3.23	Asn1Integer Class Reference	88
3.23.1	Detailed Description	89
3.23.2	Constructor & Destructor Documentation	89
3.23.2.1	Asn1Integer	89
3.23.2.2	Asn1Integer	89
3.23.3	Member Function Documentation	89
3.23.3.1	Decode	89

3.23.3.2 Decode	89
3.23.3.3 Decode	90
3.23.3.4 Decode	90
3.23.3.5 Decode	90
3.23.3.6 Decode	90
3.23.3.7 Decode16Bit	91
3.23.3.8 Decode32Bit	91
3.23.3.9 Decode8Bit	91
3.23.3.10 DecodeValue	91
3.23.3.11 DecodeValue	91
3.23.3.12 DecodeXER	91
3.23.3.13 DecodeXML	92
3.23.3.14 Encode	92
3.23.3.15 Encode	92
3.23.3.16 Encode	92
3.23.3.17 Encode	92
3.23.3.18 Encode	93
3.23.3.19 Encode	93
3.23.3.20 Encode	93
3.23.3.21 Encode	94
3.23.3.22 Encode	94
3.23.3.23 Encode	94
3.23.3.24 Encode	94
3.23.3.25 Encode	95
3.23.3.26 Encode	95
3.23.3.27 Encode	95
3.23.3.28 Encode16Bit	95
3.23.3.29 Encode32Bit	95
3.23.3.30 Encode8Bit	95
3.23.3.31 EncodeAttribute	96
3.23.3.32 EncodeValue	96
3.23.3.33 Equals	96
3.23.3.34 Equals	96
3.23.3.35 GetBitCount	96
3.23.3.36 GetBitCount	97
3.23.3.37 GetHashCode	97
3.23.3.38 GetUnsignedBitCount	97

3.23.3.39	GetUnsignedBitCount	97
3.23.3.40	ToString	97
3.23.4	Member Data Documentation	98
3.23.4.1	_TAG	98
3.23.4.2	mValue	98
3.24	Asn1InvalidArgException Class Reference	99
3.24.1	Detailed Description	99
3.24.2	Constructor & Destructor Documentation	99
3.24.2.1	Asn1InvalidArgException	99
3.25	Asn1InvalidChoiceOptionException Class Reference	100
3.25.1	Detailed Description	100
3.25.2	Constructor & Destructor Documentation	100
3.25.2.1	Asn1InvalidChoiceOptionException	100
3.25.2.2	Asn1InvalidChoiceOptionException	100
3.25.2.3	Asn1InvalidChoiceOptionException	100
3.26	Asn1InvalidEnumException Class Reference	101
3.26.1	Detailed Description	101
3.26.2	Constructor & Destructor Documentation	101
3.26.2.1	Asn1InvalidEnumException	101
3.26.2.2	Asn1InvalidEnumException	101
3.27	Asn1InvalidLengthException Class Reference	102
3.27.1	Detailed Description	102
3.27.2	Constructor & Destructor Documentation	102
3.27.2.1	Asn1InvalidLengthException	102
3.28	Asn1InvalidObjectIDException Class Reference	103
3.28.1	Detailed Description	103
3.28.2	Constructor & Destructor Documentation	103
3.28.2.1	Asn1InvalidObjectIDException	103
3.29	Asn1MessageBuffer Class Reference	104
3.29.1	Detailed Description	104
3.29.2	Member Function Documentation	104
3.29.2.1	AddNamedEventHandler	104
3.29.2.2	GetInputStream	104
3.29.2.3	HexDump	105
3.29.2.4	HexDump	105
3.29.2.5	InvokeCharacters	105
3.29.2.6	InvokeEndElement	105

3.29.2.7	InvokeStartElement	105
3.29.2.8	SetKey	106
3.29.2.9	SetPermanentKey	106
3.29.3	Property Documentation	106
3.29.3.1	Context	106
3.29.3.2	EventHandlerList	106
3.29.3.3	TypeCode	106
3.30	Asn1MissingRequiredException Class Reference	107
3.30.1	Detailed Description	107
3.30.2	Constructor & Destructor Documentation	107
3.30.2.1	Asn1MissingRequiredException	107
3.30.2.2	Asn1MissingRequiredException	107
3.31	Asn1NamedEventHandler Interface Reference	108
3.31.1	Detailed Description	108
3.31.2	Member Function Documentation	108
3.31.2.1	Characters	108
3.31.2.2	EndElement	108
3.31.2.3	StartElement	109
3.32	Asn1Null Class Reference	110
3.32.1	Detailed Description	110
3.32.2	Member Function Documentation	110
3.32.2.1	Decode	110
3.32.2.2	Decode	110
3.32.2.3	DecodeXER	111
3.32.2.4	DecodeXML	111
3.32.2.5	Encode	111
3.32.2.6	Encode	111
3.32.2.7	Encode	112
3.32.2.8	Encode	112
3.32.2.9	Encode	112
3.32.2.10	Encode	112
3.32.2.11	Equals	113
3.32.2.12	ToString	113
3.32.3	Member Data Documentation	113
3.32.3.1	_TAG	113
3.32.3.2	NULL_VALUE	113
3.33	Asn1NumericString Class Reference	114

3.33.1	Detailed Description	114
3.33.2	Constructor & Destructor Documentation	114
3.33.2.1	Asn1NumericString	114
3.33.2.2	Asn1NumericString	114
3.33.3	Member Function Documentation	114
3.33.3.1	Decode	114
3.33.3.2	Decode	115
3.33.3.3	Decode	115
3.33.3.4	Encode	115
3.33.3.5	Encode	116
3.33.3.6	Encode	116
3.33.3.7	Encode	116
3.33.4	Member Data Documentation	116
3.33.4.1	_TAG	116
3.34	Asn1ObjectDescriptor Class Reference	117
3.34.1	Detailed Description	117
3.34.2	Constructor & Destructor Documentation	117
3.34.2.1	Asn1ObjectDescriptor	117
3.34.2.2	Asn1ObjectDescriptor	117
3.34.3	Member Function Documentation	117
3.34.3.1	Decode	117
3.34.3.2	Encode	118
3.34.3.3	Encode	118
3.34.4	Member Data Documentation	118
3.34.4.1	_TAG	118
3.35	Asn1ObjectIdentifier Class Reference	119
3.35.1	Detailed Description	119
3.35.2	Constructor & Destructor Documentation	119
3.35.2.1	Asn1ObjectIdentifier	119
3.35.2.2	Asn1ObjectIdentifier	119
3.35.3	Member Function Documentation	120
3.35.3.1	Append	120
3.35.3.2	Decode	120
3.35.3.3	Decode	120
3.35.3.4	DecodeXER	120
3.35.3.5	DecodeXML	121
3.35.3.6	Encode	121

3.35.3.7	Encode	121
3.35.3.8	Encode	121
3.35.3.9	Encode	122
3.35.3.10	Encode	122
3.35.3.11	Encode	122
3.35.3.12	Equals	123
3.35.3.13	GetHashCode	123
3.35.3.14	ToString	123
3.35.4	Member Data Documentation	123
3.35.4.1	_TAG	123
3.35.4.2	MAXSUBIDS	123
3.35.4.3	mValue	123
3.36	Asn1OctetString Class Reference	124
3.36.1	Detailed Description	125
3.36.2	Constructor & Destructor Documentation	125
3.36.2.1	Asn1OctetString	125
3.36.2.2	Asn1OctetString	125
3.36.2.3	Asn1OctetString	125
3.36.2.4	Asn1OctetString	125
3.36.3	Member Function Documentation	126
3.36.3.1	CompareTo	126
3.36.3.2	Decode	126
3.36.3.3	Decode	126
3.36.3.4	Decode	126
3.36.3.5	Decode	126
3.36.3.6	Decode	127
3.36.3.7	DecodeXER	127
3.36.3.8	DecodeXML	127
3.36.3.9	Encode	127
3.36.3.10	Encode	128
3.36.3.11	Encode	128
3.36.3.12	Encode	128
3.36.3.13	Encode	129
3.36.3.14	Encode	129
3.36.3.15	Encode	129
3.36.3.16	Encode	129
3.36.3.17	Encode	129

3.36.3.18	Encode	130
3.36.3.19	Encode	130
3.36.3.20	EncodeAttribute	130
3.36.3.21	EncodeBase64Binary	131
3.36.3.22	Equals	131
3.36.3.23	Equals	131
3.36.3.24	GetHashCode	131
3.36.3.25	GetMderLength	131
3.36.3.26	toInputStream	132
3.36.3.27	ToString	132
3.36.4	Member Data Documentation	132
3.36.4.1	_TAG	132
3.36.4.2	mValue	132
3.36.5	Property Documentation	132
3.36.5.1	Length	132
3.37	Asn1OpenExt Class Reference	133
3.37.1	Detailed Description	133
3.37.2	Member Function Documentation	133
3.37.2.1	Decode	133
3.37.2.2	Decode	134
3.37.2.3	DecodeComponent	134
3.37.2.4	DecodeEventComponent	134
3.37.2.5	DecodeOpenType	134
3.37.2.6	Encode	135
3.37.2.7	Encode	135
3.37.2.8	Encode	135
3.37.2.9	Encode	135
3.37.2.10	Encode	136
3.37.2.11	Encode	136
3.37.2.12	EncodeExtBits	136
3.37.2.13	SetOpenType	136
3.37.2.14	ShrinkArray	136
3.37.2.15	ToString	137
3.37.3	Member Data Documentation	137
3.37.3.1	mValue	137
3.38	Asn1OpenType Class Reference	138
3.38.1	Detailed Description	138

3.38.2	Constructor & Destructor Documentation	138
3.38.2.1	Asn1OpenType	138
3.38.2.2	Asn1OpenType	138
3.38.2.3	Asn1OpenType	139
3.38.2.4	Asn1OpenType	139
3.38.3	Member Function Documentation	139
3.38.3.1	Decode	139
3.38.3.2	Encode	139
3.38.3.3	Encode	140
3.38.3.4	encode	140
3.38.3.5	encode	140
3.38.3.6	Encode	140
3.38.3.7	Encode	141
3.38.3.8	ToString	141
3.38.4	Member Data Documentation	141
3.38.4.1	mEncodeBuffer	141
3.38.4.2	mLength	141
3.39	Asn1OutputStream Class Reference	142
3.39.1	Detailed Description	142
3.39.2	Constructor & Destructor Documentation	142
3.39.2.1	Asn1OutputStream	142
3.39.3	Member Function Documentation	143
3.39.3.1	Close	143
3.39.3.2	Flush	143
3.39.3.3	Read	143
3.39.3.4	Seek	143
3.39.3.5	SetLength	144
3.39.3.6	Write	144
3.39.3.7	Write	145
3.39.3.8	Write2Bytes	145
3.39.3.9	Write4Bytes	145
3.39.3.10	WriteByte	145
3.39.3.11	WriteByte	146
3.39.4	Member Data Documentation	146
3.39.4.1	os	146
3.39.5	Property Documentation	146
3.39.5.1	CanRead	146

3.39.5.2	CanSeek	146
3.39.5.3	CanWrite	146
3.39.5.4	Context	146
3.39.5.5	Length	146
3.39.5.6	Position	147
3.40	Asn1PrintableString Class Reference	148
3.40.1	Detailed Description	148
3.40.2	Constructor & Destructor Documentation	148
3.40.2.1	Asn1PrintableString	148
3.40.2.2	Asn1PrintableString	148
3.40.3	Member Function Documentation	148
3.40.3.1	Decode	148
3.40.3.2	Encode	149
3.40.3.3	Encode	149
3.40.4	Member Data Documentation	149
3.40.4.1	_TAG	149
3.41	Asn1Real Class Reference	150
3.41.1	Detailed Description	150
3.41.2	Constructor & Destructor Documentation	150
3.41.2.1	Asn1Real	150
3.41.2.2	Asn1Real	151
3.41.3	Member Function Documentation	151
3.41.3.1	Decode	151
3.41.3.2	Decode	151
3.41.3.3	DecodeXER	151
3.41.3.4	DecodeXML	151
3.41.3.5	Encode	152
3.41.3.6	Encode	152
3.41.3.7	Encode	152
3.41.3.8	Encode	152
3.41.3.9	Encode	153
3.41.3.10	Encode	153
3.41.3.11	Encode	153
3.41.3.12	EncodeAttribute	153
3.41.3.13	EncodeValue	153
3.41.3.14	Equals	154
3.41.3.15	Equals	154

3.41.3.16	GetHashCode	154
3.41.3.17	ToString	154
3.41.4	Member Data Documentation	154
3.41.4.1	_TAG	154
3.41.4.2	mValue	154
3.42	Asn1Real10 Class Reference	155
3.42.1	Detailed Description	155
3.42.2	Constructor & Destructor Documentation	155
3.42.2.1	Asn1Real10	155
3.42.2.2	Asn1Real10	155
3.42.3	Member Function Documentation	156
3.42.3.1	ConvertToDecimal	156
3.42.3.2	ConvertToNR3Form	156
3.42.3.3	Decode	156
3.42.3.4	Decode	156
3.42.3.5	Encode	156
3.42.3.6	Encode	157
3.42.3.7	Encode	157
3.42.3.8	Encode	157
3.42.3.9	Encode	157
3.42.3.10	Encode	158
3.42.3.11	Encode	158
3.42.3.12	Encode	158
3.42.3.13	EncodeAttribute	158
3.42.3.14	GetNumberForm	159
3.42.3.15	GetNumberForm	159
3.42.4	Member Data Documentation	159
3.42.4.1	_TAG	159
3.43	Asn1RelativeOID Class Reference	160
3.43.1	Detailed Description	160
3.43.2	Constructor & Destructor Documentation	160
3.43.2.1	Asn1RelativeOID	160
3.43.2.2	Asn1RelativeOID	160
3.43.3	Member Function Documentation	160
3.43.3.1	Decode	160
3.43.3.2	Decode	161
3.43.3.3	DecodeXER	161

3.43.3.4	DecodeXML	161
3.43.3.5	Encode	161
3.43.3.6	Encode	162
3.43.3.7	Encode	162
3.43.3.8	Encode	162
3.43.3.9	Encode	163
3.43.3.10	Encode	163
3.43.4	Member Data Documentation	163
3.43.4.1	_TAG	163
3.44	Asn1SeqOrderException Class Reference	164
3.44.1	Detailed Description	164
3.44.2	Constructor & Destructor Documentation	164
3.44.2.1	Asn1SeqOrderException	164
3.45	Asn1Status Class Reference	165
3.45.1	Detailed Description	165
3.45.2	Member Data Documentation	165
3.45.2.1	INDEFLEN	165
3.46	Asn1T61String Class Reference	166
3.46.1	Detailed Description	166
3.46.2	Constructor & Destructor Documentation	166
3.46.2.1	Asn1T61String	166
3.46.2.2	Asn1T61String	166
3.46.3	Member Function Documentation	166
3.46.3.1	Decode	166
3.46.3.2	Encode	167
3.46.3.3	Encode	167
3.46.4	Member Data Documentation	167
3.46.4.1	_TAG	167
3.47	Asn1Tag Class Reference	168
3.47.1	Detailed Description	168
3.47.2	Constructor & Destructor Documentation	169
3.47.2.1	Asn1Tag	169
3.47.2.2	Asn1Tag	169
3.47.3	Member Function Documentation	169
3.47.3.1	Equals	169
3.47.3.2	Equals	169
3.47.3.3	IsEOC	169

3.47.3.4	ToString	170
3.47.4	Member Data Documentation	170
3.47.4.1	APPL	170
3.47.4.2	Bit8Mask	170
3.47.4.3	ClassMask	170
3.47.4.4	CONS	170
3.47.4.5	CTXT	170
3.47.4.6	ENUM	170
3.47.4.7	EOC	170
3.47.4.8	EXPL	170
3.47.4.9	EXTIDCODE	170
3.47.4.10	FormMask	171
3.47.4.11	IDMask	171
3.47.4.12	IMPL	171
3.47.4.13	L7BitsMask	171
3.47.4.14	mClass	171
3.47.4.15	mForm	171
3.47.4.16	mIDCode	171
3.47.4.17	PRIM	171
3.47.4.18	PRIV	171
3.47.4.19	SEQUENCE	171
3.47.4.20	SET	171
3.47.4.21	UNIV	171
3.47.5	Property Documentation	172
3.47.5.1	Constructed	172
3.48	Asn1Time Class Reference	173
3.48.1	Detailed Description	175
3.48.2	Constructor & Destructor Documentation	175
3.48.2.1	Asn1Time	175
3.48.2.2	Asn1Time	175
3.48.3	Member Function Documentation	175
3.48.3.1	CharAt	175
3.48.3.2	Clear	176
3.48.3.3	CompareTo	176
3.48.3.4	CompileString	176
3.48.3.5	Decode	176
3.48.3.6	Decode	177

3.48.3.7	DecodeXML	177
3.48.3.8	Encode	177
3.48.3.9	Encode	177
3.48.3.10	Encode	178
3.48.3.11	Encode	178
3.48.3.12	Encode	178
3.48.3.13	EncodeXER	178
3.48.3.14	EncodeXMLData	179
3.48.3.15	Equals	179
3.48.3.16	GetDiff	179
3.48.3.17	GetHashCode	180
3.48.3.18	GetTime	180
3.48.3.19	Init	180
3.48.3.20	ParseInt	180
3.48.3.21	ParseString	180
3.48.3.22	ParseXmlString	181
3.48.3.23	PutInteger	181
3.48.3.24	PutInteger	181
3.48.3.25	SafeParseString	181
3.48.3.26	SetDiff	181
3.48.3.27	SetDiff	182
3.48.3.28	SetTime	182
3.48.4	Member Data Documentation	182
3.48.4.1	Apr	182
3.48.4.2	April	182
3.48.4.3	Aug	182
3.48.4.4	August	182
3.48.4.5	day	183
3.48.4.6	Dec	183
3.48.4.7	December	183
3.48.4.8	derRules	183
3.48.4.9	diffHour	183
3.48.4.10	diffMin	183
3.48.4.11	Feb	183
3.48.4.12	February	183
3.48.4.13	hour	183
3.48.4.14	Jan	183

3.48.4.15	January	183
3.48.4.16	Jul	183
3.48.4.17	July	184
3.48.4.18	Jun	184
3.48.4.19	June	184
3.48.4.20	Mar	184
3.48.4.21	March	184
3.48.4.22	May	184
3.48.4.23	minute	184
3.48.4.24	month	184
3.48.4.25	Nov	184
3.48.4.26	November	184
3.48.4.27	Oct	184
3.48.4.28	October	184
3.48.4.29	parsed	185
3.48.4.30	secFraction	185
3.48.4.31	second	185
3.48.4.32	Sep	185
3.48.4.33	September	185
3.48.4.34	utcFlag	185
3.48.4.35	year	185
3.48.5	Property Documentation	185
3.48.5.1	bool	185
3.48.5.2	Day	185
3.48.5.3	DiffHour	186
3.48.5.4	DiffMinute	186
3.48.5.5	Fraction	186
3.48.5.6	Hour	186
3.48.5.7	Minute	187
3.48.5.8	Month	187
3.48.5.9	Second	187
3.48.5.10	UTC	187
3.48.5.11	Year	187
3.49	Asn1TraceHandler Class Reference	189
3.49.1	Detailed Description	189
3.49.2	Constructor & Destructor Documentation	189
3.49.2.1	Asn1TraceHandler	189

3.49.2.2	Asn1TraceHandler	189
3.49.3	Member Function Documentation	189
3.49.3.1	Characters	189
3.49.3.2	EndElement	190
3.49.3.3	StartElement	190
3.50	Asn1Type Class Reference	191
3.50.1	Detailed Description	192
3.50.2	Member Function Documentation	192
3.50.2.1	Decode	192
3.50.2.2	Decode	193
3.50.2.3	Decode	193
3.50.2.4	Decode	193
3.50.2.5	Decode	194
3.50.2.6	DecodeXML	194
3.50.2.7	Encode	194
3.50.2.8	Encode	194
3.50.2.9	Encode	195
3.50.2.10	Encode	195
3.50.2.11	Encode	196
3.50.2.12	Encode	196
3.50.2.13	Encode	196
3.50.2.14	Encode	197
3.50.2.15	Equals	197
3.50.2.16	GetTypeNames	197
3.50.2.17	Indent	197
3.50.2.18	IsOpenType	198
3.50.2.19	MatchTag	198
3.50.2.20	MatchTag	198
3.50.2.21	MatchTypeName	199
3.50.2.22	Pdiag	199
3.50.2.23	Print	199
3.50.2.24	Print	199
3.50.2.25	SetKey	199
3.50.2.26	SetKey2	200
3.50.2.27	SetOpenType	200
3.50.3	Member Data Documentation	200
3.50.3.1	_TAG	200

3.50.3.2	BIT_STRING	200
3.50.3.3	BMPString	200
3.50.3.4	BOOLEAN	200
3.50.3.5	DATE	200
3.50.3.6	ENUMERATED	200
3.50.3.7	EOC	201
3.50.3.8	EXTERNAL	201
3.50.3.9	GeneralString	201
3.50.3.10	GeneralTime	201
3.50.3.11	GraphicString	201
3.50.3.12	IA5String	201
3.50.3.13	INTEGER	201
3.50.3.14	NULL	201
3.50.3.15	NumericString	201
3.50.3.16	OBJECT_IDENTIFIER	201
3.50.3.17	ObjectDescriptor	201
3.50.3.18	OCTET_STRING	201
3.50.3.19	PrintableString	202
3.50.3.20	REAL	202
3.50.3.21	RelativeOID	202
3.50.3.22	SEQUENCE	202
3.50.3.23	SET	202
3.50.3.24	T61String	202
3.50.3.25	TeletexString	202
3.50.3.26	TIME	202
3.50.3.27	UniversalString	202
3.50.3.28	UTCTime	202
3.50.3.29	UTF8String	202
3.50.3.30	VideotexString	202
3.50.3.31	VisibleString	203
3.50.4	Property Documentation	203
3.50.4.1	Length	203
3.51	Asn1TypeIF Interface Reference	204
3.51.1	Detailed Description	204
3.51.2	Member Function Documentation	204
3.51.2.1	Decode	204
3.51.2.2	Decode	204

3.51.2.3	Decode	205
3.51.2.4	Decode	205
3.51.2.5	Encode	205
3.51.2.6	Encode	206
3.51.2.7	Encode	206
3.51.2.8	Encode	206
3.51.2.9	Encode	207
3.51.2.10	Encode	207
3.51.2.11	IsOpenType	207
3.51.2.12	Print	207
3.51.2.13	SetOpenType	208
3.52	Asn1UniversalString Class Reference	209
3.52.1	Detailed Description	210
3.52.2	Constructor & Destructor Documentation	210
3.52.2.1	Asn1UniversalString	210
3.52.2.2	Asn1UniversalString	210
3.52.2.3	Asn1UniversalString	210
3.52.3	Member Function Documentation	211
3.52.3.1	Decode	211
3.52.3.2	Decode	211
3.52.3.3	Decode	211
3.52.3.4	Decode	212
3.52.3.5	Decode	212
3.52.3.6	Decode	212
3.52.3.7	Decode	212
3.52.3.8	DecodeXER	213
3.52.3.9	DecodeXML	213
3.52.3.10	Encode	213
3.52.3.11	Encode	213
3.52.3.12	Encode	214
3.52.3.13	Encode	214
3.52.3.14	Encode	215
3.52.3.15	Encode	215
3.52.3.16	Encode	215
3.52.3.17	Encode	216
3.52.3.18	Encode	216
3.52.3.19	Encode	216

3.52.3.20	Encode	216
3.52.3.21	Encode	217
3.52.3.22	Encode	217
3.52.3.23	Encode	217
3.52.3.24	Encode	218
3.52.3.25	Encode	218
3.52.3.26	EncodeData	218
3.52.3.27	Equals	218
3.52.3.28	GetHashCode	219
3.52.3.29	ToString	219
3.52.3.30	validate	219
3.52.4	Member Data Documentation	219
3.52.4.1	_TAG	219
3.52.4.2	BITSPERCHAR	219
3.52.4.3	mStringBuffer	219
3.52.4.4	mValue	219
3.52.5	Property Documentation	220
3.52.5.1	Length	220
3.53	Asn1UTCTime Class Reference	221
3.53.1	Detailed Description	221
3.53.2	Constructor & Destructor Documentation	221
3.53.2.1	Asn1UTCTime	221
3.53.2.2	Asn1UTCTime	221
3.53.2.3	Asn1UTCTime	222
3.53.2.4	Asn1UTCTime	222
3.53.3	Member Function Documentation	222
3.53.3.1	Clear	222
3.53.3.2	CompareTo	222
3.53.3.3	CompileString	222
3.53.3.4	Decode	223
3.53.3.5	Encode	223
3.53.3.6	Encode	223
3.53.3.7	Init	223
3.53.3.8	ParseString	224
3.53.3.9	SetTime	224
3.53.4	Member Data Documentation	224
3.53.4.1	_TAG	224

3.53.5	Property Documentation	224
3.53.5.1	Fraction	224
3.53.5.2	Year	225
3.54	Asn1UTF8String Class Reference	226
3.54.1	Detailed Description	226
3.54.2	Constructor & Destructor Documentation	226
3.54.2.1	Asn1UTF8String	226
3.54.2.2	Asn1UTF8String	226
3.54.3	Member Function Documentation	226
3.54.3.1	Decode	226
3.54.3.2	Decode	227
3.54.3.3	Decode	227
3.54.3.4	Encode	227
3.54.3.5	Encode	228
3.54.3.6	Encode	228
3.54.3.7	Encode	228
3.54.3.8	Encode	228
3.54.3.9	Encode	229
3.54.4	Member Data Documentation	229
3.54.4.1	_TAG	229
3.55	Asn1Util Class Reference	230
3.55.1	Detailed Description	230
3.55.2	Member Function Documentation	230
3.55.2.1	BCDToString	230
3.55.2.2	DecodeBase64Array	230
3.55.2.3	EncodeBase64Array	231
3.55.2.4	GetAddressBytes	231
3.55.2.5	GetBytesCount	231
3.55.2.6	GetUlongBytesCount	231
3.55.2.7	StringToBCD	232
3.55.2.8	StringToTBCD	232
3.55.2.9	TBCDToString	232
3.55.2.10	ToArray	232
3.55.2.11	ToByteArray	233
3.55.2.12	ToCharArray	233
3.55.2.13	ToHexString	233
3.55.2.14	ToHexString	234

3.55.2.15 URShift	234
3.55.2.16 URShift	234
3.55.2.17 URShift	234
3.55.2.18 URShift	235
3.55.2.19 WriteStackTrace	235
3.56 Asn1Value Class Reference	236
3.56.1 Detailed Description	236
3.56.2 Member Function Documentation	236
3.56.2.1 ParseString	236
3.56.2.2 ParseString	236
3.57 Asn1ValueParseException Class Reference	237
3.57.1 Detailed Description	237
3.57.2 Constructor & Destructor Documentation	237
3.57.2.1 Asn1ValueParseException	237
3.57.2.2 Asn1ValueParseException	237
3.58 Asn1VarWidthCharString Class Reference	238
3.58.1 Detailed Description	238
3.58.2 Constructor & Destructor Documentation	238
3.58.2.1 Asn1VarWidthCharString	238
3.58.2.2 Asn1VarWidthCharString	238
3.58.3 Member Function Documentation	239
3.58.3.1 Decode	239
3.58.3.2 Decode	239
3.58.3.3 Encode	239
3.58.3.4 Encode	240
3.58.3.5 Encode	240
3.58.3.6 Encode	240
3.58.4 Member Data Documentation	240
3.58.4.1 BITSPERCHAR_A	240
3.58.4.2 BITSPERCHAR_U	240
3.59 Asn1VideotexString Class Reference	241
3.59.1 Detailed Description	241
3.59.2 Constructor & Destructor Documentation	241
3.59.2.1 Asn1VideotexString	241
3.59.2.2 Asn1VideotexString	241
3.59.3 Member Function Documentation	241
3.59.3.1 Decode	241

3.59.3.2	Encode	242
3.59.3.3	Encode	242
3.59.4	Member Data Documentation	242
3.59.4.1	_TAG	242
3.60	Asn1VisibleString Class Reference	243
3.60.1	Detailed Description	243
3.60.2	Constructor & Destructor Documentation	243
3.60.2.1	Asn1VisibleString	243
3.60.2.2	Asn1VisibleString	243
3.60.3	Member Function Documentation	243
3.60.3.1	Decode	243
3.60.3.2	Encode	244
3.60.3.3	Encode	244
3.60.4	Member Data Documentation	244
3.60.4.1	_TAG	244
3.61	BigInteger Class Reference	245
3.61.1	Detailed Description	245
3.61.2	Constructor & Destructor Documentation	245
3.61.2.1	BigInteger	245
3.61.2.2	BigInteger	245
3.61.2.3	BigInteger	246
3.61.2.4	BigInteger	246
3.61.2.5	BigInteger	246
3.61.3	Member Function Documentation	246
3.61.3.1	Equals	246
3.61.3.2	Equals	246
3.61.3.3	GetData	247
3.61.3.4	GetHashCode	247
3.61.3.5	Init	247
3.61.3.6	IsNegative	247
3.61.3.7	operator BigInteger	247
3.61.3.8	SecureDelete	247
3.61.3.9	SetData	248
3.61.3.10	ToString	248
3.61.3.11	ToString	248
3.62	BooleanHolder Class Reference	249
3.62.1	Detailed Description	249

3.62.2	Constructor & Destructor Documentation	249
3.62.2.1	BooleanHolder	249
3.62.2.2	BooleanHolder	249
3.62.3	Member Data Documentation	249
3.62.3.1	mValue	249
3.63	Diag Class Reference	250
3.63.1	Detailed Description	250
3.63.2	Member Function Documentation	250
3.63.2.1	HexDump	250
3.63.2.2	HexDump	251
3.63.2.3	HexDump	251
3.63.2.4	Instance	251
3.63.2.5	IsEnabled	251
3.63.2.6	IsEnabled	251
3.63.2.7	Println	251
3.63.2.8	Println	252
3.63.2.9	Prtln	252
3.63.2.10	Prtln	252
3.63.2.11	Prtln	252
3.63.2.12	Prtln	252
3.63.2.13	SetEnabled	253
3.63.2.14	SetTraceLevel	253
3.63.2.15	SetTraceLevel2	253
3.63.3	Property Documentation	253
3.63.3.1	PrintStream	253
3.64	IntHolder Class Reference	254
3.64.1	Detailed Description	254
3.64.2	Constructor & Destructor Documentation	254
3.64.2.1	IntHolder	254
3.64.2.2	IntHolder	254
3.64.3	Member Data Documentation	254
3.64.3.1	mValue	254
3.65	StringBufferExt Class Reference	255
3.65.1	Detailed Description	255
3.65.2	Member Function Documentation	255
3.65.2.1	Replace	255
3.66	Tokenizer Class Reference	256

3.66.1	Detailed Description	256
3.66.2	Constructor & Destructor Documentation	256
3.66.2.1	Tokenizer	256
3.66.2.2	Tokenizer	256
3.66.2.3	Tokenizer	256
3.66.3	Member Function Documentation	257
3.66.3.1	HasMoreTokens	257
3.66.3.2	MoveNext	257
3.66.3.3	NextToken	257
3.66.3.4	NextToken	257
3.66.3.5	RemainingString	257
3.66.3.6	Reset	258
3.66.4	Property Documentation	258
3.66.4.1	Count	258
3.66.4.2	Current	258

Chapter 1

ASN1C C# Runtime Library

The ASN.1 C# runtime library uses the `Com.Objsys.Asn1.Runtime` namespace. This namespace contains the implementation of the following rules:

- BER (As per ITU-T X.690 standard)
- CER (As per ITU-T X.690 standard)
- DER (As per ITU-T X.690 standard)
- MDER (As per ISO/IEEE 11073-2101:2004 standard)
- PER (As per ITU-T X.691 standard)
- XER (As per ITU-T X.693 standard)
- XML (As per asn2xsd converter)

Chapter 2

Namespace Documentation

2.1 Package Com.Objsys.Asn1.Runtime

Classes

- class [Asn18BitCharString](#)
- class [Asn1BigInteger](#)
- class [Asn1BitString](#)
- class [Asn1BMPString](#)
- class [Asn1Boolean](#)
- class [Asn1CharRange](#)
- class [Asn1CharSet](#)
- class [Asn1CharString](#)
- class [Asn1Choice](#)
- class [Asn1ChoiceExt](#)
- class [Asn1ConsVioException](#)
- class [Asn1DecodeBuffer](#)
- class [Asn1DiscreteCharSet](#)
- class [Asn1EncodeBuffer](#)
- class [Asn1EndOfBufferException](#)
- class [Asn1Enumerated](#)
- class [Asn1Exception](#)
- class [Asn1GeneralizedTime](#)
- class [Asn1GeneralString](#)
- class [Asn1GraphicString](#)
- class [Asn1IA5String](#)
- interface [Asn1InputStream](#)
- class [Asn1Integer](#)
- class [Asn1InvalidArgException](#)
- class [Asn1InvalidChoiceOptionException](#)
- class [Asn1InvalidEnumException](#)
- class [Asn1InvalidLengthException](#)
- class [Asn1InvalidObjectIDException](#)
- class [Asn1MessageBuffer](#)
- class [Asn1MissingRequiredException](#)
- interface [Asn1NamedEventHandler](#)

- class [Asn1Null](#)
- class [Asn1NumericString](#)
- class [Asn1ObjectDescriptor](#)
- class [Asn1ObjectIdentifier](#)
- class [Asn1OctetString](#)
- class [Asn1OpenExt](#)
- class [Asn1OpenType](#)
- class [Asn1OutputStream](#)
- class [Asn1PrintableString](#)
- class [Asn1Real](#)
- class [Asn1Real10](#)
- class [Asn1RelativeOID](#)
- class [Asn1SeqOrderException](#)
- class [Asn1Status](#)
- class [Asn1T61String](#)
- class [Asn1Tag](#)
- class [Asn1Time](#)
- class [Asn1TraceHandler](#)
- class [Asn1Type](#)
- interface [Asn1TypeIF](#)
- class [Asn1UniversalString](#)
- class [Asn1UTCTime](#)
- class [Asn1UTF8String](#)
- class [Asn1Util](#)
- class [Asn1Value](#)
- class [Asn1ValueParseException](#)
- class [Asn1VarWidthCharString](#)
- class [Asn1VideotexString](#)
- class [Asn1VisibleString](#)
- class [BigInteger](#)
- class [BooleanHolder](#)
- class [Diag](#)
- class [IntHolder](#)
- class [StringBufferExt](#)
- class [Tokenizer](#)

2.1.1 Detailed Description

The ASN.1 C# runtime library uses the [Com.Objsys.Asn1.Runtime](#) namespace. This namespace contains the implementation of the following rules:

- BER (As per ITU-T X.690 standard)
- CER (As per ITU-T X.690 standard)
- DER (As per ITU-T X.690 standard)
- MDER (As per ISO/IEEE 11073-2101:2004 standard)
- PER (As per ITU-T X.691 standard)
- XER (As per ITU-T X.693 standard)
- XML (As per asn2xsd converter)

Chapter 3

Class Documentation

3.1 Asn18BitCharString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1CharString](#).

Inherited by [Asn1IA5String](#), [Asn1NumericString](#), [Asn1PrintableString](#), [Asn1Time](#), and [Asn1VisibleString](#).

Public Member Functions

- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, [Asn1CharSet](#) charSet)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- virtual void [Encode](#) (Asn1PerOutputStream outs, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Encode](#) (Asn1PerOutputStream outs, [Asn1CharSet](#) charSet)
- override void [Encode](#) (Asn1PerOutputStream outs)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, [Asn1CharSet](#) charSet)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)

Public Attributes

- const int [BITSPERCHAR_A](#) = 8
- const int [BITSPERCHAR_U](#) = 7

Protected Member Functions

- internal [Asn18BitCharString](#) (System.String data, short typeCode)
- internal [Asn18BitCharString](#) (short typeCode)

3.1.1 Detailed Description

This is an abstract base class for holding the ASN.1 8-bit character string types (IA5String, VisibleString, PrintableString, etc.).

3.1.2 Constructor & Destructor Documentation

3.1.2.1 internal Asn18BitCharString (short *typeCode*) [protected]

The default constructor creates an empty string object.

Parameters

typeCode Universal ID code for ASN.1 character string

3.1.2.2 internal Asn18BitCharString (System.String *data*, short *typeCode*) [protected]

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data Character string

typeCode Universal ID code for ASN.1 character string

3.1.3 Member Function Documentation

3.1.3.1 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the Decode method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present and an optional permitted alphabet constraint.

The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.1.3.2 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Asn1CharSet *charSet*) [virtual]

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

3.1.3.3 **override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]**

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1NumericString](#), and [Asn1Time](#).

3.1.3.4 **virtual void Encode (Asn1PerOutputStream *outs*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]**

This overloaded version of the encode method encodes an ASN.1 character string value directly into the stream, in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present and an optional permitted alphabet constraint.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Also throws any exception thrown by the [Asn1PerOutputStream](#).

Parameters

outs PER Encode message stream object

charSet Object representing permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.1.3.5 **virtual void Encode (Asn1PerOutputStream *outs*, Asn1CharSet *charSet*) [virtual]**

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER) directly into the stream. This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Also throws any exception thrown by the [Asn1PerOutputStream](#).

Parameters

outs PER Encode message stream object

charSet Object representing permitted alphabet constraint character set (optional)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.1.3.6 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER) directly into the stream. This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Also throws any exception thrown by the [Asn1PerOutputStream](#).

Parameters

outs PER Encode message stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Time](#).

3.1.3.7 virtual void Encode (Asn1PerEncodeBuffer *buffer*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the encode method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present and an optional permitted alphabet constraint.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Encode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.1.3.8 virtual void Encode (Asn1PerEncodeBuffer *buffer*, Asn1CharSet *charSet*) [virtual]

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Encode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

3.1.3.9 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1NumericString](#), and [Asn1Time](#).

3.1.4 Member Data Documentation

3.1.4.1 `const int BITSPERCHAR_A = 8`

The `BITSPERCHAR_A` constant specifies the number of bits per character for PER (aligned).

3.1.4.2 `const int BITSPERCHAR_U = 7`

The `BITSPERCHAR_U` constant specifies the number of bits per character for PER (unaligned).

3.2 Asn1BigInteger Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1BigInteger](#) (System.String value, int radix)
- [Asn1BigInteger](#) (System.String value)
- [Asn1BigInteger](#) ([BigInteger](#) value)
- [Asn1BigInteger](#) ()
- override void [Decode](#) ([Asn1PerDecodeBuffer](#) buffer)
- override void [Decode](#) ([Asn1BerDecodeBuffer](#) buffer, bool explicitTagging, int implicitLength)
- [BigInteger DecodeValue](#) ([Asn1DecodeBuffer](#) buffer, int length)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) ([Asn1PerOutputStream](#) outs)
- override void [Encode](#) ([Asn1BerOutputStream](#) outs, bool explicitTagging)
- virtual void [Encode](#) ([Asn1XmlEncoder](#) buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) ([Asn1XerEncoder](#) buffer, System.String elemName)
- override void [Encode](#) ([Asn1PerEncodeBuffer](#) buffer)
- override int [Encode](#) ([Asn1BerEncodeBuffer](#) buffer, bool explicitTagging)
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (long value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()

Public Attributes

- [BigInteger mValue](#)

Static Public Attributes

- static new readonly [Asn1Tag _TAG](#) = new [Asn1Tag](#)([Asn1Tag.UNIV](#), [Asn1Tag.PRIM](#), [Asn1Type.INTEGER](#))

Static Protected Member Functions

- static internal int [EncodeValue](#) ([Asn1EncodeBuffer](#) buffer, [BigInteger](#) ivalue, bool doCopy)

3.2.1 Detailed Description

This class represents an ASN.1 INTEGER built-in type. In this case, the values can be greater than 64 bits in size. This class is used in generated source code if the <bigInteger> qualifier is specified in a compiler configuration file.

3.2.2 Constructor & Destructor Documentation

3.2.2.1 [Asn1BigInteger](#) ()

The default constructor sets the big integer value object reference to null.

3.2.2.2 Asn1BigInteger (BigInteger value)

This constructor assigns a big integer object.

Parameters

value [BigInteger](#) value

3.2.2.3 Asn1BigInteger (System.String value)

This constructor creates a new big integer object and sets it to the string value passed in. String value may contain the prefix that describes the radix: 0x - hexadecimal, 0o - octal, 0b - binary. The string value without prefix assumes decimal value. The optional sign '-' may be specified at the beginning of the string to specify the negative value.

Parameters

value String value

3.2.2.4 Asn1BigInteger (System.String value, int radix)

This constructor creates a new big integer object and sets it to the string value passed in. String value may contain the prefix that describes the radix: 0x - hexadecimal, 0o - octal, 0b - binary. The string value without prefix assumes decimal value. The optional sign '-' may be specified at the beginning of the string to specify the negative value.

Parameters

value String value

radix Can be 16 for hexadecimal, 8 for octal, 2 for binary or 10 for decimal

3.2.3 Member Function Documentation

3.2.3.1 override void Decode (Asn1PerDecodeBuffer buffer) [virtual]

This method decodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are decoded. The decoded result is stored in the public `mValue` member variable.

Parameters

buffer PER Decode message buffer object

Reimplemented from [Asn1Type](#).

3.2.3.2 override void Decode (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength) [virtual]

This method decodes an ASN.1 integer value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.2.3.3 BigInteger DecodeValue (Asn1DecodeBuffer *buffer*, int *length*)

This method decodes the contents of an ASN.1 integer value using either the Basic Encoding Rules (BER) or the Packed Encoding Rules (PER).

Parameters

buffer Decode message buffer object

length Length of encoded contents

Returns

Decoded integer value

3.2.3.4 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 integer value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.2.3.5 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 integer value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.2.3.6 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.2.3.7 override void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to the stream an ASN.1 integer value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

outs BER Output Stream object
explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.2.3.8 virtual void Encode (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix) [virtual]

This method encodes an ASN.1 integer value using the XML Encoding as specified in the XML schema standard.

Parameters

buffer Encode message buffer object
elemName Element name
nsPrefix Element namespace prefix name

3.2.3.9 override void Encode (Asn1XerEncoder buffer, System.String elemName) [virtual]

This method encodes an ASN.1 integer value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object
elemName Element name

Reimplemented from [Asn1Type](#).

3.2.3.10 override void Encode (Asn1PerEncodeBuffer buffer) [virtual]

This method encodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.2.3.11 **override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method encodes an ASN.1 integer value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object
explicitTagging Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.2.3.12 **static internal int EncodeValue (Asn1EncodeBuffer *buffer*, BigInteger *ivalue*, bool *doCopy*) [static, protected]**

This method encodes an ASN.1 integer value's contents in accordance with either the ASN.1 Basic Encoding Rules (BER) or Packed Encoding Rules (PER).

Parameters

buffer Encode message buffer object
ivalue Integer value to encode
doCopy Encode the copy of the value

Returns

Length of encoded component

3.2.3.13 **override bool Equals (System.Object *value*)**

This method compares this value to the given [Asn1BigInteger](#) value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1BigInteger](#).

Returns

`true` if the specified Object is equal to the current Object; otherwise, `false`.

3.2.3.14 **virtual bool Equals (long *value*) [virtual]**

This method compares this value to the given integer value for equality.

Parameters

value The long value to compare with the current Object.

Returns

`true` if the specified long value is equal to the current Object; otherwise, `false`.

3.2.3.15 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.2.3.16 override System.String ToString ()

This method will return a string representation of the integer value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

3.2.4 Member Data Documentation

3.2.4.1 new readonly Asn1Tag _TAG = new Asn1Tag(Asn1Tag.UNIV, Asn1Tag.PRIM, Asn1Type.INTEGER) [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 2).

Reimplemented from [Asn1Type](#).

3.2.4.2 BigInteger mValue

The magnitude of this [Asn1BigInteger](#), in *big-endian* order: the zeroth element of this array is the most-significant int of the magnitude. The magnitude must be "minimal" in that the most-significant int (`mValue[0]`) must be non-zero. This is necessary to ensure that there is exactly one representation for each [Asn1BigInteger](#) value. Note that this implies that the [Asn1BigInteger](#) zero has a zero-length mValue array.

3.3 Asn1BitString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Types

- enum [StringFormat](#)

Public Member Functions

- [Asn1BitString](#) (System.Collections.BitArray bitArray)
- [Asn1BitString](#) (System.String value_)
- [Asn1BitString](#) (bool[] bitValues)
- [Asn1BitString](#) (int numbits_, byte[] data)
- [Asn1BitString](#) ()
- virtual void [Clear](#) (int bitno)
- void [Decode](#) (Asn1MderDecodeBuffer buffer, int length)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, long upper)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix, System.String[] namedbits, int[] namedbitindex)
- virtual void [Encode](#) (Asn1XerEncoder buffer, System.String elemName, System.String[] namedbits, int[] namedbitindex)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- void [Encode](#) (Asn1MderOutputStream outs, int length)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (int nbits, byte[] value)
- virtual bool [Get](#) (int bitno)
- override int [GetHashCode](#) ()
- virtual bool [IsNamedBitStr](#) (System.String buffer)
- virtual void [Set](#) (int bitno)
- virtual void [Set](#) (int bitno, bool value)
- virtual bool[] [ToBoolArray](#) ()
- virtual System.String [ToHexString](#) ()
- override System.String [ToString](#) ()

Public Attributes

- byte[] [mValue](#)
- int [numbits](#)
- bool [trimZeroBits](#)

Static Public Attributes

- static new readonly [Asn1Tag _TAG](#)
- static [StringFormat mStringFormat](#) = StringFormat.HEXBIN

Properties

- override int [Length](#) [get]
- virtual bool [this](#) [int bitno] [get, set]

3.3.1 Detailed Description

This is a container class for holding the components of an ASN.1 bit string value.

3.3.2 Member Enumeration Documentation

3.3.2.1 enum StringFormat

Defines possible string fomrats.

The HEX constant describes the string format as hex digit value (e.g. 0123456789ABCDEF).

The BITS constant describes the string format as binary digit value (e.g. only 0 and 1 digits).

The ASN1VALUE constant describes the string format as hex or binary digit value. The binary string value will end with letter 'B' and hex string value will end with letter 'H' (e.g. '0101'B or '11'H). If the number of bits is less than or equal to 16, than it will be printed as Binary digits, else as Hex digits.

3.3.3 Constructor & Destructor Documentation

3.3.3.1 Asn1BitString ()

This constructor creates an empty bit string that can be used in a Decode method call to receive a bit string value.

3.3.3.2 Asn1BitString (int *numbits_*, byte[] *data*)

This constructor initializes a bit string with the given number of bits and data.

Parameters

numbits_ Number of bits

data Binary bit string contents

3.3.3.3 Asn1BitString (bool[] *bitValues*)

This constructor initializes a bit string from the given boolean array. Each array position corresponds to a bit in the bit string.

Parameters

bitValues The boolean array

3.3.3.4 Asn1BitString (System.String *value_*)

This constructor parses the given ASN.1 value text (either a binary or hex data string) and assigns the values to the internal bit string.

Examples of valid value formats are as follows:

Binary string: '11010010111001'B

Hex string: '0fa56920014abc'H

Parameters

value_ The ASN.1 value specification text

3.3.3.5 Asn1BitString (System.Collections.BitArray *bitArray*)

This constructor initializes a bit string from the given BitSet object.

Parameters

bitArray C# BitArray object

3.3.4 Member Function Documentation

3.3.4.1 virtual void Clear (int *bitno*) [virtual]

This method clears the given bit in the bit string.

Parameters

bitno The zero-based index of the bit to clear. The bit numbers start at zero and with the MSB of the first byte and progress from left to right.

3.3.4.2 void Decode (Asn1MderDecodeBuffer *buffer*, int *length*)

Decode a BIT STRING from the MDER encoding into this object. Exactly the given length of bits will be decoded.

Parameters

length This should be 8, 16, or 32, as these are the only lengths MDER supports. However, this is not checked here as it should be able to be checked at code generation time.

3.3.4.3 virtual void Decode (Asn1PerDecodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method decodes a sized ASN.1 bit string value using the packed encoding rules (PER).

Parameters

buffer Decode message buffer object

lower Lower bound (inclusive) of size constraint

upper Upper bound (inclusive) of size constraint

3.3.4.4 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 bit string value using the packed encoding rules (PER). The string is assumed to not contain a size constraint.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

3.3.4.5 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 bit string value using the BER or DER encoding rules. The UNIVERSAL tag value and length are decoded if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.3.4.6 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes ASN.1 bit string type using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.3.4.7 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes ASN.1 bit string type using the XML decoding as specified in the XML Schema standard.

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.3.4.8 virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, long *upper*) [virtual]

This method encodes a size-constrained ASN.1 bit string value using the packed encoding rules (PER) into the stream. The value to be encoded is stored in the 'numbits' and 'mValue' public member variables within this class.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object
lower Lower bound (inclusive) of size constraint
upper Upper bound (inclusive) of size constraint

Exceptions

Asn1Exception Thrown, if operation is failed.

3.3.4.9 override void Encode (Asn1PerOutputStream outs) [virtual]

This method encodes an unconstrained ASN.1 bit string value using the packed encoding rules (PER) into the stream. The value to be encoded is stored in the 'numbits' and 'mValue' public member variables within this class.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.3.4.10 override void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to the stream an ASN.1 bit string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

outs BER Output Stream object
explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.3.4.11 virtual void Encode (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix) [virtual]

This method encodes ASN.1 bit string type using the XML Encoding as specified in the XML Schema standard.

Parameters

buffer Encode message buffer object
elemName XML element name used to wrap string
nsPrefix XML element namespace name

3.3.4.12 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*, System.String[] *namedbits*, int[] *namedbitindex*) [virtual]

This method encodes ASN.1 bit string type using the XML Encoding as specified in the XML Schema standard.

Parameters

- buffer* Encode message buffer object
- elemName* XML element name used to wrap string
- nsPrefix* XML element namespace name
- namedbits* Array of named bits
- namedbitindex* Array of named bits index values

3.3.4.13 virtual void Encode (Asn1XerEncoder *buffer*, System.String *elemName*, System.String[] *namedbits*, int[] *namedbitindex*) [virtual]

This method encodes ASN.1 bit string type using the XML Encoding as specified in the itu-t XER standard.

Parameters

- buffer* Encode message buffer object
- elemName* XML element name used to wrap string
- namedbits* Array of named bits
- namedbitindex* Array of named bits index values

3.3.4.14 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes ASN.1 bit string type using the XML encoding rules (XER).

Parameters

- buffer* Encode message buffer object
- elemName* XML element name used to wrap string

Reimplemented from [Asn1Type](#).

3.3.4.15 void Encode (Asn1MderOutputStream *outs*, int *length*)

Encode this BIT STRING into the MDER encoding. The length of this BIT STRING must match the given length.

Parameters

- length* This should be 8, 16, or 32, as these are the only lengths MDER supports. However, this is not checked here as it should be able to be checked at code generation time. We only check here that the actual and given lengths match.

3.3.4.16 virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method encodes a size-constrained ASN.1 bit string value using the packed encoding rules (PER). The value to be encoded is stored in the 'numbits' and 'mValue' public member variables within this class.

Parameters

- buffer* Encode message buffer object
- lower* Lower bound (inclusive) of size constraint
- upper* Upper bound (inclusive) of size constraint

3.3.4.17 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an unconstrained ASN.1 bit string value using the packed encoding rules (PER). The value to be encoded is stored in the 'numbits' and 'mValue' public member variables within this class.

Parameters

- buffer* Encode message buffer object

Reimplemented from [Asn1Type](#).

3.3.4.18 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 bit string value using the BER or DER encoding rules. The UNIVERSAL tag value and length are encoded if explicit tagging is specified.

Parameters

- buffer* Encode message buffer object
- explicitTagging* Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.3.4.19 override bool Equals (System.Object *value*)

This method compares this bit string value to the given value for equality. This method assumes all unused bits in the last byte are set to zero.

Parameters

- value* The Object to compare with the current Object. Object should be instance of [Asn1BitString](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

3.3.4.20 virtual bool Equals (int *nbits*, byte[] *value*) [virtual]

This method compares this bit string value to the given value for equality. This method assumes all unused bits in the last byte are set to zero.

Parameters

nbits The number of bits to compare from the byte array.

value The byte array to compare with the current Object.

Returns

true if the specified bit array is equal to the current Object; otherwise, false.

3.3.4.21 virtual bool Get (int *bitno*) [virtual]

Gets the value of the bit at a specific position in the bit array.

Parameters

bitno The zero-based index of the bit to get. The bit numbers start at zero and with the MSB of the first byte and progress from left to right.

Returns

true if bit is set; otherwise false.

3.3.4.22 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.3.4.23 virtual bool IsNamedBitStr (System.String *buffer*) [virtual]

This method determines is the input character string represented as named bit string or as bits sequence. It is used for XML decoding.

Parameters

buffer Bit string as string to be tested.

Returns

true, if bit string is represented as sequece of identifiers.

3.3.4.24 virtual void Set (int *bitno*) [virtual]

This method will set the given bit number to one (1). It will expand the existing bit array if it needs to.

Parameters

bitno The zero-based index of the bit to set. The bit numbers start at zero and with the MSB of the first byte and progress from left to right.

3.3.4.25 virtual void Set (int *bitno*, bool *value*) [virtual]

This method sets the given bit number in the bit string with given value. It will expand the existing bit array if it needs to.

Parameters

bitno The zero-based index of the bit to set. The bit numbers start at zero and with the MSB of the first byte and progress from left to right.

value The Boolean value to assign to the bit.

3.3.4.26 virtual bool [] ToBoolArray () [virtual]

This method converts the bit string stored in this object to a boolean array.

Returns

Boolean array value

3.3.4.27 virtual System.String ToHexString () [virtual]

This method will return a hex string representation of the bit string value. The output format is a string of hex bytes with no extra delimiting characters (ex. 0D56EF).

Returns

Stringified representation of the value

3.3.4.28 override System.String ToString ()

This method will return a string representation of the bit string value. The output format is a string of hex digits/binary digits according to the value set for **mStringFormat** variable.

Returns

String representation of the value

3.3.5 Member Data Documentation

3.3.5.1 new readonly Asn1Tag _TAG [static]

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 3).

Reimplemented from [Asn1Type](#).

3.3.5.2 `StringFormat mStringFormat = StringFormat.HEXBIN` `[static]`

The `mStringFormat` variable can be used to set the string format for `print()` or event handler calls or `toString()` functions. The possible options are: `HEX`, `BITS`, `ASN1VALUE` `HEX` is the default format.

3.3.5.3 `byte [] mValue`

This variable holds the bit string value. These are the bits that are encoded when `encode` is invoked. It is also where the decoded bit string is stored after a `Decode` operation.

3.3.5.4 `int numbits`

This variable contains the number of bits in the bit string value.

3.3.5.5 `bool trimZeroBits`

This variable tells whether or not to trim zero bits at the end of a bit string encoding. In `CER` and `DER`, it is required to trim trailing zero bits if the bit string is a `Named Bit String`.

3.3.6 Property Documentation

3.3.6.1 `override int Length` `[get]`

Gets the length of the `BIT STRING` in bits.

Value: Number of bits.

Reimplemented from [Asn1Type](#).

3.3.6.2 `virtual bool this[int bitno]` `[get, set]`

Gets or Sets the given bit in the bit string. It will expand the existing bit array if it needs to set the bit value.

Parameters

bitno The position of the bit in bit array

Value: true if bit is set; otherwise false.

3.4 Asn1BMPString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1CharString](#).

Public Member Functions

- [Asn1BMPString](#) (System.String data)
- [Asn1BMPString](#) ()
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, [Asn1CharSet](#) charSet)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [Encode](#) (Asn1PerOutputStream outs, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Encode](#) (Asn1PerOutputStream outs, [Asn1CharSet](#) charSet)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, [Asn1CharSet](#) charSet)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Public Attributes

- const int [BITSPERCHAR](#) = 16

Static Public Attributes

- static new readonly [Asn1Tag _TAG](#)

3.4.1 Detailed Description

This is a container class for holding the components of an ASN.1 BMP string value.

3.4.2 Constructor & Destructor Documentation

3.4.2.1 [Asn1BMPString](#) ()

The default constructor creates an empty string object.

3.4.2.2 [Asn1BMPString](#) (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string value.

Parameters

- data* string representation of BMPString

3.4.3 Member Function Documentation

3.4.3.1 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the Decode method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes both a size constraint and permitted alphabet constraint are present.

The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.4.3.2 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Asn1CharSet *charSet*) [virtual]

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but allows a permitted alphabet character set to be specified. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

3.4.3.3 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

3.4.3.4 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 BMP string value including the UNIVERSAL tag value and length if explicit tagging is specified. This string type uses 16-bit characters.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.4.3.5 virtual void Encode (Asn1PerOutputStream outs, Asn1CharSet charSet, long lower, long upper) [virtual]

This overloaded version of the encode method encodes an ASN.1 BMP string value in accordance with the packed encoding rules (PER). This version of the method assumes both a size constraint and permitted alphabet constraint are present.

The value to encode is stored in the public `mValue` member variable.

Also throws any exception thrown by the underlying `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

charSet Object representing the permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.4.3.6 virtual void Encode (Asn1PerOutputStream outs, Asn1CharSet charSet) [virtual]

This method encodes an ASN.1 BMP string value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Also throws any exception thrown by the underlying `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

charSet Object representing permitted alphabet constraint character set (optional)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.4.3.7 override void Encode (Asn1PerOutputStream outs) [virtual]

This method encodes an ASN.1 BMP string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Also throws any exception thrown by the underlying `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.4.3.8 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 BMP string including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.4.3.9 virtual void Encode (Asn1PerEncodeBuffer *buffer*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the encode method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes both a size constraint and permitted alphabet constraint are present.

The value to encode is stored in the public `mValue` member variable.

Parameters

buffer Encode message buffer object

charSet Object representing the permitted alphabet constraint character set

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.4.3.10 virtual void Encode (Asn1PerEncodeBuffer *buffer*, Asn1CharSet *charSet*) [virtual]

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Encode message buffer object

charSet Object representing permitted alphabet constraint character set (optional)

3.4.3.11 **override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]**

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

3.4.3.12 **override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method encodes an ASN.1 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.4.4 **Member Data Documentation**

3.4.4.1 **new readonly Asn1Tag _TAG [static]**

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 30).

Reimplemented from [Asn1Type](#).

3.4.4.2 **const int BITSPERCHAR = 16**

The `BITSPERCHAR` constant specifies the number of bits per character for PER (aligned or unaligned).

3.5 Asn1Boolean Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1Boolean](#) (bool value_)
- [Asn1Boolean](#) ()
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- void [Encode](#) (Asn1XmlEncoder buffer, String elemName, String nsPrefix, bool asText)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- virtual void [Encode](#) (Asn1XerEncodeBuffer buffer)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual void [EncodeAttribute](#) (Asn1XmlEncoder buffer, System.String attrName)
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (bool value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()

Static Public Member Functions

- static void [setTrueEncodedByte](#) (byte b)

Public Attributes

- bool [mValue](#)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)
- static readonly [Asn1Boolean FALSE_VALUE](#) = new [Asn1Boolean](#)(false)
- static readonly [Asn1Boolean TRUE_VALUE](#) = new [Asn1Boolean](#)(true)

3.5.1 Detailed Description

This class represents the ASN.1 BOOLEAN built-in type.

3.5.2 Constructor & Destructor Documentation

3.5.2.1 Asn1Boolean ()

The default constructor sets the boolean value to false.

3.5.2.2 Asn1Boolean (bool *value_*)

This constructor creates a boolean object from a boolean value.

Parameters

value_ Boolean value

3.5.3 Member Function Documentation

3.5.3.1 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 boolean value using

the Packed Encoding Rules (PER).

The decoded result is stored in the public member `mValue`

in this object.

Parameters

buffer PER Decode message buffer object

Reimplemented from [Asn1Type](#).

3.5.3.2 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 boolean value including the UNIVERSAL

tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER) or the Distinguished Encoding Rules (DER).

The decoded result is stored in the public member `mValue`

in this object.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Returns

Decoded boolean value

Reimplemented from [Asn1Type](#).

3.5.3.3 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 boolean value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.5.3.4 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 boolean value using the XML Schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.5.3.5 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 boolean value using the Packed Encoding Rules (PER).

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Encode message stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.5.3.6 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 boolean value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, exception thrown by the underlying System.IO.Stream object.

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.5.3.7 void Encode (Asn1XmlEncoder *buffer*, String *elemName*, String *nsPrefix*, bool *asText*)

This method encodes an ASN.1 boolean value. It is for use with extended-XER.

Parameters

buffer Encode message buffer object

elemName Element name for optional surrounding element.

nsPrefix XML element name space prefix

asText If true, encode as text. Otherwise, encode as an empty element.

3.5.3.8 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 boolean value according to the Obj-Sys XML encoding rules. It encodes the value as XML text.

Parameters

buffer Encode message buffer object

elemName Element name for optional surrounding element.

nsPrefix Element namespace prefix value

3.5.3.9 virtual void Encode (Asn1XerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 boolean value using the XML encoding rules (XER). This method does not add start and end tags (<tag> and </tag>), only value is encoded (<true/> or <false/>).

Parameters

buffer Encode message buffer object

3.5.3.10 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 boolean value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1Type](#).

3.5.3.11 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 boolean value using the Packed Encoding Rules (PER).

Parameters

buffer PER Encode message buffer object

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.5.3.12 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 boolean value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER) or the Distinguished Encoding Rules (DER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length (in octets) of encoded component

Reimplemented from [Asn1Type](#).

3.5.3.13 virtual void EncodeAttribute (Asn1XmlEncoder *buffer*, System.String *attrName*) [virtual]

This method encodes an ASN.1 boolean value using the XML Encoding as specified in the W3C XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

attrName Element name

3.5.3.14 override bool Equals (System.Object *value*)

This method compares this boolean value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1Boolean](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

3.5.3.15 virtual bool Equals (bool *value*) [virtual]

This method compares this boolean value to the given value for equality.

Parameters

value The bool value to compare with the current Object.

Returns

true if the specified bool value is equal to the current Object; otherwise, false.

3.5.3.16 **override int GetHashCode ()**

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.5.3.17 **static void setTrueEncodedByte (byte *b*) [static]**

This method sets the byte value that represents the boolean value TRUE. If a zero byte (0x00) is passed, the value is transparently set to 0xFF, the valid representation for BER, CER, and DER.

Parameters

b The byte value to set.

3.5.3.18 **override System.String ToString ()**

This method will return a string representation of the boolean value. The format is the ASN.1 value format for this type.

Returns

Stringified representation of the value

3.5.4 **Member Data Documentation**

3.5.4.1 **new readonly Asn1Tag _TAG [static]**

The _TAG constant describes the universal tag for this data type (UNIVERSAL 1).

Reimplemented from [Asn1Type](#).

3.5.4.2 **readonly Asn1Boolean FALSE_VALUE = new Asn1Boolean(false) [static]**

The FALSE_VALUE constant represents a boolean FALSE value.

3.5.4.3 **bool mValue**

This public member variable is where the boolean value is stored. This is the value that is encoded when one of the encode methods is called. It is also where the decoded result is stored when a Decode method is called.

3.5.4.4 **readonly Asn1Boolean TRUE_VALUE = new Asn1Boolean(true) [static]**

The TRUE_VALUE constant represents a boolean TRUE value.

3.6 Asn1CharRange Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1CharSet](#).

Public Member Functions

- [Asn1CharRange](#) (int lower, int upper)
- override int [GetCharAtIndex](#) (int index)
- override int [GetCharIndex](#) (int charValue)
- override bool [validate](#) (String s)

Protected Attributes

- internal int [mLower](#)
- internal int [mUpper](#)

Properties

- override int [MaxValue](#) [get]

3.6.1 Detailed Description

This class is used to represent a permitted alphabet that is specified

as a large, continuous range of characters. An example of this can be found in the following extract from T.124:

```
simpleTextFirstCharacter UniversalString ::= {0, 0, 0, 0}
```

```
simpleTextLastCharacter UniversalString ::= {0, 0, 0, 255}
```

```
SimpleTextString ::= BMPString (SIZE (0..255))
```

```
(FROM (simpleTextFirstCharacter..simpleTextLastCharacter))
```

This class is mainly for internal use by the compiler when generating

methods that encode/Decode PER character string components containing permitted alphabet constraints.

3.6.2 Constructor & Destructor Documentation

3.6.2.1 Asn1CharRange (int *lower*, int *upper*)

This constructor sets the range values.

Parameters

lower Range lower value

upper Range upper value

3.6.3 Member Function Documentation

3.6.3.1 override int GetCharAtIndex (int *index*) [virtual]

This method will fetch the character from the permitted alphabet at the given index.

Parameters

index Index of character within the character set

Returns

Character at given index

Exceptions

[Asn1ConsVioException](#) Index not within define range

Implements [Asn1CharSet](#).

3.6.3.2 override int GetCharIndex (int *charValue*) [virtual]

This method will determine the index of the given character within the permitted alphabet character set.

Parameters

charValue Character value to search for

Returns

Index of character

Exceptions

[Asn1ConsVioException](#) Character not found in set

Implements [Asn1CharSet](#).

3.6.3.3 override bool validate (String *s*) [virtual]

This method will validate a character string by comparing its contents to the character range. Each character in the string is checked against the range. If it exceeds the upper or lower limit of the range, false is returned. Otherwise true is returned.

Parameters

s The string to be validated.

Returns

False if the string contains invalid characters; true otherwise.

Implements [Asn1CharSet](#).

3.6.4 Member Data Documentation

3.6.4.1 internal int mLower [protected]

This variable represents the lower value of the range.

3.6.4.2 internal int mUpper [protected]

This variable represents the upper value of the range.

3.6.5 Property Documentation

3.6.5.1 override int MaxValue [get]

Gets the maximum value of character within the given permitted alphabet character set.

Value: Upper Bound Character or Character with max int value

Reimplemented from [Asn1CharSet](#).

3.7 Asn1CharSet Class Reference

Inherited by [Asn1BMPStringCharset](#), [Asn1CharRange](#), [Asn1DiscreteCharset](#), [Asn1IA5StringCharset](#), [Asn1NumericStringCharset](#), [Asn1PrintableStringCharset](#), and [Asn1VisibleStringCharset](#).

Public Member Functions

- abstract int [GetCharAtIndex](#) (int index)
- abstract int [GetCharIndex](#) (int charValue)
- virtual int [GetNumBitsPerChar](#) (bool aligned)
- abstract bool [validate](#) (String s)

Protected Member Functions

- internal [Asn1CharSet](#) (int nchars)

Protected Attributes

- internal int [mABitsPerChar](#)
- internal int [mUBitsPerChar](#)

Properties

- abstract int [MaxValue](#) [get]

3.7.1 Detailed Description

This is the base class for representing character sets that are defined in ASN.1 permitted alphabet constraints.

3.7.2 Constructor & Destructor Documentation

3.7.2.1 internal Asn1CharSet (int *nchars*) [protected]

This constructor sets the number of bits-per-character values based on the given number of characters in the character set.

Parameters

nchars Number of characters in the character set

3.7.3 Member Function Documentation

3.7.3.1 abstract int GetCharAtIndex (int *index*) [pure virtual]

This method will fetch the character from the permitted alphabet at the given index.

Parameters

index Index of character within the character set

Returns

Character at given index

Exceptions

[*Asn1ConsVioException*](#) Index not within define range

Implemented in [Asn1CharRange](#), and [Asn1DiscreteCharSet](#).

3.7.3.2 abstract int GetCharIndex (int *charValue*) [pure virtual]

This method will determine the index of the given character within the permitted alphabet character set.

Parameters

charValue Character value to search for

Returns

Index of character

Exceptions

[*Asn1ConsVioException*](#) Character not found in set

Implemented in [Asn1CharRange](#), and [Asn1DiscreteCharSet](#).

3.7.3.3 virtual int GetNumBitsPerChar (bool *aligned*) [virtual]

This method will return the number of bits-per-character.

Parameters

aligned Boolean value indicating whether number of aligned (true) or unaligned (false) characters should be returned.

Returns

Number of bits-per-character

3.7.3.4 abstract bool validate (String *s*) [pure virtual]

This method will validate a character string by comparing its contents to the character set. If a character string contains characters that are not in the character set, this method will return false. Otherwise it returns true.

Parameters

s The string to be validated.

Returns

False if the string contains invalid characters; true otherwise.

Implemented in [Asn1CharRange](#), and [Asn1DiscreteCharSet](#).

3.7.4 Member Data Documentation

3.7.4.1 internal int mABitsPerChar [protected]

This variable holds number of bits-per-character (PER aligned).

3.7.4.2 internal int mUBitsPerChar [protected]

This variable holds number of bits-per-character (PER unaligned).

3.7.5 Property Documentation

3.7.5.1 abstract int MaxValue [get]

Gets the maximum value of the character within the given permitted alphabet character set.

Value: Upper Bound Character or Character with max int value

Reimplemented in [Asn1CharRange](#), and [Asn1DiscreteCharSet](#).

3.8 Asn1CharString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Inherited by [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1UTF8String](#), and [Asn1VarWidthCharString](#).

Public Member Functions

- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override bool [Equals](#) (System.Object value)
- bool [Equals](#) (System.String value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()
- bool [validate](#) ([Asn1CharSet](#) charSet)

Public Attributes

- System.String [mValue](#)

Protected Member Functions

- internal [Asn1CharString](#) (System.String data, short typeCode)
- internal [Asn1CharString](#) (short typeCode)
- virtual internal void [Decode](#) (Asn1PerDecodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual internal void [Decode](#) (Asn1PerDecodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet)
- virtual internal void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength, [Asn1Tag](#) tag)
- virtual internal void [Encode](#) (Asn1PerEncodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual internal void [Encode](#) (Asn1PerEncodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet)
- virtual internal int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging, [Asn1Tag](#) tag)

Protected Attributes

- internal System.Text.StringBuilder [mStringBuffer](#)

Properties

- override int [Length](#) [get]

3.8.1 Detailed Description

This is a container class for holding the components of an ASN.1 character string value. Subclasses are defined for all of the different string types.

3.8.2 Constructor & Destructor Documentation

3.8.2.1 internal Asn1CharString (short *typeCode*) [protected]

This constructor creates an empty string that can be used in a Decode method call to receive a string value.

Parameters

typeCode Universal ID code for ASN.1 character string

3.8.2.2 internal Asn1CharString (System.String *data*, short *typeCode*) [protected]

This constructor initializes a character string from the given string data.

Parameters

data Character string

typeCode Universal ID code for ASN.1 character string

3.8.3 Member Function Documentation

3.8.3.1 virtual internal void Decode (Asn1PerDecodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, long *lower*, long *upper*) [protected, virtual]

This overloaded version of the Decode method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The decoded result is stored in the public `mValue` member variable.

Parameters

buffer Decode message buffer object

abpc Number of bits per character (aligned)

ubpc Number of bits per character (unaligned)

charSet Object representing permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.8.3.2 virtual internal void Decode (Asn1PerDecodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [protected, virtual]

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes that a permitted alphabet constraint has been specified that would reduce the the number of bits-per-character from the default character set. It also assumes a general length determinant is present (i.e. there is not size constraint). The decoded result is stored in the public `mValue` member variable.

Parameters

buffer Decode message buffer object

abpc Number of bits per character (aligned)

ubpc Number of bits per character (unaligned)

charSet Object representing the permitted alphabet constraint character set (optional)

3.8.3.3 virtual internal void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*, Asn1Tag *tag*) [protected, virtual]

This method decodes an ASN.1 character string value including the UNIVERSAL tag value and length if explicit tagging is specified. It is a protected method that can only be accessed by objects subclassed from this type.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

tag Universal tag to apply

Reimplemented in [Asn1Time](#).

3.8.3.4 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.8.3.5 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. using the XML Schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

Reimplemented in [Asn1Time](#).

3.8.3.6 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName XML element name used to wrap string

nsPrefix XML element namespace value

Reimplemented in [Asn1Real10](#), and [Asn1Time](#).

3.8.3.7 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName XML element name used to wrap string

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.8.3.8 virtual internal void Encode (Asn1PerEncodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, long *lower*, long *upper*) [protected, virtual]

This overloaded version of the encode method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The value to encode is stored in the public `mValue` member variable.

Parameters

buffer Encode message buffer object

abpc Number of bits per character (aligned)

ubpc Number of bits per character (unaligned)

charSet Object representing the permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.8.3.9 virtual internal void Encode (Asn1PerEncodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [protected, virtual]

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable.

Parameters

buffer Encode message buffer object

abpc Number of bits per character (aligned)

ubpc Number of bits per character (unaligned)

charSet Object representing the permitted alphabet constraint character set (optional)

3.8.3.10 virtual internal int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*, Asn1Tag *tag*) [protected, virtual]

This method encodes ASN.1 8-bit character string types including IA5String, PrintableString, NumericString, etc. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified (the universal identifier must be provided by the caller).

Parameters

buffer Encode message buffer object
explicitTagging Flag indicating explicit tagging should be done
tag Universal tag to apply

Returns

Length in octets of encoded component

Reimplemented in [Asn1Time](#).

3.8.3.11 override bool Equals (System.Object *value*)

This method compares this character string value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1CharString](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

Reimplemented in [Asn1Time](#).

3.8.3.12 bool Equals (System.String *value*)

This method compares this character string value to the given value for equality.

Parameters

value The String value to compare with the current Object.

Returns

true if the specified string is equal to the current Object; otherwise, false.

3.8.3.13 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

Reimplemented in [Asn1Time](#).

3.8.3.14 **override System.String ToString ()**

This method will return a string representation of the value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

3.8.3.15 **bool validate (Asn1CharSet charSet)**

This method will attempt to validate a string against its internal character set.

Returns

True or False.

3.8.4 **Member Data Documentation**

3.8.4.1 **internal System.Text.StringBuilder mStringBuffer [protected]**

The `mStringBuffer` member variable is used to do internal operations on a string being encoded or decoded.

3.8.4.2 **System.String mValue**

The `mValue` public member variable is used to hold the string value to be encoded or the results of a Decode operation.

3.8.5 **Property Documentation**

3.8.5.1 **override int Length [get]**

Gets the length of the character string in characters.

Value: Number of characters.

Reimplemented from [Asn1Type](#).

3.9 Asn1Choice Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1Choice](#) ()
- override bool [Equals](#) (System.Object value)
- virtual [Asn1Type GetElement](#) ()
- override int [GetHashCode](#) ()
- virtual void [SetElement](#) (int choiceID, [Asn1Type](#) element)

Protected Attributes

- internal int [choiceID](#)
- internal [Asn1Type](#) [element](#)

Properties

- virtual int [ChoiceID](#) [get]
- abstract System.String [ElemName](#) [get]

3.9.1 Detailed Description

This class represents the ASN.1 CHOICE built-in type.

3.9.2 Constructor & Destructor Documentation

3.9.2.1 Asn1Choice ()

The default constructor initializes the choiceID and value.

3.9.3 Member Function Documentation

3.9.3.1 override bool Equals (System.Object value)

This method compares this type element with the passed type element.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1Choice](#).

Returns

`true` if the specified Object is equal to the current Object; otherwise, `false`.

3.9.3.2 virtual Asn1Type GetElement () [virtual]

This method returns the element object.

Returns

element data member.

3.9.3.3 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.9.3.4 virtual void SetElement (int choiceID, Asn1Type element) [virtual]

This protected method sets the choice ID and value to the given values. Refer the Set_<element>() methods in compiler generated inherited classes.

Parameters

choiceID The identifier for element value. The identifier value can be defined by compiler-generated derived class.

element The element value. The possible value types can be defined by compiler-generated derived class.

3.9.4 Member Data Documentation

3.9.4.1 internal int choiceID [protected]

This member variable is where the selected choice option identifier is stored. This selects the choice option to be used. It is populated with one of the generated choice ID constants in a compiler-generated derived class.

3.9.4.2 internal Asn1Type element [protected]

This member variable is where the selected choice option value is stored. It can be accessed via the get and set methods in this class and in compiler-generated derived classes.

3.9.5 Property Documentation

3.9.5.1 virtual int ChoiceID [get]

Gets the choice identifier.

Value: choice option identifier

3.9.5.2 abstract System.String ElemName [get]

Gets the name of the selected element. A concrete version is generated by the compiler-generated derived class.

Value: choice option name

3.10 Asn1ChoiceExt Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1OpenType](#).

Public Member Functions

- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Public Attributes

- short [choiceIndex](#)

3.10.1 Detailed Description

This is a container class for holding a CHOICE open type extension element. This class is used for an open type extension (i.e. a ... at the end of a constructed type or a ..., ... at some other point in a constructed type).

3.10.2 Member Function Documentation

3.10.2.1 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an open type extension in a CHOICE construct using the packed encoding rules (PER). This method will capture the extension item in an open type object and store it in the `mValue` public member list variable. The public member variable `choiceIndex` will be populated with the decoded choice index value.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1OctetString](#).

3.10.2.2 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an extension field using the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1OpenType](#).

3.10.2.3 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 open type value using the Packed Encoding Rules (PER).

Parameters

outs PER Output Stream object

Reimplemented from [Asn1OpenType](#).

3.10.2.4 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 open type extension value using the Basic Encoding Rules (BER).

Parameters

outs BER Output Stream object

explicitTagging Flag indicating element is explicitly tagged

Reimplemented from [Asn1OpenType](#).

3.10.2.5 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 open type extension value using the Packed Encoding Rules (PER).

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1OpenType](#).

3.10.2.6 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 open type extension value using the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating element is explicitly tagged

Returns

Length of encoded component

Reimplemented from [Asn1OpenType](#).

3.10.3 Member Data Documentation

3.10.3.1 short choiceIndex

The choice index value is used with the packed encoding rules (PER) when this object is used to encode/Decode a choice extension.

3.11 Asn1ConsVioException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1ConsVioException](#) (System.String varname, System.String value)
- [Asn1ConsVioException](#) (System.String varname, double value)
- [Asn1ConsVioException](#) (System.String varname, long value)

3.11.1 Detailed Description

This class defines the 'ASN.1 constraint violation' exception that is thrown when an element is parsed that is outside the bounds to a defined constraint..

3.11.2 Constructor & Destructor Documentation

3.11.2.1 Asn1ConsVioException (System.String *varname*, long *value*)

This constructor creates an exception object with a standard message based on the given variable name and value. The form of the message is "Element '*varname*' with value '*value*' violates defined constraint".

Parameters

varname Name of variable that violates constraint

value Value of variable

3.11.2.2 Asn1ConsVioException (System.String *varname*, double *value*)

This constructor creates an exception object with a standard message based on the given variable name and value. The form of the message is "Element '*varname*' with value '*value*' violates defined constraint".

Parameters

varname Name of variable that violates constraint

value Value of variable

3.11.2.3 Asn1ConsVioException (System.String *varname*, System.String *value*)

This constructor creates an exception object with a standard message based on the given variable name and value. The form of the message is "Element '*varname*' with value '*value*' violates defined constraint".

Parameters

varname Name of variable that violates constraint

value Value of variable

3.12 Asn1DecodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1MessageBuffer](#).

Public Member Functions

- virtual void [AddCaptureBuffer](#) (System.IO.MemoryStream buffer)
- virtual void [Capture](#) (int nbytes)
- virtual long [DecodeIntValue](#) (int length, bool signExtend)
- virtual int[] [DecodeOIDContents](#) (int llen)
- virtual int[] [DecodeRelOIDContents](#) (int llen)
- override System.IO.Stream [GetInputStream](#) ()
- virtual void [HexDump](#) ()
- virtual void [Mark](#) ()
- virtual void [Read](#) (byte[] buffer)
- virtual void [Read](#) (byte[] buffer, int offset, int nbytes)
- virtual int [Read](#) ()
- int [Read2Bytes](#) ()
- int [Read4Bytes](#) ()
- abstract int [ReadByte](#) ()
- virtual void [RemoveCaptureBuffer](#) (System.IO.MemoryStream buffer)
- virtual void [Reset](#) ()
- virtual void [SetInputStream](#) (byte[] msgdata, int offset, int length)
- virtual long [Skip](#) (long nbytes)

Protected Member Functions

- virtual internal void [Init](#) ()

Protected Attributes

- internal int [mByteCount](#)

Properties

- virtual int [ByteCount](#) [get]
- bool [LazyOpenTypeDecode](#) [get, set]

3.12.1 Detailed Description

This is the base class to specific Decode buffer classes for the different types of encoding rules (BER, DER and PER).

3.12.2 Member Function Documentation

3.12.2.1 virtual void AddCaptureBuffer (System.IO.MemoryStream *buffer*) [virtual]

This method is used to add a capture buffer to the internal capture buffer list. A capture buffer is used to capture all bytes read from this position forward from the input stream.

Parameters

buffer Buffer into which captured bytes are to be stored

3.12.2.2 virtual void Capture (int *nbytes*) [virtual]

This method captures bytes from the input stream to a separate object for later analysis.

Parameters

nbytes Number of bytes to capture

3.12.2.3 virtual long DecodeIntValue (int *length*, bool *signExtend*) [virtual]

This method decodes the contents of an ASN.1 integer value. It can be used for either BER or PER decoding.

Parameters

length Length of encoded contents

signExtend Sign-extend the decoded value to form a 2's comp result

Returns

Decoded long integer value

3.12.2.4 virtual int [] DecodeOIDContents (int *llen*) [virtual]

This method decodes the contents of an ASN.1 object identifier value. It can be used for either BER or PER decoding.

Parameters

llen Length of encoded contents

Returns

Decoded object identifier value

3.12.2.5 virtual int [] DecodeRelOIDContents (int *llen*) [virtual]

This method decodes the contents of an ASN.1 relative object identifier value. It can be used for either BER or PER decoding.

Parameters

llen Length of encoded contents

Returns

Decoded object identifier value

3.12.2.6 override System.IO.Stream GetInputStream () [virtual]

This method returns a reference to the current current Decode input stream object.

Returns

New input stream object containing encoded message

Implements [Asn1MessageBuffer](#).

3.12.2.7 virtual void HexDump () [virtual]

This method provides a hex dump of the bytes in the message being decoded.

3.12.2.8 virtual internal void Init () [protected, virtual]

This method initializes the input stream for decoding.

3.12.2.9 virtual void Mark () [virtual]

This method is used to mark the current position in the input stream for retry processing.

3.12.2.10 virtual void Read (byte[] *buffer*) [virtual]

This version of the read method reads the number of bytes equal to the length of the given input buffer.

Throws, Exception thrown by C# System.IO.Stream for I/O error, for Stream as input data

Parameters

buffer the buffer into which the data is read

Exceptions

[Asn1EndOfBufferException](#) Thrown if at end-of-stream

3.12.2.11 virtual void Read (byte[] *buffer*, int *offset*, int *nbytes*) [virtual]

This version of the read method reads the given number of bytes from the current input stream and writes them to the specified byte array at the given offset. It also writes the data to all registered capture buffers.

Throws, Exception thrown by C# System.IO.Stream for I/O error for Stream as input data

Parameters

buffer the buffer into which the data is read

offset the start offset of the data

nbytes number of bytes to read

Exceptions

Asn1EndOfBufferException Thrown if at end-of-stream

3.12.2.12 virtual int Read () [virtual]

The read method reads a single byte from the current input stream and returns it to the caller. It will also write the byte out to all registered capture buffers.

Throws, Exception thrown by C# System.IO.Stream for I/O error for Stream as input data

Returns

byte that was read from the input stream

Exceptions

Asn1EndOfBufferException Thrown if at end-of-stream

3.12.2.13 int Read2Bytes ()

Read the next two bytes from the current input stream into an int, and return that int. The bytes of the int, from lowest to highest, will correspond to the bytes read from the stream, from last to first. The highest two bytes will be 0.

Each byte read will be written to all registered capture buffers.

Returns

an int representing the 2 bytes read, as described above.

Exceptions

Asn1EndOfBufferException if at end-of-stream

3.12.2.14 int Read4Bytes ()

Read the next four bytes from the current input stream into an int, and return that int. The bytes of the int, from lowest to highest, will correspond to the bytes read from the stream, from last to first.

Each byte read will be written to all registered capture buffers.

Returns

an int representing the 4 bytes read, as described above.

Exceptions

Asn1EndOfBufferException if at end-of-stream

3.12.2.15 **abstract int ReadByte () [pure virtual]**

This abstract method returns the next available 8-bit value from the input stream. It is implemented differently for BER/DER and PER to take into account odd alignments in PER.

Returns

Next 8-bit byte value from input stream

3.12.2.16 **virtual void RemoveCaptureBuffer (System.IO.MemoryStream *buffer*) [virtual]**

This method is used to remove a capture buffer from the internal capture buffer list. The add and remove methods can be used to get a set of raw bytes from the input stream for further processing.

Parameters

buffer Buffer in which captured bytes stored

3.12.2.17 **virtual void Reset () [virtual]**

This method is used to reset the current position in the decode buffer back to the location of the last 'mark' call.

3.12.2.18 **virtual void SetInputStream (byte[] *msgdata*, int *offset*, int *length*) [virtual]**

This method will set the input stream from which data is read. This version of the method allows a byte array containing encoded data to be specified.

Parameters

msgdata Byte array containing encoded message data

offset Starting offset of data in the byte array

length Length (in bytes) of the encoded data

3.12.2.19 **virtual long Skip (long *nbytes*) [virtual]**

This method will skip over the requested number of bytes in the input stream.

Parameters

nbytes Number of bytes to skip

Returns

Skipped number of bytes

3.12.3 **Member Data Documentation**

3.12.3.1 **internal int mByteCount [protected]**

This member variable holds the count of bytes currently read from the message being decoded or input stream.

3.12.4 Property Documentation

3.12.4.1 virtual int ByteCount [get]

Gets the count of bytes currently read from the message being decoded or input stream.

3.12.4.2 bool LazyOpenTypeDecode [get, set]

Lazy open type decoding. This property is relevant only when generating table constraint code (otherwise, open types cannot be decoded). Generated decode methods check this property to determine whether to decode open types or not. When lazy open type decoding is turned on, you can use the generated decodeOpenType* methods to decode open types (again, assuming table constraint code was generated).

3.13 Asn1DiscreteCharSet Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1CharSet](#).

Public Member Functions

- [Asn1DiscreteCharSet](#) (int[] charSet)
- [Asn1DiscreteCharSet](#) (System.String charSet)
- override int [GetCharAtIndex](#) (int index)
- override int [GetCharIndex](#) (int charValue)
- override bool [validate](#) (String s)

Protected Member Functions

- bool [helpValidate](#) (char c)

Properties

- override int [MaxValue](#) [get]

3.13.1 Detailed Description

This class is used to represent a discrete set of characters from a permitted alphabet.

3.13.2 Constructor & Destructor Documentation

3.13.2.1 Asn1DiscreteCharSet (System.String *charSet*)

This constructor sets the permitted alphabet character set

Parameters

charSet Permitted alphabet character set

3.13.2.2 Asn1DiscreteCharSet (int[] *charSet*)

This constructor sets the permitted alphabet character set

Parameters

charSet Permitted alphabet character set

3.13.3 Member Function Documentation

3.13.3.1 override int GetCharAtIndex (int *index*) [virtual]

This method will fetch the character from the permitted alphabet at the given index.

Parameters

index Index of character within the character set

Returns

Character at given index

Exceptions

Asn1ConsVioException Thrown if index not within define range

Implements [Asn1CharSet](#).

3.13.3.2 override int GetCharIndex (int *charValue*) [virtual]

This method will determine the index of the given character within the permitted alphabet character set.

Parameters

charValue Character value to search for

Returns

Index of character

Exceptions

Asn1ConsVioException thrown if 'charValue' not found in set

Implements [Asn1CharSet](#).

3.13.3.3 bool helpValidate (char *c*) [protected]

This function helps validate a character string by checking a character to see if it is in the character set. It returns false if a character is not contained in the set and true otherwise.

3.13.3.4 override bool validate (String *s*) [virtual]

This method will validate a character string by comparing its contents to the character set. If a character string contains characters that are not in the character set, this method will return false. Otherwise it returns true.

Parameters

s The string to be validated.

Returns

False if the string contains invalid characters; true otherwise.

Implements [Asn1CharSet](#).

3.13.4 Property Documentation

3.13.4.1 `override int MaxValue` [get]

Gets Upper Bound Character or Character with max int value. It will determine the maximum value of the given character within the permitted alphabet character set. As the charset is canonical order, max value is of the last character.

Reimplemented from [Asn1CharSet](#).

3.14 Asn1EncodeBuffer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1MessageBuffer](#).

Public Member Functions

- abstract void [BinDump](#) (System.IO.StreamWriter outs, System.String varName)
- virtual void [BinDump](#) (System.String varName)
- abstract void [Copy](#) (byte[] value)
- abstract void [Copy](#) (byte value)
- virtual void [HexDump](#) (System.IO.StreamWriter outs)
- virtual void [HexDump](#) ()
- abstract void [Reset](#) ()
- abstract void [Write](#) (System.IO.Stream outs)

Public Attributes

- const int [SIZE_INCREMENT](#) = 1024

Protected Member Functions

- virtual internal void [CheckSize](#) (int bytesRequired)
- virtual internal void [InitBuffer](#) (int sizeIncrement)

Protected Attributes

- internal int [mByteIndex](#)
- internal byte[] [mData](#)
- internal int [mSizeIncrement](#)

Properties

- abstract byte[] [MsgCopy](#) [get]
- abstract int [MsgLength](#) [get]

3.14.1 Detailed Description

This is the base class to specific encode buffer classes for the different types of encoding rules (BER, DER and PER).

3.14.2 Member Function Documentation

3.14.2.1 abstract void [BinDump](#) (System.IO.StreamWriter *outs*, System.String *varName*) [pure virtual]

This method dumps the encoded message in a human-readable format showing a bit trace of all fields to the given print output stream.

Parameters

outs Output will be written to this stream

varName Name of the Decoded ASN1 Type

3.14.2.2 virtual void BinDump (System.String varName) [virtual]

This method invokes an overloaded version of BinDump to dump the encoded message to standard output.

Parameters

varName Name of the Decoded ASN1 Type

3.14.2.3 virtual internal void CheckSize (int bytesRequired) [protected, virtual]

This method determines if the encode buffer can hold the requested number of bytes. If not, the buffer is expanded.

Parameters

bytesRequired Number of required bytes.

3.14.2.4 abstract void Copy (byte[] value) [pure virtual]

This method copies multiple bytes to the encode buffer

Parameters

value Array of bytes to copy to the encode buffer

3.14.2.5 abstract void Copy (byte value) [pure virtual]

This abstract method is used to copy a single byte to the encode buffer.

Parameters

value The byte value to copy

3.14.2.6 virtual void HexDump (System.IO.StreamWriter outs) [virtual]

This method dumps the encoded message in hex/ascii format to the given print output stream.

Parameters

outs Output stream object reference

3.14.2.7 virtual void HexDump () [virtual]

This method dumps the encoded message in hex/ascii format to the standard output stream.

3.14.2.8 virtual internal void InitBuffer (int *sizeIncrement*) [protected, virtual]

This method will initialize this class member variables.

Parameters

sizeIncrement Buffer size increment in bytes

3.14.2.9 abstract void Reset () [pure virtual]

This method resets the buffer to allow a new record to be encoded into it. Any previously encoded data is lost.

3.14.2.10 abstract void Write (System.IO.Stream *outs*) [pure virtual]

This method writes the encoded record to the given output stream.

Parameters

outs Output stream to which record is to be written

3.14.3 Member Data Documentation

3.14.3.1 internal int mByteIndex [protected]

This variable holds the position of the byte array for encode buffer.

3.14.3.2 internal byte [] mData [protected]

This variable holds the encoded data as byte array.

3.14.3.3 internal int mSizeIncrement [protected]

This variable holds the user defined buffer increment size. It defines initial size and size it will be incremented by each time the buffer expands.

3.14.3.4 const int SIZE_INCREMENT = 1024

This constant specifies the default size of the encode buffer and size it will be incremented by each time the buffer expands. It is currently set to 1024 bytes.

3.14.4 Property Documentation

3.14.4.1 abstract byte [] MsgCopy [get]

Gets the encoded message in a byte array. This is less efficient than the GetInputStream method because the message contents must be copied to a newly created byte array.

Value: byte array containing encoded message

3.14.4.2 abstract int MsgLength [get]

Gets the length (in bytes) of the encoded message component.

Value: length of encoded message component

3.15 Asn1EndOfBufferException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1EndOfBufferException](#) ([Asn1DecodeBuffer](#) *buffer*)

3.15.1 Detailed Description

This class defines the 'ASN.1 end of buffer' exception that is thrown when an unexpected end-of-buffer condition is encountered when decoding a message..

3.15.2 Constructor & Destructor Documentation

3.15.2.1 Asn1EndOfBufferException ([Asn1DecodeBuffer](#) *buffer*)

This constructor creates an exception object with a textual message describing the tag of the duplicate element..

Parameters

buffer Decode buffer object reference

3.16 Asn1Enumerated Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1Enumerated](#) (int value_)
- [Asn1Enumerated](#) ()
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, long upper)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, String elemName, String nsPrefix, bool asText)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- virtual void [Encode](#) (Asn1XerEncodeBuffer buffer)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (int value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()

Static Public Member Functions

- static int [ParseValue](#) (System.String value)

Public Attributes

- int [mValue](#)
- const int [UNDEFINED](#) = - 999

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.16.1 Detailed Description

This class represents the ASN.1 ENUMERATED built-in type. It is declared to be an abstract class and therefore cannot be used on its own. It must be extended by a specific enumerated type class.

3.16.2 Constructor & Destructor Documentation

3.16.2.1 Asn1Enumerated ()

The default constructor sets the enumerated value to undefined.

3.16.2.2 Asn1Enumerated (int *value_*)

This constructor creates an enumerated object from a integer value.

Parameters

value_ Integer value

3.16.3 Member Function Documentation

3.16.3.1 virtual void Decode (Asn1PerDecodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method decodes an ASN.1 enumerated value using the Packed Encoding Rules (PER). The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

lower Smallest enumerated value in the set

upper Largest enumerated value in the set

3.16.3.2 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 enumerated value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.16.3.3 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 enumerated value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded. The value is assumed to be clear text with wrapping element delimiters (i.e. "<" and ">") removed.

attrs Attributes string from element tag

3.16.3.4 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 enumerated value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.16.3.5 virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, long *upper*) [virtual]

This method encodes an ASN.1 enumerated value using the Packed Encoding Rules (PER).

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object

lower Smallest enumerated value in the set

upper Largest enumerated value in the set

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.16.3.6 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 enumerated value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.16.3.7 virtual void Encode (Asn1XmlEncoder *buffer*, String *elemName*, String *nsPrefix*, bool *asText*) [virtual]

This method encodes an ASN.1 enumerated value. It is for use with extended-XER.

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix XML element name space prefix

asText If true, encode the value as XML text, otherwise encode as an empty element.

3.16.3.8 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 enumerated value using the Obj-Sys XML Encoding rules. It encodes the value as XML text.

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

3.16.3.9 virtual void Encode (Asn1XerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 enumerated value using the XML encoding rules (XER). This method does not add start and end tags (<tag> and </tag>), only value is encoded (<val1/> or <val2/>).

Parameters

buffer Encode message buffer object

3.16.3.10 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 enumerated value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1Type](#).

3.16.3.11 virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method encodes an ASN.1 enumerated value using the Packed Encoding Rules (PER).

Parameters

buffer PER Encode message buffer object

lower Smallest enumerated value in the set

upper Largest enumerated value in the set

3.16.3.12 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 enumerated value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.16.3.13 override bool Equals (System.Object value)

This method compares this enumerated value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1Enumerated](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

3.16.3.14 virtual bool Equals (int value) [virtual]

This method compares this enumerated value to the given value for equality.

Parameters

value The int or enumerated value to compare with the current Object.

Returns

true if the specified int value is equal to the current Object; otherwise, false.

3.16.3.15 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.16.3.16 static int ParseValue (System.String value) [static]

This method will parse the given enumeration text and set the enumerated value. This method is implemented by the extending class for XER or XML code generation ONLY.

Parameters

value enumeration text

Returns

Stringified representation of the value

AB: don't make it abstract (it is only for XER)

3.16.3.17 override System.String ToString ()

This method will return the enumeration text for a given enumerated value.

Returns

Stringified representation of the value

3.16.4 Member Data Documentation

3.16.4.1 new readonly Asn1Tag _TAG [static]

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 10).

Reimplemented from [Asn1Type](#).

3.16.4.2 int mValue

This public member variable is where the enumerated value is stored. This is the value that is encoded when one of the encode methods is called. It is also where the decoded result is stored when a Decode method is called.

3.16.4.3 const int UNDEFINED = - 999

The `UNDEFINED` constant is stored in the `mValue` member variable when the value of this enumerated type is undetermined.

3.17 Asn1Exception Class Reference

Inherited by [Asn1ConsVioException](#), [Asn1EndOfBufferException](#), [Asn1InvalidArgException](#), [Asn1InvalidChoiceOptionException](#), [Asn1InvalidEnumException](#), [Asn1InvalidLengthException](#), [Asn1InvalidObjectIDException](#), [Asn1MissingRequiredException](#), [Asn1SeqOrderException](#), and [Asn1ValueParseException](#).

Public Member Functions

- [Asn1Exception](#) ([Asn1DecodeBuffer](#) buffer, System.String message)
- [Asn1Exception](#) (System.String message, System.Exception innerException)
- [Asn1Exception](#) (System.String message)

3.17.1 Detailed Description

This class defines a generic ASN.1 exception for use as a base class for exceptions common to all encode/decode operations. Specific exceptions for BER, DER, and PER encoding and decoding are subclassed from this base class..

3.17.2 Constructor & Destructor Documentation

3.17.2.1 Asn1Exception (System.String message)

This constructor passes the given message text to the superclass.

Parameters

message Error message text

3.17.2.2 Asn1Exception (System.String message, System.Exception innerException)

This constructor passes the given message text to the superclass.

Parameters

message Error message text

innerException The exception that is the cause of the current exception.

3.17.2.3 Asn1Exception (Asn1DecodeBuffer buffer, System.String message)

This constructor creates the base exception object and captures the current buffer offset from the Decode buffer..

Parameters

buffer ASN.1 Decode buffer object reference

message Error message text

3.18 Asn1GeneralizedTime Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Time](#).

Public Member Functions

- [Asn1GeneralizedTime](#) (System.String data, bool useDerRules)
- [Asn1GeneralizedTime](#) (System.String data)
- [Asn1GeneralizedTime](#) (bool useDerRules)
- [Asn1GeneralizedTime](#) ()
- override System.Int32 [CompareTo](#) (System.Object obj)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- override void [ParseString](#) (System.String data)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

Protected Member Functions

- internal override bool [CompileString](#) ()

Properties

- virtual int [Century](#) [get, set]

3.18.1 Detailed Description

This is a container class for holding the components of an ASN.1 generalized time string value.

3.18.2 Constructor & Destructor Documentation

3.18.2.1 Asn1GeneralizedTime ()

The default constructor creates an empty time string object.

3.18.2.2 Asn1GeneralizedTime (bool useDerRules)

This constructor creates an empty time string object and allows DER encoding rules to be specified.

Parameters

useDerRules 'true' if time string should be encoded with DER/PER.

3.18.2.3 `Asn1GeneralizedTime` (`System.String data`)

This version of the constructor can be used to set the string `mValue` member variable to the given time string. The format of a `GeneralizedTime` string is `YYYYMMDDHHMMSS.n[Z][[-HHMM]]`.

Parameters

data Character string

3.18.2.4 `Asn1GeneralizedTime` (`System.String data`, `bool useDerRules`)

This version of the constructor can be used to set the string `mValue` member variable to the given time string and specify DER encoding rules be used to construct the string.

Parameters

data Character string

useDerRules 'true' if time string should be encoded with DER/PER.

3.18.3 Member Function Documentation

3.18.3.1 `override System.Int32 CompareTo` (`System.Object obj`) [`virtual`]

This method compares this object with [Asn1Time](#) class instance or with `System.DateTime` instance. Returns a negative integer, zero, or a positive integer as this object is less than, equal to, or greater than the specified object. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

obj the Object to be compared.

Returns

The difference in Ticks with the specified object.

Reimplemented from [Asn1Time](#).

3.18.3.2 `internal override bool CompileString` () [`protected`, `virtual`]

Compiles new time string accoring X.680 (clause 41) and ISO 8601.

Returns

true, if succeed, or false code, if error.

Implements [Asn1Time](#).

3.18.3.3 `override void Decode` (`Asn1BerDecodeBuffer buffer`, `bool explicitTagging`, `int implicitLength`) [`virtual`]

This method decodes an ASN.1 string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

- buffer* Decode message buffer object
- explicitTagging* Flag indicating element is explicitly tagged
- implicitLength* Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.18.3.4 override void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to stream an ASN.1 generalized time string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

- outs* BER Output Stream object
- explicitTagging* Flag indicating explicit tagging should be done

Reimplemented from [Asn1Type](#).

3.18.3.5 override int Encode (Asn1BerEncodeBuffer buffer, bool explicitTagging) [virtual]

This method encodes an ASN.1 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

- buffer* Encode message buffer object
- explicitTagging* Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.18.3.6 override void ParseString (System.String data) [virtual]

This method parses the given time string value. It will throw an exception if the string is not in the valid time format. The valid format of a GeneralizedTime string is YYYYMMDDHHMMSS.n[Z][[-HHMM]].

Parameters

- data* The time string value to be parsed.

Exceptions

- [Asn1Exception](#) Thrown, if operation is failed.

Implements [Asn1Time](#).

3.18.4 Member Data Documentation

3.18.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 24).

Reimplemented from [Asn1Type](#).

3.18.5 Property Documentation

3.18.5.1 virtual int Century [get, set]

Gets or Sets the century part (first two digits) of the year component of the time value.

Value: Century part (first two digits) of the year component.

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.19 Asn1GeneralString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString](#).

Public Member Functions

- [Asn1GeneralString](#) (System.String data)
- [Asn1GeneralString](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.19.1 Detailed Description

This is a container class for holding the components of an ASN.1 general string value.

3.19.2 Constructor & Destructor Documentation

3.19.2.1 Asn1GeneralString ()

The default constructor creates an empty string object.

3.19.2.2 Asn1GeneralString (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string value.

Parameters

data Character string

3.19.3 Member Function Documentation

3.19.3.1 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.19.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 general string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.19.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.19.4 Member Data Documentation

3.19.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 27).

Reimplemented from [Asn1Type](#).

3.20 Asn1GraphicString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString](#).

Public Member Functions

- [Asn1GraphicString](#) (System.String data)
- [Asn1GraphicString](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.20.1 Detailed Description

This is a container class for holding the components of an ASN.1 graphic string value.

3.20.2 Constructor & Destructor Documentation

3.20.2.1 Asn1GraphicString ()

The default constructor creates an empty string object.

3.20.2.2 Asn1GraphicString (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string value.

Parameters

data string representation of GraphicString

3.20.3 Member Function Documentation

3.20.3.1 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 graphic string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.20.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 graphic string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.20.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 graphic string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.20.4 Member Data Documentation

3.20.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 25).

Reimplemented from [Asn1Type](#).

3.21 Asn1IA5String Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn18BitCharString](#).

Public Member Functions

- [Asn1IA5String](#) (System.String data)
- [Asn1IA5String](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.21.1 Detailed Description

This is a container class for holding the components of an ASN.1 IA5 string value.

3.21.2 Constructor & Destructor Documentation

3.21.2.1 [Asn1IA5String](#) ()

The default constructor creates an empty string object.

3.21.2.2 [Asn1IA5String](#) (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data string representation of IA5String

3.21.3 Member Function Documentation

3.21.3.1 override void [Decode](#) (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 IA5 string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.21.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 IA5 string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.21.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 IA5 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.21.4 Member Data Documentation

3.21.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 22).

Reimplemented from [Asn1Type](#).

3.22 Asn1InputStream Interface Reference

Public Member Functions

- int [Available](#) ()
- void [Close](#) ()
- void [Mark](#) ()
- bool [MarkSupported](#) ()
- void [Reset](#) ()
- long [Skip](#) (long nbytes)

3.22.1 Detailed Description

This interface is a base interface for all classes, which implement an input stream functionality for decoding.

3.22.2 Member Function Documentation

3.22.2.1 int Available ()

Returns the number of bytes that can be read (or skipped over) from this input stream without blocking by the next caller of a method for this input stream. The next caller might be the same thread or or another thread.

Returns

the number of bytes that can be read from this input stream without blocking.

Exceptions

System.SystemException if an I/O error occurs.

3.22.2.2 void Close ()

Closes this input stream and releases any system resources associated with the stream.

Exceptions

System.SystemException if an I/O error occurs.

3.22.2.3 void Mark ()

This method is used to mark the current position in the input stream for retry processing or resetting the input stream position to current position.

3.22.2.4 bool MarkSupported ()

Tests if this input stream supports the seeking. This method is equivalent to C# `CanSeek` method of `System.IO.Stream`.

Returns

`true` if input stream supports seeking; Otherwise `false`.

3.22.2.5 void Reset ()

This method is used to reset the current position in the input stream back to the location of the last 'mark' call. It is equivalent to calling 'Stream.Position' to marked location.

3.22.2.6 long Skip (long *nbytes*)

This method will skip over the requested number of bytes in the input stream.

Parameters

nbytes Number of bytes to skip

Exceptions

System.SystemException if an I/O error occurs.

Returns

Skipped number of bytes

3.23 Asn1Integer Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1Integer](#) (long value)
- [Asn1Integer](#) ()
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, Object lower, Object upper)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, Object upper)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, Object lower, long upper)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- void [Decode16Bit](#) (Asn1MderDecodeBuffer buffer, bool signed)
- void [Decode32Bit](#) (Asn1MderDecodeBuffer buffer, bool signed)
- void [Decode8Bit](#) (Asn1MderDecodeBuffer buffer, bool signed)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- virtual void [Encode](#) (Asn1PerOutputStream outs, Object lower, Object upper)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, Object upper)
- virtual void [Encode](#) (Asn1PerOutputStream outs, Object lower, long upper)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, long upper)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, Object lower, Object upper)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, Object upper)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, Object lower, long upper)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- void [Encode16Bit](#) (Asn1MderOutputStream outs, bool signed)
- void [Encode32Bit](#) (Asn1MderOutputStream outs, bool signed)
- void [Encode8Bit](#) (Asn1MderOutputStream outs, bool signed)
- virtual void [EncodeAttribute](#) (Asn1XmlEncoder buffer, System.String attrName)
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (long value)
- virtual int [GetBitCount](#) ()
- override int [GetHashCode](#) ()
- virtual int [GetUnsignedBitCount](#) ()
- override System.String [ToString](#) ()

Static Public Member Functions

- static long [DecodeValue](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- static long [DecodeValue](#) (Asn1PerDecodeBuffer buffer)
- static void [EncodeValue](#) (Asn1PerEncoder encoder, long val, long lower, long upper)
- static int [GetBitCount](#) (long ivalue)
- static int [GetUnsignedBitCount](#) (long ivalue)

Public Attributes

- long `mValue`

Static Public Attributes

- static new readonly `Asn1Tag_TAG`

3.23.1 Detailed Description

This class represents the ASN.1 INTEGER built-in type.

3.23.2 Constructor & Destructor Documentation

3.23.2.1 `Asn1Integer ()`

The default constructor sets the integer value to zero.

3.23.2.2 `Asn1Integer (long value)`

This constructor creates an integer object from a integer value.

Parameters

value Integer value

3.23.3 Member Function Documentation

3.23.3.1 `virtual void Decode (Asn1PerDecodeBuffer buffer, Object lower, Object upper) [virtual]`

This method decodes a unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

lower Lower bound equal MIN

upper Upper bound equal MAX

3.23.3.2 `virtual void Decode (Asn1PerDecodeBuffer buffer, long lower, Object upper) [virtual]`

This method decodes a semi-constrained ASN.1 integer value using the Packed Encoding Rules (PER). The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

lower Lower bound of the integer range

upper Upper bound equal MAX

3.23.3.3 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Object *lower*, long *upper*) [virtual]

This method decodes a unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

lower Lower bound equal MIN

upper Upper bound of the integer range

3.23.3.4 virtual void Decode (Asn1PerDecodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method decodes a constrained ASN.1 integer value using the Packed Encoding Rules (PER). The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

lower Lower bound of the integer range

upper Upper bound of the integer range

3.23.3.5 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are decoded. The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

Reimplemented from [Asn1Type](#).

3.23.3.6 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 integer value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.23.3.7 void Decode16Bit (Asn1MderDecodeBuffer *buffer*, bool *signed*)

Decode a signed or unsigned 16-bit integer from an MDER encoding. This should be used to decode integer types that are constrained to exactly the value space of a signed/unsigned 16 bit integer.

3.23.3.8 void Decode32Bit (Asn1MderDecodeBuffer *buffer*, bool *signed*)

Decode a signed or unsigned 32-bit integer from an MDER encoding. This should be used to decode integer types that are constrained to exactly the value space of a signed/unsigned 32 bit integer.

3.23.3.9 void Decode8Bit (Asn1MderDecodeBuffer *buffer*, bool *signed*)

Decode a signed or unsigned 8-bit integer from an MDER encoding. This should be used to decode integer types that are constrained to exactly the value space of a signed/unsigned 8 bit integer.

3.23.3.10 static long DecodeValue (Asn1PerDecodeBuffer *buffer*, long *lower*, long *upper*) [static]

This method decodes a constrained ASN.1 integer value using the Packed Encoding Rules (PER). The decoded result is returned.

Parameters

buffer PER Decode message buffer object

lower Lower bound of the integer range

upper Upper bound of the integer range

3.23.3.11 static long DecodeValue (Asn1PerDecodeBuffer *buffer*) [static]

This method decodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are decoded. The decoded result is returned.

Parameters

buffer PER Decode message buffer object

3.23.3.12 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 integer value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.23.3.13 **override void DecodeXML (System.String *buffer*, System.String *attrs*)**

This method decodes an ASN.1 integer value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.23.3.14 **virtual void Encode (Asn1PerOutputStream *outs*, Object *lower*, Object *upper*) [virtual]**

This method encodes a unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

outs PER Encode message buffer object

lower Lower bound equal MIN

upper Upper bound equal MAX

3.23.3.15 **virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, Object *upper*) [virtual]**

This method encodes a semi-constrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

outs PER Encode message buffer object

lower Lower bound (inclusive) of integer being encoded

upper Upper bound equal MAX

3.23.3.16 **virtual void Encode (Asn1PerOutputStream *outs*, Object *lower*, long *upper*) [virtual]**

This method encodes a unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

outs PER Encode message buffer object

lower Lower bound equal MIN

upper Upper bound (inclusive) of integer being encoded

3.23.3.17 **virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, long *upper*) [virtual]**

This method encodes a constrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Encode message buffer object
lower Lower bound (inclusive) of integer being encoded
upper Upper bound (inclusive) of integer being encoded

Exceptions

Asn1Exception Thrown, if operation is failed.

3.23.3.18 override void Encode (Asn1PerOutputStream outs) [virtual]

This method encodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Encode message buffer object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.23.3.19 override void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to the stream an ASN.1 integer value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object
explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.23.3.20 virtual void Encode (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix) [virtual]

This method encodes an ASN.1 integer value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object
elemName Element name
nsPrefix Element namespace value

3.23.3.21 **override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]**

This method encodes an ASN.1 integer value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1Type](#).

3.23.3.22 **virtual void Encode (Asn1PerEncodeBuffer *buffer*, Object *lower*, Object *upper*) [virtual]**

This method encodes a unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

lower Lower bound equal MIN

upper Upper bound equal MAX

3.23.3.23 **virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, Object *upper*) [virtual]**

This method encodes a semi-constrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

lower Lower bound (inclusive) of integer being encoded

upper Upper bound equal MAX

3.23.3.24 **virtual void Encode (Asn1PerEncodeBuffer *buffer*, Object *lower*, long *upper*) [virtual]**

This method encodes a unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

lower Lower bound equal MIN

upper Upper bound (inclusive) of integer being encoded

3.23.3.25 virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method encodes a constrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

- buffer* PER Encode message buffer object
- lower* Lower bound (inclusive) of integer being encoded
- upper* Upper bound (inclusive) of integer being encoded

3.23.3.26 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an unconstrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

- buffer* PER Encode message buffer object

Reimplemented from [Asn1Type](#).

3.23.3.27 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 integer value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

- buffer* Encode message buffer object
- explicitTagging* Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.23.3.28 void Encode16Bit (Asn1MderOutputStream *outs*, bool *signed*)

This method encodes this ASN.1 INTEGER value to the MDER encoding. The value must fall in the set of 16-bit unsigned integers (if signed is false) or 16-bit signed integers (if signed is true).

3.23.3.29 void Encode32Bit (Asn1MderOutputStream *outs*, bool *signed*)

This method encodes this ASN.1 INTEGER value to the MDER encoding. The value must fall in the set of 32-bit unsigned integers (if signed is false) or 32-bit signed integers (if signed is true).

3.23.3.30 void Encode8Bit (Asn1MderOutputStream *outs*, bool *signed*)

This method encodes this ASN.1 INTEGER value to the MDER encoding. The value must fall in the set of 8-bit unsigned integers (if signed is false) or 8-bit signed integers (if signed is true).

3.23.3.31 virtual void EncodeAttribute (Asn1XmlEncoder *buffer*, System.String *attrName*) [virtual]

This method encodes an ASN.1 integer value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

attribute Element attribute value

3.23.3.32 static void EncodeValue (Asn1PerEncoder *encoder*, long *val*, long *lower*, long *upper*) [static]

This method encodes a constrained ASN.1 integer value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

lower Lower bound (inclusive) of integer being encoded

upper Upper bound (inclusive) of integer being encoded

3.23.3.33 override bool Equals (System.Object *value*)

This method compares this integer value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1Integer](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

3.23.3.34 virtual bool Equals (long *value*) [virtual]

This method compares this integer value to the given value for equality.

Parameters

value The long value to compare with the current Object.

Returns

true if the specified long value is equal to the current Object; otherwise, false.

3.23.3.35 virtual int GetBitCount () [virtual]

This method calculates the count of bits in the contained integer value.

Returns

Bit count.

3.23.3.36 static int GetBitCount (long *ivalue*) [static]

This method calculates the count of bits in an integer value.

Parameters

ivalue Integer value in which to count bits.

Returns

Bit count.

3.23.3.37 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.23.3.38 virtual int GetUnsignedBitCount () [virtual]

This method calculates the count of bits in the contained unsigned integer value.

Returns

Bit count.

3.23.3.39 static int GetUnsignedBitCount (long *ivalue*) [static]

This method calculates the count of bits in an unsigned integer value.

Parameters

ivalue Integer value in which to count bits.

Returns

Bit count.

3.23.3.40 override System.String ToString ()

This method will return a string representation of the integer value. The format is the ASN.1 value format for this type.

Returns

Stringified representation of the value

3.23.4 Member Data Documentation

3.23.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 2).

Reimplemented from [Asn1Type](#).

3.23.4.2 long mValue

This public member variable is where the integer value is stored. This is the value that is encoded when one of the encode methods is called. It is also where the decoded result is stored when a Decode method is called.

3.24 Asn1InvalidArgException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1InvalidArgException](#) (System.String argName, System.String argValue)

3.24.1 Detailed Description

This class defines the 'ASN.1 invalid argument' exception that is thrown when an argument that is passed to a method is determined to be invalid (for example, not within a defined range)..

3.24.2 Constructor & Destructor Documentation

3.24.2.1 Asn1InvalidArgException (System.String *argName*, System.String *argValue*)

This constructor creates an exception object with a textual message describing the argument that was invalid..

Parameters

argName Name of invalid argument

argValue Value of invalid argument

3.25 Asn1InvalidChoiceOptionException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1InvalidChoiceOptionException](#) ()
- [Asn1InvalidChoiceOptionException](#) (Asn1PerDecodeBuffer buffer, int index)
- [Asn1InvalidChoiceOptionException](#) (Asn1BerDecodeBuffer buffer, [Asn1Tag](#) tag)

3.25.1 Detailed Description

This class defines the 'ASN.1 invalid choice option' exception that is thrown when a CHOICE construct is detected to contain an element that is not within the given set.

3.25.2 Constructor & Destructor Documentation

3.25.2.1 [Asn1InvalidChoiceOptionException](#) (Asn1BerDecodeBuffer *buffer*, Asn1Tag *tag*)

This constructor creates an exception object with a textual message describing the tag of the invalid element..

Parameters

buffer BER Decode buffer object reference

tag Tag value of duplicate element

3.25.2.2 [Asn1InvalidChoiceOptionException](#) (Asn1PerDecodeBuffer *buffer*, int *index*)

This constructor creates an exception object with a textual message describing the PER choice index of the invalid element..

Parameters

buffer PER Decode buffer object reference

index Parsed choice index value

3.25.2.3 [Asn1InvalidChoiceOptionException](#) ()

The default constructor is invoked in the encode logic if the object assigned to the choice item is not in the allowed set..

3.26 Asn1InvalidEnumException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1InvalidEnumException](#) (System.String data)
- [Asn1InvalidEnumException](#) (long data)

3.26.1 Detailed Description

This class defines the 'ASN.1 invalid enum' exception that is thrown when an enumerated value is not within the defined set of values.

3.26.2 Constructor & Destructor Documentation

3.26.2.1 Asn1InvalidEnumException (long data)

This constructor creates an exception object with a default textual message with integer value.

Parameters

data Invalid enumerated value

3.26.2.2 Asn1InvalidEnumException (System.String data)

This constructor creates an exception object with a default textual message with textual enumerated value.

Parameters

data Invalid enumerated value

3.27 Asn1InvalidLengthException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1InvalidLengthException \(\)](#)

3.27.1 Detailed Description

This class defines the 'ASN.1 invalid length' exception that is thrown when a length is determined to be invalid.

Things that can cause this to be thrown are:

- Constructor length field is not sum of parts.
- Object identifier length is not sum of sub ID lengths.

3.27.2 Constructor & Destructor Documentation

3.27.2.1 Asn1InvalidLengthException ()

This constructor creates an exception object with a default textual message.

3.28 Asn1InvalidObjectIDException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1InvalidObjectIDException \(\)](#)

3.28.1 Detailed Description

This class defines the 'ASN.1 invalid object identifier' exception that is thrown when an Object Identifier is determined to be invalid.

Things that can cause this to be thrown are:

- Max subID's (128) exceeded.
- Not enough subID's in the OID (must contain at least 2).
- First subID > 2 and/or second subID > 40.

3.28.2 Constructor & Destructor Documentation

3.28.2.1 Asn1InvalidObjectIDException ()

This constructor creates an exception object with a default textual message.

3.29 Asn1MessageBuffer Class Reference

Inherited by [Asn1DecodeBuffer](#), and [Asn1EncodeBuffer](#).

Public Member Functions

- virtual void [AddNamedEventHandler](#) ([Asn1NamedEventHandler](#) handler)
- abstract System.IO.Stream [GetInputStream](#) ()
- virtual void [InvokeCharacters](#) (System.String svalue)
- virtual void [InvokeEndElement](#) (System.String name, int index)
- virtual void [InvokeStartElement](#) (System.String name, int index)
- void [SetKey](#) (byte[] rtkey)
- void [SetPermanentKey](#) (byte[] rtkey)

Static Public Member Functions

- static void [HexDump](#) (System.IO.Stream ins)
- static void [HexDump](#) (System.IO.Stream ins, System.IO.StreamWriter outs)

Properties

- Asn1Context [Context](#) [get]
- virtual [Asn1MessageBuffer EventHandlerList](#) [set]
- virtual short [TypeCode](#) [set]

3.29.1 Detailed Description

This is the base class for all of the different message buffer types. This includes the BER and PER encode and decode message buffer classes.

3.29.2 Member Function Documentation

3.29.2.1 virtual void AddNamedEventHandler ([Asn1NamedEventHandler](#) *handler*) [virtual]

This method adds a named event handler to the named event handler list for this buffer.

Parameters

handler [Asn1NamedEventHandler](#) object to be added

3.29.2.2 abstract System.IO.Stream GetInputStream () [pure virtual]

This abstract method must be implemented by all of the derived classes. It returns an input stream object reference to the message buffer contents (i.e. the encoded data).

Returns

Input stream object reference

Implemented in [Asn1DecodeBuffer](#).

3.29.2.3 static void HexDump (System.IO.Stream *ins*) [static]

This method prints a formatted hex dump of the contents of the given input stream to the standard output stream.

Parameters

ins System.IO.Stream containing data to be dumped

3.29.2.4 static void HexDump (System.IO.Stream *ins*, System.IO.StreamWriter *outs*) [static]

This method prints a formatted hex dump of the contents of the given input stream to the given output stream.

Parameters

ins System.IO.Stream containing data to be dumped

outs StreamWriter to which formatted data is to be written

3.29.2.5 virtual void InvokeCharacters (System.String *svalue*) [virtual]

This method is used by the event handling logic to invoke the 'characters' event handling method when message contents are parsed. The TypeCode property is used for the event's type code.

Parameters

svalue Stringified representation of a parsed value field

3.29.2.6 virtual void InvokeEndElement (System.String *name*, int *index*) [virtual]

This method is used by the event handling logic to invoke the 'endElement' event handling method when parsing of an element within a message is completed.

Parameters

name Name of the element

index Index of element if SEQUENCE OF or SET OF element

3.29.2.7 virtual void InvokeStartElement (System.String *name*, int *index*) [virtual]

This method is used by the event handling logic to invoke the 'StartElement' event handling method when parsing of an element within a message is started.

Parameters

name Name of the element

index Index of element if SEQUENCE OF or SET OF element

3.29.2.8 void SetKey (byte[] *rtkey*)

This method is used with the limited run-time to set a run-time key value generated by the compiler to allow the run-time to operate on the licensed hosts. This is not used in the unlimited redistribution versions.

Parameters

rtkey Run-time key generated by ASN1C

3.29.2.9 void SetPermanentKey (byte[] *rtkey*)

This method is used to set a run-time key value such that subsequent calls to SetKey won't overwrite it.

Parameters

rtkey The run-time key to set.

3.29.3 Property Documentation

3.29.3.1 Asn1Context Context [get]

The event dispatcher for this buffer.

3.29.3.2 virtual Asn1MessageBuffer EventHandlerList [set]

Sets the event dispatcher in this object to be equal to that in the given message buffer object. The two buffers will share the event dispatcher.

Value: Message buffer object

3.29.3.3 virtual short TypeCode [set]

Sets the internal type code to the given value. This is a code describing the last type parsed by the decoder.

Value: Type code (codes are defined in Asn1Type.cs). The codes correspond to the UNIVERSAL tag ID values for the built-in types.

3.30 Asn1MissingRequiredException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1MissingRequiredException](#) (System.String elemName)
- [Asn1MissingRequiredException](#) (Asn1BerDecodeBuffer buffer)

3.30.1 Detailed Description

This class defines the 'ASN.1 set missing required element' exception that is thrown from Decode methods when a SET construct is decoded and found to be missing a required element..

3.30.2 Constructor & Destructor Documentation

3.30.2.1 Asn1MissingRequiredException (Asn1BerDecodeBuffer *buffer*)

This constructor creates an exception object with a textual message describing the error.

Parameters

buffer BER decode buffer object reference

3.30.2.2 Asn1MissingRequiredException (System.String *elemName*)

This constructor creates an exception object with a textual message describing the error including the name of the required element that is missing.

Parameters

elemName Name of missing required element

3.31 Asn1NamedEventHandler Interface Reference

Inherited by [Asn1TraceHandler](#).

Public Member Functions

- void [Characters](#) (System.String svalue, short typeCode)
- void [EndElement](#) (System.String name, int index)
- void [StartElement](#) (System.String name, int index)

3.31.1 Detailed Description

This interface defines the methods that must be implemented to define a SAX-like event handler. These methods are invoked from within the generated C# decode logic when significant events occur during the parsing of an ASN.1 message.

3.31.2 Member Function Documentation

3.31.2.1 void Characters (System.String svalue, short typeCode)

The Characters callback method is invoked when content (primitive data) is encountered. A stringified representation of the parsed value is returned.

Parameters

svalue Stringified representation of the parsed value. The representation will be in ASN.1 value format.

typeCode Identifier specifying the type of the parsed data variable. The enumerated list of values that might appear here is provided in the the [Asn1Type](#) class (see the documentation on this class for a full list of the names).

See also

<seealso cref=Asn1Type The type codes are member of [Asn1Type](#) class

Implemented in [Asn1TraceHandler](#).

3.31.2.2 void EndElement (System.String name, int index)

The EndElement callback method is invoked when the end of an element within a constructed type (SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE) is detected.

Parameters

name Name of the parsed element.

index Index of element in array. Only used for SEQUENCE OF or SET OF elements. Set to -1 for all others.

Implemented in [Asn1TraceHandler](#).

3.31.2.3 void StartElement (System.String *name*, int *index*)

The StartElement callback method is invoked when the start of an element within a constructed type (SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE) is encountered.

Parameters

name Name of the parsed element.

index Index of element in array. Only used for SEQUENCE OF or SET OF elements. Set to -1 for all others.

Implemented in [Asn1TraceHandler](#).

3.32 Asn1Null Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- override bool [Equals](#) (object o)
- override System.String [ToString](#) ()

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)
- static readonly [Asn1Null NULL_VALUE](#) = new [Asn1Null](#)()

3.32.1 Detailed Description

This class represents the ASN.1 NULL built-in type.

3.32.2 Member Function Documentation

3.32.2.1 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 null value in accordance with the Packed Encoding Rules (PER).

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

3.32.2.2 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 null value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.32.2.3 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 null value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.32.2.4 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 null value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.32.2.5 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 null value in accordance with the Packed Encoding Rules (PER).

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.32.2.6 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 NULL value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.32.2.7 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 null value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

3.32.2.8 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 null value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1Type](#).

3.32.2.9 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 null value in accordance with the Packed Encoding Rules (PER).

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

3.32.2.10 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 null value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version used the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length (in octets) of encoded component

Reimplemented from [Asn1Type](#).

3.32.2.11 override bool Equals (object o)

Tests for equality with any other object. Returns true if the input type is an [Asn1Null](#) object and false otherwise.

3.32.2.12 override System.String ToString ()

This method will return a string representation of the null value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

3.32.3 Member Data Documentation

3.32.3.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 5).

Reimplemented from [Asn1Type](#).

3.32.3.2 readonly Asn1Null NULL_VALUE = new Asn1Null() [static]

The NULL_VALUE constant represents a NULL value.

3.33 Asn1NumericString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn18BitCharString](#).

Public Member Functions

- [Asn1NumericString](#) (System.String data)
- [Asn1NumericString](#) ()
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.33.1 Detailed Description

This is a container class for holding the components of an ASN.1 numeric string value.

3.33.2 Constructor & Destructor Documentation

3.33.2.1 Asn1NumericString ()

The default constructor creates an empty string object.

3.33.2.2 Asn1NumericString (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string value.

Parameters

data string representation of numeric string

3.33.3 Member Function Documentation

3.33.3.1 virtual void Decode (Asn1PerDecodeBuffer buffer, long lower, long upper) [virtual]

This overloaded version of the Decode method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

- buffer* Decode message buffer object
- lower* Effective size constraint lower bound
- upper* Effective size constraint upper bound

3.33.3.2 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

- buffer* Decode message buffer object

Reimplemented from [Asn18BitCharString](#).

3.33.3.3 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

- buffer* Decode message buffer object
- explicitTagging* Flag indicating element is explicitly tagged
- implicitLength* Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.33.3.4 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 numeric string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

- outs* BER Output Stream object
- explicitTagging* Flag indicating explicit tagging should be done

Exceptions

- [Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.33.3.5 virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This overloaded version of the encode method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

- buffer* Encode message buffer object
- lower* Effective size constraint lower bound
- upper* Effective size constraint upper bound

3.33.3.6 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

- buffer* Encode message buffer object

Reimplemented from [Asn18BitCharString](#).

3.33.3.7 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

- buffer* Encode message buffer object
- explicitTagging* Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.33.4 Member Data Documentation

3.33.4.1 new readonly Asn1Tag _TAG [static]

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 18).

Reimplemented from [Asn1Type](#).

3.34 Asn1ObjectDescriptor Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString](#).

Public Member Functions

- [Asn1ObjectDescriptor](#) (System.String data)
- [Asn1ObjectDescriptor](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.34.1 Detailed Description

This is a container class for holding the components of an ASN.1 object descriptor value.

3.34.2 Constructor & Destructor Documentation

3.34.2.1 Asn1ObjectDescriptor ()

The default constructor creates an empty string object.

3.34.2.2 Asn1ObjectDescriptor (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data string representation of ObjectDescriptor

3.34.3 Member Function Documentation

3.34.3.1 override void Decode (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength) [virtual]

This method decodes an ASN.1 string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.34.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 object descriptor value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.34.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.34.4 Member Data Documentation

3.34.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 7).

Reimplemented from [Asn1Type](#).

3.35 Asn1ObjectIdentifier Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Inherited by [Asn1RelativeOID](#).

Public Member Functions

- virtual void [Append](#) (int[] value2)
- [Asn1ObjectIdentifier](#) (int[] value)
- [Asn1ObjectIdentifier](#) ()
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- override bool [Equals](#) (System.Object value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()

Public Attributes

- const int [MAXSUBIDS](#) = 128
- int[] [mValue](#)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.35.1 Detailed Description

This is a container class for holding the components of an ASN.1 object identifier value.

3.35.2 Constructor & Destructor Documentation

3.35.2.1 Asn1ObjectIdentifier ()

This constructor creates an empty object identifier that can be used in a Decode method call to receive an OID value.

3.35.2.2 Asn1ObjectIdentifier (int[] value)

This constructor initializes the object identifier from the given array of integer subidentifier values.

Parameters

value Array of subidentifiers

3.35.3 Member Function Documentation

3.35.3.1 virtual void Append (int[] *value2*) [virtual]

This method appends an object identifier value onto the existing value. A typical use of this method would be for SNMP objects to create the base and index parts.

Parameters

value2 Array of subidentifiers to append

3.35.3.2 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 object identifier value using the packed encoding rules (PER).

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.3 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 object identifier value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.4 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 object identifier value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

Reimplemented in [Asn1RelativeOID](#).

3.35.3.5 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 object identifier value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

Reimplemented in [Asn1RelativeOID](#).

3.35.3.6 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 object identifier value using the packed encoding rules (PER).

The value to be encoded is stored in the `mValue` public member variable within this class.

Also throws any exception thrown by the underlying `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.7 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 object identifier value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# `System.IO.Stream` for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.8 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 object identifier value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

Reimplemented in [Asn1RelativeOID](#).

3.35.3.9 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 object identifier value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.10 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 object identifier value using the packed encoding rules (PER).

The value to be encoded is stored in the `mValue` public member variable within this class.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.11 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 object identifier value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of encoded component in octets

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.3.12 override bool Equals (System.Object value)

This method compares this object identifier to the given one for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1ObjectIdentifier](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

3.35.3.13 override int GetHashCode ()

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.35.3.14 override System.String ToString ()

This method will return a string representation of the OID value. The format is the ASN.1 value format for this type. Note that textual subidentifiers are not used, only numeric values..

Returns

Stringified representation of the value

3.35.4 Member Data Documentation

3.35.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 6).

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1RelativeOID](#).

3.35.4.2 const int MAXSUBIDS = 128

The MAXSUBIDS constant specifies the maximum number of subidentifiers that can appear in an OID value (128).

3.35.4.3 int [] mValue

The mValue public member variable is where the object identifier value is stored.

3.36 Asn1OctetString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Inherited by [Asn1OpenType](#).

Public Member Functions

- [Asn1OctetString](#) (System.String value)
- [Asn1OctetString](#) (byte[] data, int offset, int nbytes)
- [Asn1OctetString](#) (byte[] data)
- [Asn1OctetString](#) ()
- virtual int [CompareTo](#) (System.Object octstr)
- void [Decode](#) (Asn1MderDecodeBuffer buffer, int constrainedLength)
- virtual void [Decode](#) (Asn1MderDecodeBuffer buffer)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs, bool base64)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, long upper)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix, bool base64)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- void [Encode](#) (Asn1MderOutputStream outs, int constrainedLength)
- virtual void [Encode](#) (Asn1MderOutputStream outs)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual void [EncodeAttribute](#) (Asn1XmlEncoder buffer, System.String attrName)
- override bool [Equals](#) (System.Object value)
- bool [Equals](#) (byte[] value)
- override int [GetHashCode](#) ()
- int [GetMderLength](#) ()
- virtual System.IO.Stream [toInputStream](#) ()
- override System.String [ToString](#) ()

Static Public Member Functions

- static System.String [EncodeBase64Binary](#) (byte[] data)

Public Attributes

- byte[] [mValue](#)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

Properties

- override int [Length](#) [get]

3.36.1 Detailed Description

This is a container class for holding the components of an ASN.1 octet string value.

3.36.2 Constructor & Destructor Documentation

3.36.2.1 `Asn1OctetString ()`

This constructor creates an empty octet string that can be used in a Decode method call to receive an octet string value.

3.36.2.2 `Asn1OctetString (byte[] data)`

This constructor initializes an octet string from the given byte array.

Parameters

data Byte array containing an octet string in binary form.

3.36.2.3 `Asn1OctetString (byte[] data, int offset, int nbytes)`

This constructor initializes an octet string from a portion of the given byte array. A new byte array is created starting at the given offset and consisting of the given number of bytes.

Parameters

data Byte array containing an octet string in binary form.

offset The offset in array at which to begin copy.

nbytes Number of bytes to copy from target array

3.36.2.4 `Asn1OctetString (System.String value)`

This constructor parses the given ASN.1 value text (either a binary or hex data string) and assigns the values to the internal bit string.

Examples of valid value formats are as follows:

Binary string: '11010010111001'B

Hex string: '0fa56920014abc'H

Char string: 'abcdefg'

Parameters

value The ASN.1 value specification text

3.36.3 Member Function Documentation

3.36.3.1 virtual int CompareTo (System.Object *octstr*) [virtual]

This method compares two [Asn1OctetString](#) objects for equality. The OCTET STRING's are equal if a) all octets are equal, and b) the lengths are the same.

This method is required to implement the Comparable interface used for sorting.

Parameters

octstr [Asn1OctetString](#) to compare

Returns

0 if equal, 1 if this string is greater than supplied string, -1 if this string is less than supplied string.

3.36.3.2 void Decode (Asn1MderDecodeBuffer *buffer*, int *constrainedLength*)

Decode an octet string from the MDER encoding into this object.

Parameters

constrainedLength The constrained length of the type being encoded. Pass -1 if the type is unconstrained. For a constrained length octet string, exactly that many octets will be read.

3.36.3.3 virtual void Decode (Asn1MderDecodeBuffer *buffer*) [virtual]

Decode an unconstrained octet string from the MDER encoding into this object.

3.36.3.4 virtual void Decode (Asn1PerDecodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method decodes a sized ASN.1 octet string value using the packed encoding rules (PER).

Parameters

buffer Decode message buffer object

lower Lower bound (inclusive) of size constraint

upper Upper bound (inclusive) of size constraint

3.36.3.5 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 octet string value using the packed encoding rules (PER). The string is assumed to not contain a size constraint.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1ChoiceExt](#).

3.36.3.6 **override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]**

This method decodes an ASN.1 octet string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object
explicitTagging Flag indicating element is explicitly tagged
implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1ChoiceExt](#), and [Asn1OpenType](#).

3.36.3.7 **virtual void DecodeXER (System.String *buffer*, System.String *attrs*, bool *base64*) [virtual]**

This method decodes ASN.1 octet string type using the XML encoding rules (XER). Extended-XER is supported by the base64

Parameters

buffer String containing data to be decoded
attrs Attributes string from element tag
base64 pass true if encoding is base64 (extended-XER only)

3.36.3.8 **override void DecodeXML (System.String *buffer*, System.String *attrs*)**

This method decodes an ASN.1 octet string type using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded
attrs Attributes string from element tag

3.36.3.9 **virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, long *upper*) [virtual]**

This method encodes a size-constrained ASN.1 octet string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object
lower Lower bound (inclusive) of size constraint
upper Upper bound (inclusive) of size constraint

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.36.3.10 override void Encode (Asn1PerOutputStream outs) [virtual]

This method encodes an unconstrained ASN.1 octet string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1ChoiceExt](#), and [Asn1OpenType](#).

3.36.3.11 override void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to the stream an ASN.1 octet string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1ChoiceExt](#), and [Asn1OpenType](#).

3.36.3.12 virtual void Encode (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix, bool base64) [virtual]

This method encodes ASN.1 octet string type using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName XML element name used to wrap string

nsPrefix Element namespace value

base64 Pass true to encode as base64 (extended-XER only, including XSD compilation)

3.36.3.13 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes ASN.1 octet string type as an xmlhstring.

Parameters

- buffer* Encode message buffer object
- elemName* XML element name used to wrap string
- nsPrefix* Element namespace value

3.36.3.14 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes ASN.1 octet string type using the XML encoding rules (XER).

Parameters

- buffer* Encode message buffer object
- elemName* XML element name used to wrap string

Reimplemented from [Asn1Type](#).

3.36.3.15 void Encode (Asn1MderOutputStream *outs*, int *constrainedLength*)

Encode this octet string into the MDER encoding.

Parameters

- constrainedLength* The constrained length of the type being encoded. Pass -1 if the type is unconstrained.

Exceptions

- [Asn1ConsVioException](#) if a constrained length is given and the value is not exactly that length.
- [Asn1MderUnsupported](#) if the length is unconstrained and the actual length > 65535 (maximum allowed by MDER).

3.36.3.16 virtual void Encode (Asn1MderOutputStream *outs*) [virtual]

Encode this octet string into the MDER encoding. This should be used for octet string types that are not of fixed length.

Exceptions

- [Asn1MderUnsupported](#) if the actual length > 65535 (maximum allowed by MDER).

3.36.3.17 virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method encodes a size-constrained ASN.1 octet string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Parameters

buffer Encode message buffer object

lower Lower bound (inclusive) of size constraint

upper Upper bound (inclusive) of size constraint

3.36.3.18 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an unconstrained ASN.1 octet string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1ChoiceExt](#), and [Asn1OpenType](#).

3.36.3.19 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 octet string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of encoded component

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1ChoiceExt](#), and [Asn1OpenType](#).

3.36.3.20 virtual void EncodeAttribute (Asn1XmlEncoder *buffer*, System.String *attrName*) [virtual]

This method encodes ASN.1 octet string type using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName XML element name used to wrap string

attribute Element attribute value

3.36.3.21 `static System.String EncodeBase64Binary (byte[] data) [static]`

Encodes `xsd:Base64Binary` data into ASCII character using the algorithm defined in RFC2045, as defined in w3c standard <http://www.w3.org/tr/2001/rec-xmlschema-2-20010502#base64Binary>

Parameters

base64binary Array containing base64binary

Returns

Encoded ASCII string

3.36.3.22 `override bool Equals (System.Object value)`

This method compares this octet string value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1OctetString](#).

Returns

`true` if the specified Object is equal to the current Object; otherwise, `false`.

3.36.3.23 `bool Equals (byte[] value)`

This method compares this octet string value to the given value for equality.

Parameters

value The byte array to compare with the current Object.

Returns

`true` if the specified byte array is equal to the current Object; otherwise, `false`.

3.36.3.24 `override int GetHashCode ()`

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.36.3.25 `int GetMderLength ()`

Return the length of the MDER encoding for this type, assuming that the type is NOT a fixed length OCTET STRING (if it is fixed length, you need not call this method!).

3.36.3.26 virtual System.IO.Stream toInputStream () [virtual]

This method will return a byte array input stream representation of the octet string value.

Returns

Reference to System.IO.MemoryStream object

3.36.3.27 override System.String ToString ()

This method will return a string representation of the octet string value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

Reimplemented in [Asn1OpenType](#).

3.36.4 Member Data Documentation

3.36.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 4).

Reimplemented from [Asn1Type](#).

3.36.4.2 byte [] mValue

This variable holds the octet string value. These are the octets that are encoded when encode is invoked. It is also where the decoded octet string is stored after a Decode operation.

3.36.5 Property Documentation

3.36.5.1 override int Length [get]

Gets the length of the OCTET STRING in octets.

Value: length of the octet string

Reimplemented from [Asn1Type](#).

3.37 Asn1OpenExt Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeComponent](#) (Asn1BerDecodeBuffer buffer)
- virtual void [DecodeEventComponent](#) (Asn1BerDecodeBuffer buffer)
- virtual [Asn1OpenType DecodeOpenType](#) (Asn1PerDecodeBuffer buffer, bool present, int index)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer)
- override void [Encode](#) (Asn1XerEncoder buffer)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual void [EncodeExtBits](#) (Asn1PerEncodeBuffer buffer)
- virtual void [SetOpenType](#) ([Asn1OpenType](#) obj, int index)
- virtual void [ShrinkArray](#) (int numrecs)
- override System.String [ToString](#) ()

Public Attributes

- System.Collections.ArrayList [mValue](#)

3.37.1 Detailed Description

This is a container class for holding open type elements that may occur within an open type extension (i.e. a ... at the end of a constructed type or a ..., ... at some other point in a constructed type).

3.37.2 Member Function Documentation

3.37.2.1 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an open type extension in a SEQUENCE or SET construct using the packed encoding rules (PER). This method will capture each extension item in a separate open type object and store it in the `mValue` public member list variable. If optional items are absent, null placeholders will be inserted in the list.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

3.37.2.2 **override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]**

This method decodes an ASN.1 open type extension value using the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length if implicit element

Reimplemented from [Asn1Type](#).

3.37.2.3 **virtual void DecodeComponent (Asn1BerDecodeBuffer *buffer*) [virtual]**

This method decodes a single component of a BER open type extension by decoding an open type value and appending it to the list of open type objects.

Parameters

buffer Decode message buffer object

3.37.2.4 **virtual void DecodeEventComponent (Asn1BerDecodeBuffer *buffer*) [virtual]**

This method decodes a single component of a BER open type extension by decoding an open type value and appending it to the list of open type objects, this function also triggers event handler code, with element name "..."

Parameters

buffer Decode message buffer object

3.37.2.5 **virtual Asn1OpenType DecodeOpenType (Asn1PerDecodeBuffer *buffer*, bool *present*, int *index*) [virtual]**

This method decodes a single open type extension item in a SEQUENCE or SET construct using the packed encoding rules (PER). It will then add the item to the open extension element list.

Parameters

buffer Decode message buffer object

present Flag indicating whether element is present

index Index of element in the object array

Returns

Decoded open type

3.37.2.6 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 open type extension value using the Packed Encoding Rules (PER). Also throws any exception thrown by the underlying Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.37.2.7 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 open type extension value using the Basic Encoding Rules (BER) and writes it into the stream.

Also throws any exception thrown by the underlying Asn1BerOutputStream.

Parameters

outs BER Output Stream object

explicitTagging Flag indicating element is explicitly tagged

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.37.2.8 virtual void Encode (Asn1XmlEncoder *buffer*) [virtual]

This method encodes an ASN.1 open type extension value using the XML Encoding as specified in the XML schema standard (asn2xsd).

Parameters

buffer Encode message buffer object

3.37.2.9 override void Encode (Asn1XerEncoder *buffer*) [virtual]

This method encodes an ASN.1 open type extension value using the XML Encoding Rules (XER).

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

3.37.2.10 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 open type extension value using the Packed Encoding Rules (PER).

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

3.37.2.11 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 open type extension value using the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating element is explicitly tagged

Returns

Length of encoded component

Reimplemented from [Asn1Type](#).

3.37.2.12 virtual void EncodeExtBits (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 open type extension value bits using the Packed Encoding Rules (PER).

Parameters

buffer Encode message buffer object

3.37.2.13 virtual void SetOpenType (Asn1OpenType *obj*, int *index*) [virtual]

This method will add the given open type object to the open extension element list at the given index.

Parameters

obj Open type object

index Index in open type list where element is to be placed

3.37.2.14 virtual void ShrinkArray (int *numrecs*) [virtual]

This method adjusts the size of the open type component array downward to the given size value.

Parameters

numrecs Number of entries the array should hold

3.37.2.15 **override System.String ToString ()**

This method will return a string representation of the open extension value. The format is the ASN.1 value format for each open type in the extension.

Returns

Stringified representation of the value

3.37.3 **Member Data Documentation**

3.37.3.1 **System.Collections.ArrayList mValue**

Initial value:

```
new System.Collections.ArrayList ()
```

The value is a list of [Asn1OpenType](#) objects. Each of these objects contains a fully encoded extension item.

3.38 Asn1OpenType Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1OctetString](#).

Inherited by [Asn1ChoiceExt](#).

Public Member Functions

- [Asn1OpenType](#) ([Asn1EncodeBuffer](#) buffer)
- [Asn1OpenType](#) (byte[] data, int offset, int nbytes)
- [Asn1OpenType](#) (byte[] data)
- [Asn1OpenType](#) ()
- override void [Decode](#) ([Asn1BerDecodeBuffer](#) buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) ([Asn1PerOutputStream](#) outs)
- override void [Encode](#) ([Asn1BerOutputStream](#) outs, bool explicitTagging)
- void [encode](#) ([Asn1XerEncoder](#) buffer, String elemName)
- void [encode](#) ([Asn1XmlEncoder](#) buffer, String elemName, String nsPrefix)
- override void [Encode](#) ([Asn1PerEncodeBuffer](#) buffer)
- override int [Encode](#) ([Asn1BerEncodeBuffer](#) buffer, bool explicitTagging)
- override System.String [ToString](#) ()

Protected Attributes

- internal [Asn1EncodeBuffer](#) [mEncodeBuffer](#)
- internal int [mLength](#)

3.38.1 Detailed Description

This is a container class for holding the an ASN.1 open type value.

3.38.2 Constructor & Destructor Documentation

3.38.2.1 [Asn1OpenType](#) ()

This constructor creates an empty type that can be used in a Decode method call to receive an encoded value.

3.38.2.2 [Asn1OpenType](#) (byte[] data)

This constructor initializes an open type from the given byte array. The array is assumed to contain a previously encoded message component.

Parameters

data Byte array containing a previously encoded message component.

3.38.2.3 `Asn1OpenType` (`byte[] data`, `int offset`, `int nbytes`)

This constructor initializes the open type from a portion of the given byte array. A new byte array is created starting at the given offset and consisting of the given number of bytes.

Parameters

data Byte array containing an octet string in binary form.

offset The offset in array at which to begin copy.

nbytes Number of bytes to copy from target array

3.38.2.4 `Asn1OpenType` (`Asn1EncodeBuffer buffer`)

This constructor initializes an open type using an encoded component. This can be used if a header (for example, a ROSE header) is being prepended to a pre-encoded component.

Parameters

buffer Reference to encode buffer into which component type was encoded.

3.38.3 Member Function Documentation

3.38.3.1 `override void Decode` (`Asn1BerDecodeBuffer buffer`, `bool explicitTagging`, `int implicitLength`) `[virtual]`

This method decodes an ASN.1 open type value.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1OctetString](#).

Reimplemented in [Asn1ChoiceExt](#).

3.38.3.2 `override void Encode` (`Asn1PerOutputStream outs`) `[virtual]`

This method encodes an ASN.1 open type value using the Packed Encoding Rules (PER).

Also throws any exception thrown by the underlying `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1OctetString](#).

Reimplemented in [Asn1ChoiceExt](#).

3.38.3.3 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 open type value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1OctetString](#).

Reimplemented in [Asn1ChoiceExt](#).

3.38.3.4 void encode (Asn1XerEncoder *buffer*, String *elemName*)

This method encodes an ASN.1 open type value using the XML Encoding as specified in the XML schema standard(asn2xsd). The value is encoded as an XML comment, since the element name will be unknown.

Parameters

buffer Encode message buffer object

elemName Ignored

3.38.3.5 void encode (Asn1XmlEncoder *buffer*, String *elemName*, String *nsPrefix*)

This method encodes an ASN.1 open type value using the XML Encoding as specified in the XML schema standard(asn2xsd). The value is encoded as an XML comment, since the element name will be unknown.

Parameters

buffer Encode message buffer object

elemName Ignored

nsPrefix Ignored

3.38.3.6 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 open type value using the Packed Encoding Rules (PER).

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1OctetString](#).

Reimplemented in [Asn1ChoiceExt](#).

3.38.3.7 **override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method encodes an ASN.1 open type value. The value is assumed to be an already-encoded message component and will be copied to the encoded buffer. An optimization is available in which no copy will be performed if the encoded component is already present in the encode buffer. This is done if the form of constructor specifying only a component length is used.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating element is explicitly tagged

Returns

Length of encoded component

Reimplemented from [Asn1OctetString](#).

Reimplemented in [Asn1ChoiceExt](#).

3.38.3.8 **override System.String ToString ()**

This method will return a string representation of the open type value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

Reimplemented from [Asn1OctetString](#).

3.38.4 **Member Data Documentation**

3.38.4.1 **internal Asn1EncodeBuffer mEncodeBuffer [protected]**

The encode buffer into which component type will be encoded. /p>

3.38.4.2 **internal int mLength [protected]**

Length of the pre-encoded component. /p>

3.39 Asn1OutputStream Class Reference

Public Member Functions

- [Asn1OutputStream](#) (System.IO.Stream *os*)
- override void [Close](#) ()
- override void [Flush](#) ()
- override int [Read](#) (byte[] buffer, int offset, int count)
- override long [Seek](#) (long offset, System.IO.SeekOrigin origin)
- override void [SetLength](#) (long value)
- override void [Write](#) (System.Byte[] b, int off, int len)
- virtual void [Write](#) (byte[] b)
- void [Write2Bytes](#) (int value)
- void [Write4Bytes](#) (int value)
- override void [WriteByte](#) (byte b)
- virtual void [WriteByte](#) (int b)

Protected Attributes

- internal System.IO.Stream *os*

Properties

- override bool [CanRead](#) [get]
- override bool [CanSeek](#) [get]
- override bool [CanWrite](#) [get]
- Asn1Context [Context](#) [get]
- override long [Length](#) [get]
- override long [Position](#) [get, set]

3.39.1 Detailed Description

This abstract class implements the base output stream to encode ASN.1 messages.

3.39.2 Constructor & Destructor Documentation

3.39.2.1 Asn1OutputStream (System.IO.Stream *os*)

This constructor creates an output stream object.

Parameters

- os* The underlying System.IO.Stream object.

3.39.3 Member Function Documentation

3.39.3.1 override void Close ()

Closes this output stream and releases any system resources associated with this stream. The general contract of `close` is that it closes the output stream. A closed stream cannot perform output operations and cannot be reopened.

Exceptions

System.IO.IOException An error occurred while trying to close the stream.

3.39.3.2 override void Flush ()

Flushes this output stream and forces any buffered output bytes to be written out. The general contract of `flush` is that calling it is an indication that, if any bytes previously written have been buffered by the implementation of the output stream, such bytes should immediately be written to their intended destination.

Exceptions

System.IO.IOException An I/O error occurs.

System.ObjectDisposedException The stream is closed.

3.39.3.3 override int Read (byte[] *buffer*, int *offset*, int *count*)

This method always throws `NotSupportedException`. [Asn1OutputStream](#) doesn't support reading.

Parameters

buffer When this method returns, contains the specified byte array with the values between `offset` and (`offset + count - 1`) replaced by the bytes read from the current source.

offset The byte offset in array at which to begin reading.

count The maximum number of bytes to read.

Returns

The total number of bytes read into the buffer.

Exceptions

System.NotSupportedException The stream does not support reading.

3.39.3.4 override long Seek (long *offset*, System.IO.SeekOrigin *origin*)

Sets the current position of this stream to the given value.

Parameters

offset The point relative to origin from which to begin seeking.

origin Specifies the beginning, the end, or the current position as a reference point for origin, using a value of type `SeekOrigin`.

Returns

The new position in the stream.

Exceptions

System.IO.IOException An I/O error occurs.

System.NotSupportedException The stream does not support seeking, such as if the `FileStream` is constructed from a pipe or console output.

System.ArgumentException Attempted seeking before the beginning of the stream.

System.ObjectDisposedException Methods were called after the stream was closed.

3.39.3.5 override void SetLength (long value)

Sets the length of this stream to the given value.

Parameters

value The new length of the stream.

Exceptions

System.IO.IOException An I/O error has occurred.

System.NotSupportedException The stream does not support both writing and seeking.

System.ArgumentOutOfRangeException Attempted to set the value parameter to less than 0.

3.39.3.6 override void Write (System.Byte[] b, int off, int len)

Writes `len` bytes from the specified byte array starting at offset `off` to this output stream.

Parameters

b The byte array data to be written.

off The offset in array at which to begin write.

len the number of bytes to write.

Exceptions

System.ArgumentNullException `array` is a null reference

System.ArgumentException `offset` and `count` describe an invalid range in array.

System.ArgumentOutOfRangeException `offset` or `count` is negative.

System.IO.IOException An I/O error occurs.

System.ObjectDisposedException The stream is closed.

System.NotSupportedException The current stream instance does not support writing.

3.39.3.7 virtual void Write (byte[] b) [virtual]

Writes `b.length` bytes from the specified byte array to this output stream. The general contract for `write(b)` is that it should have exactly the same effect as the call `Write(b, 0, b.length)`.

Parameters

b the data.

Exceptions

System.ArgumentNullException array is a null reference

System.ArgumentException offset and count describe an invalid range in array.

System.ArgumentOutOfRangeException offset or count is negative.

System.IO.IOException An I/O error occurs.

System.ObjectDisposedException The stream is closed.

System.NotSupportedException The current stream instance does not support writing.

3.39.3.8 void Write2Bytes (int value)

Write the lowest two bytes of value to the output stream. The lowest byte is written last.

Parameters

value

3.39.3.9 void Write4Bytes (int value)

Write the four bytes of value to the output stream. The lowest byte is written last.

Parameters

value

3.39.3.10 override void WriteByte (byte b)

Writes the specified byte to this output stream. The general contract for `Write` is that one byte is written to the output stream. The byte to be written is the eight low-order bits of the argument `b`. The 24 high-order bits of `b` are ignored.

Parameters

b the byte.

Exceptions

System.ObjectDisposedException The stream is closed.

System.NotSupportedException The stream does not support writing.

3.39.3.11 virtual void WriteByte (int b) [virtual]

Writes the specified byte to this output stream. The general contract for `Write` is that one byte is written to the output stream. The byte to be written is the eight low-order bits of the argument `b`. The 24 high-order bits of `b` are ignored.

Parameters

b the byte.

Exceptions

System.ObjectDisposedException The stream is closed.

System.NotSupportedException The stream does not support writing.

3.39.4 Member Data Documentation

3.39.4.1 internal System.IO.Stream os [protected]

C# Stream object

3.39.5 Property Documentation

3.39.5.1 override bool CanRead [get]

Gets a value indicating whether the current stream supports reading.

Value: false, the stream doesn't supports reading.

3.39.5.2 override bool CanSeek [get]

Gets a value indicating whether the current stream supports seeking.

Value: true if the stream supports seeking; otherwise, false.

3.39.5.3 override bool CanWrite [get]

Gets a value indicating whether the current stream supports writing.

Value: true if the stream supports writing; otherwise, false.

3.39.5.4 Asn1Context Context [get]

The context associated with this output stream.

3.39.5.5 override long Length [get]

Gets the length in bytes of the stream.

Value: A long value representing the length of the stream in bytes.

Exceptions

System.NotSupportedException `CanSeek` for this stream is false.

System.IO.IOException An I/O error occurs, such as the file being closed.

3.39.5.6 override long Position [get, set]

Gets or sets the current position of this stream.

Value: The current position of this stream.

Exceptions

System.NotSupportedException The stream does not support seeking.

System.IO.IOException An I/O error occurs.

System.ArgumentOutOfRangeException Attempted to set the position to a negative value.

System.IO.EndOfStreamException Attempted seeking past the end of a stream that does not support this.

3.40 Asn1PrintableString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn18BitCharString](#).

Public Member Functions

- [Asn1PrintableString](#) (System.String data)
- [Asn1PrintableString](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.40.1 Detailed Description

This is a container class for holding the components of an ASN.1 printable string value.

3.40.2 Constructor & Destructor Documentation

3.40.2.1 Asn1PrintableString ()

The default constructor creates an empty string object.

3.40.2.2 Asn1PrintableString (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data value string

3.40.3 Member Function Documentation

3.40.3.1 override void Decode (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength) [virtual]

This method decodes an ASN.1 string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.40.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to stream an ASN.1 printable string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws Exception, if any exception thrown by the underlying System.IO.Stream.

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Reimplemented from [Asn1Type](#).

3.40.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.40.4 Member Data Documentation

3.40.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 19).

Reimplemented from [Asn1Type](#).

3.41 Asn1Real Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1Real](#) (double value)
- [Asn1Real](#) ()
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- void [Encode](#) (Asn1XmlEncoder buffer, String elemName, String nsPrefix, bool asText)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual void [EncodeAttribute](#) (Asn1XmlEncoder buffer, System.String attrName)
- virtual void [EncodeValue](#) (Asn1XmlEncoder buffer)
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (double value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()

Public Attributes

- double [mValue](#)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.41.1 Detailed Description

This class represents the ASN.1 REAL built-in type.

3.41.2 Constructor & Destructor Documentation

3.41.2.1 Asn1Real ()

The default constructor sets the double value to zero.

3.41.2.2 Asn1Real (double *value*)

This constructor creates an REAL object from a double value.

Parameters

value double value

3.41.3 Member Function Documentation

3.41.3.1 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes ASN.1 REAL value using the Packed Encoding Rules (PER). The length and contents components of the message are decoded. The decoded result is stored in the public member 'mValue' in this object.

Parameters

buffer PER Decode message buffer object

Reimplemented from [Asn1Type](#).

3.41.3.2 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 REAL value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.41.3.3 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 real value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.41.3.4 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 real value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.41.3.5 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes ASN.1 REAL value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Also throws any exception thrown by the Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.41.3.6 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 real value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.41.3.7 void Encode (Asn1XmlEncoder *buffer*, String *elemName*, String *nsPrefix*, bool *asText*)

This method encodes an ASN.1 real value according to XER encoding rules. It is for use with extended-XER.

Parameters

buffer Encode message buffer object

elemName Element name

asText If TRUE, encode special values as text. Otherwise, special values are encoded as empty elements.

3.41.3.8 virtual void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 real value according to Obj-Sys encoding rules. The value is encoded as text.

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

3.41.3.9 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 real value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1Type](#).

3.41.3.10 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes ASN.1 REAL value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

Reimplemented from [Asn1Type](#).

3.41.3.11 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 REAL value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

Reimplemented from [Asn1Type](#).

3.41.3.12 virtual void EncodeAttribute (Asn1XmlEncoder *buffer*, System.String *attrName*) [virtual]

This method encodes an ASN.1 real value using the XML Encoding as specified in the W3C XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

attrName Attribute name

3.41.3.13 virtual void EncodeValue (Asn1XmlEncoder *buffer*) [virtual]

This method encodes an ASN.1 real value using the XML encoding (non-XER).

Parameters

buffer Encode message buffer object

3.41.3.14 **override bool Equals (System.Object value)**

Determines whether the specified Object is equal to the current Object.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1Real](#).

Returns

`true` if the specified Object is equal to the current Object; otherwise, `false`.

3.41.3.15 **virtual bool Equals (double value) [virtual]**

This method compares this REAL value to the given value for equality.

Parameters

value The double value to compare with the current Object.

Returns

`true` if the specified double value is equal to the current Object; otherwise, `false`.

3.41.3.16 **override int GetHashCode ()**

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.41.3.17 **override System.String ToString ()**

This method will return a string representation of the REAL value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

3.41.4 **Member Data Documentation**

3.41.4.1 **new readonly Asn1Tag _TAG [static]**

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 9).

Reimplemented from [Asn1Type](#).

3.41.4.2 **double mValue**

This public member variable is where the double value is stored. This is the value that is encoded when one of the encode methods is called. It is also where the decoded result is stored when a Decode method is called.

3.42 Asn1Real10 Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1UTF8String](#).

Public Member Functions

- [Asn1Real10](#) (System.String data)
- [Asn1Real10](#) ()
- void [ConvertToDecimal](#) ()
- void [ConvertToNR3Form](#) (bool cxerForm)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1CerOutputStream outs, bool explicitTagging)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- virtual int [Encode](#) (Asn1DerEncodeBuffer buffer, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual void [EncodeAttribute](#) (Asn1XmlEncoder buffer, System.String attrName)
- byte [GetNumberForm](#) ()

Static Public Member Functions

- static byte [GetNumberForm](#) (System.String value)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.42.1 Detailed Description

This class represents the ASN.1 REAL BASE 10 built-in type.

3.42.2 Constructor & Destructor Documentation

3.42.2.1 Asn1Real10 ()

The default constructor sets the real10 value to zero.

3.42.2.2 Asn1Real10 (System.String data)

This constructor creates an real10 object from a string value.

Parameters

data String value

3.42.3 Member Function Documentation

3.42.3.1 void ConvertToDecimal ()

This method convert the contained real10 value to XML decimal. Result number placed in mStringBuffer field.

3.42.3.2 void ConvertToNR3Form (bool *cxerForm*)

This method convert the contained real10 value to NR3 form. NR3 form number placed in mStringBuffer field.

3.42.3.3 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an real10 value using the Packed Encoding Rules (PER). The length and contents components of the message are decoded. The decoded result is stored in the public member 'value' in this object.

Parameters

buffer PER Decode message buffer object

Returns

void. Decoded result is stored in the 'value' member variable and can be accessed using '<object>.value'.

Reimplemented from [Asn1UTF8String](#).

3.42.3.4 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 real10 value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1UTF8String](#).

3.42.3.5 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 real10 value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

outs PER Encode message buffer object

<throws> IOException Any exception thrown by the Asn1PerOutputStream. </throws> <throws> [Asn1Exception](#) Thrown, if operation is failed. </throws>

Reimplemented from [Asn1UTF8String](#).

3.42.3.6 override void Encode (Asn1CerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to the stream an ASN.1 real10 value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Canonical Encoding Rules (CER).

Parameters

outs CER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

Reimplemented from [Asn1Type](#).

3.42.3.7 override void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method encodes and writes to the stream an ASN.1 real10 value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

<throws> IOException Any exception thrown by the underlying OutputStream. </throws> <throws> Asn1Exception Thrown, if operation is failed. </throws>

Reimplemented from [Asn1UTF8String](#).

3.42.3.8 override void Encode (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix) [virtual]

This method encodes an ASN.1 real10 value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

Reimplemented from [Asn1CharString](#).

3.42.3.9 override void Encode (Asn1XerEncoder buffer, System.String elemName) [virtual]

This method encodes an ASN.1 real10 value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1CharString](#).

3.42.3.10 **override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]**

This method encodes an real10 value using the Packed Encoding Rules (PER). The length and contents components of the message are encoded.

Parameters

buffer PER Encode message buffer object

Returns

Length of component or negative status value

Reimplemented from [Asn1UTF8String](#).

3.42.3.11 **virtual int Encode (Asn1DerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method encodes an ASN.1 real10 value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Distinguished Encoding Rules (DER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

3.42.3.12 **override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method encodes an ASN.1 real10 value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of component or negative status value

Reimplemented from [Asn1UTF8String](#).

3.42.3.13 **virtual void EncodeAttribute (Asn1XmlEncoder *buffer*, System.String *attrName*) [virtual]**

This method encodes an ASN.1 real10 value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

attribute Element attribute value

3.42.3.14 byte GetNumberForm ()

This method calculates the number form of the contained real10 value.

Parameters

value Real10 value in which to count bits.

Returns

Number form.

3.42.3.15 static byte GetNumberForm (System.String value) [static]

This method calculates the number form of an real10 value.

Parameters

value Real10 value in which to count bits.

Returns

Number form.

3.42.4 Member Data Documentation

3.42.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 9).

Reimplemented from [Asn1UTF8String](#).

3.43 Asn1RelativeOID Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier](#).

Public Member Functions

- [Asn1RelativeOID](#) (int[] value)
- [Asn1RelativeOID](#) ()
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- new static readonly [Asn1Tag_TAG](#)

3.43.1 Detailed Description

This is a container class for holding the components of an ASN.1 relative object identifier value.

3.43.2 Constructor & Destructor Documentation

3.43.2.1 Asn1RelativeOID ()

This constructor creates an empty object identifier that can be used in a Decode method call to receive an OID value.

3.43.2.2 Asn1RelativeOID (int[] value)

This constructor initializes the object identifier from the given array of integer subidentifier values.

Parameters

value Array of subidentifiers

3.43.3 Member Function Documentation

3.43.3.1 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 relative object identifier value using the packed encoding rules (PER).

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.2 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 relative object identifier value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.3 override void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 RELATIVE-OID value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.4 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 RELATIVE-OID value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.5 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 relative object identifier value using the packed encoding rules (PER).

The value to be encoded is stored in the `mValue` public member variable within this class.

Also throws any exception thrown by the `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.6 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 object identifier value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.7 override void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 RELATIVE-OID value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

elemName Element name

nsPrefix Element namespace value

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.8 override void Encode (Asn1XerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 RELATIVE-OID value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object

elemName Element name

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.9 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an ASN.1 relative object identifier value using the packed encoding rules (PER). The value to be encoded is stored in the `mValue` public member variable within this class.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.3.10 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 relative object identifier value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length of encoded component in octets

Reimplemented from [Asn1ObjectIdentifier](#).

3.43.4 Member Data Documentation

3.43.4.1 new static readonly Asn1Tag _TAG [static]

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 13).

Reimplemented from [Asn1ObjectIdentifier](#).

3.44 Asn1SeqOrderException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1SeqOrderException \(\)](#)

3.44.1 Detailed Description

This class defines the 'ASN.1 sequence order' exception that is thrown when an element is received in a SEQUENCE construct that is not in the correct order..

3.44.2 Constructor & Destructor Documentation

3.44.2.1 Asn1SeqOrderException ()

This constructor creates an exception object with a textual message describing the element that was received out-of-order.

3.45 Asn1Status Class Reference

Public Attributes

- const int [INDEFLEN](#) = - 9999

3.45.1 Detailed Description

This class defines common constants used in the run-time and generated code. Note that all error reporting in the C# version is done via exceptions. Therefore, there are very few status values defined in the class.

3.45.2 Member Data Documentation

3.45.2.1 const int INDEFLEN = - 9999

This constant indicates an indefinite length field was parsed

3.46 Asn1T61String Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString](#).

Public Member Functions

- [Asn1T61String](#) (System.String data)
- [Asn1T61String](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.46.1 Detailed Description

This is a container class for holding the components of an ASN.1 teletex (T61) string value.

3.46.2 Constructor & Destructor Documentation

3.46.2.1 [Asn1T61String](#) ()

The default constructor creates an empty string object.

3.46.2.2 [Asn1T61String](#) (System.String *data*)

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data String value of T61String

3.46.3 Member Function Documentation

3.46.3.1 override void [Decode](#) (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 T61String value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.46.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 T61String value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.46.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 T61String type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.46.4 Member Data Documentation

3.46.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 20).

Reimplemented from [Asn1Type](#).

3.47 Asn1Tag Class Reference

Public Member Functions

- [Asn1Tag](#) (short tagclass, short form, int idCode)
- [Asn1Tag](#) ()
- bool [Equals](#) ([Asn1Tag](#) tag)
- virtual bool [Equals](#) (short tagclass, short form, int idCode)
- virtual bool [IsEOC](#) ()
- override System.String [ToString](#) ()

Public Attributes

- const short [APPL](#) = (short) (0x40)
- const short [Bit8Mask](#) = (short) (0x80)
- const short [ClassMask](#) = (short) (0xC0)
- const short [CONS](#) = (short) (0x20)
- const short [CTXT](#) = (short) (0x80)
- const bool [EXPL](#) = true
- const short [EXTIDCODE](#) = (short) (0x1F)
- const short [FormMask](#) = (short) (0x20)
- const short [IDMask](#) = (short) (0x1F)
- const bool [IMPL](#) = false
- const short [L7BitsMask](#) = (short) (0x7f)
- short [mClass](#)
- short [mForm](#)
- int [mIDCode](#)
- const short [PRIM](#) = (short) (0x00)
- const short [PRIV](#) = (short) (0xC0)
- const short [UNIV](#) = (short) (0x00)

Static Public Attributes

- static readonly [Asn1Tag](#) [ENUM](#)
- static readonly [Asn1Tag](#) [EOC](#)
- static readonly [Asn1Tag](#) [SEQUENCE](#)
- static readonly [Asn1Tag](#) [SET](#)

Properties

- virtual bool [Constructed](#) [get]

3.47.1 Detailed Description

This is a container class for holding the components of an ASN.1 tag value.

3.47.2 Constructor & Destructor Documentation

3.47.2.1 Asn1Tag ()

The default constructor initializes all fields to zero

3.47.2.2 Asn1Tag (short tagclass, short form, int idCode)

This constructor initializes all fields to the given values

Parameters

tagclass Tag class value (UNIV, APPL, CTXT, or PRIV)

form Tag form value (PRIM or CONS)

idCode Tag identifier code

3.47.3 Member Function Documentation

3.47.3.1 bool Equals (Asn1Tag tag)

This method compares this tag with the given tag value for equality.

Parameters

tag [Asn1Tag](#) object to which this tag is to be compared

Returns

`true` if the specified Tags are equal; otherwise, `false`.

3.47.3.2 virtual bool Equals (short tagclass, short form, int idCode) [virtual]

This method compares this tag with the given tag value for equality.

Parameters

tagclass Tag class value (UNIV, APPL, CTXT, or PRIV)

form Tag form value (PRIM or CONS)

idCode Tag identifier code

Returns

`true` if the specified Tags are equal; otherwise, `false`.

3.47.3.3 virtual bool IsEOC () [virtual]

This method tests if the tag is an end-of-contents (EOC) tag.

Returns

True if tag is an EOC.

3.47.3.4 **override System.String ToString ()**

This method will return a formatted string representing the tag value. The form is "[<class> <ID>]" (i.e. the ASN.1 standard syntax for a tag value).

Returns

Formatted tag string

3.47.4 **Member Data Documentation**

3.47.4.1 **const short APPL = (short) (0x40)**

Mask value for an APPLICATION tag

3.47.4.2 **const short Bit8Mask = (short) (0x80)**

Bit 8 (MSB) octet mask value

3.47.4.3 **const short ClassMask = (short) (0xC0)**

Mask value to mask the class bits from a tag

3.47.4.4 **const short CONS = (short) (0x20)**

Mask value for CONSTRUCTED form

3.47.4.5 **const short CTXT = (short) (0x80)**

Mask value for a context-specific tag

3.47.4.6 **readonly Asn1Tag ENUM [static]**

ASN.1 ENUMERATED type tag value

3.47.4.7 **readonly Asn1Tag EOC [static]**

ASN.1 end-of-contents (EOC) type tag value

3.47.4.8 **const bool EXPL = true**

This specifies that explicit tagging should be used.

3.47.4.9 **const short EXTIDCODE = (short) (0x1F)**

Mask value for extended tag identifier indicator

3.47.4.10 const short FormMask = (short) (0x20)

Mask value to mask the form bit from a tag

3.47.4.11 const short IDMask = (short) (0x1F)

Mask value to mask the tag ID bits from a tag

3.47.4.12 const bool IMPL = false

This specifies that implicit tagging should be used.

3.47.4.13 const short L7BitsMask = (short) (0x7f)

Lower 7 bits octet mask value

3.47.4.14 short mClass

Tag class value (UNIV, APPL, CTXT, or PRIV)

3.47.4.15 short mForm

Tag form value (PRIM or CONS)

3.47.4.16 int mIDCode

Tag ID code

3.47.4.17 const short PRIM = (short) (0x00)

Mask value for PRIMITIVE form

3.47.4.18 const short PRIV = (short) (0xC0)

Mask value for a PRIVATE tag

3.47.4.19 readonly Asn1Tag SEQUENCE [static]

ASN.1 SEQUENCE type tag value

3.47.4.20 readonly Asn1Tag SET [static]

ASN.1 SET type tag value

3.47.4.21 const short UNIV = (short) (0x00)

Mask value for a UNIVERSAL tag

3.47.5 Property Documentation

3.47.5.1 virtual bool Constructed [get]

Gets the tag is constructed.

Value: true if tag is constructed; otherwise false.

3.48 Asn1Time Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn18BitCharString](#).

Inherited by [Asn1GeneralizedTime](#), and [Asn1UTCTime](#).

Public Member Functions

- [Asn1Time](#) (System.String data, short typeCode, bool useDerRules)
- [Asn1Time](#) (short typeCode, bool useDerRules)
- virtual void [Clear](#) ()
- virtual int [CompareTo](#) (System.Object other)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- override void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1PerOutputStream outs)
- virtual void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging, [Asn1Tag](#) tag)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- void [EncodeXER](#) (Asn1XmlEncoder buffer, String elemName, String nsPrefix)
- virtual void [EncodeXMLData](#) (Asn1XmlXerEncoder buffer)
- override bool [Equals](#) (System.Object value)
- virtual int [GetDiff](#) ()
- override int [GetHashCode](#) ()
- virtual System.DateTime [GetTime](#) ()
- abstract void [ParseString](#) (System.String data)
- virtual void [ParseXmlString](#) (System.String data)
- virtual void [SetDiff](#) (int inMinutes)
- virtual void [SetDiff](#) (int dhour, int dminute)
- virtual void [SetTime](#) (System.DateTime time)

Static Public Member Functions

- static void [PutInteger](#) (System.Text.StringBuilder data, int width, int value)

Public Attributes

- const int [Apr](#) = 4
- const int [April](#) = 4
- const int [Aug](#) = 8
- const int [August](#) = 8
- const int [Dec](#) = 12
- const int [December](#) = 12
- const int [Feb](#) = 2
- const int [February](#) = 2
- const int [Jan](#) = 1
- const int [January](#) = 1
- const int [Jul](#) = 7
- const int [July](#) = 7
- const int [Jun](#) = 6
- const int [June](#) = 6

- const int [Mar](#) = 3
- const int [March](#) = 3
- const int [May](#) = 5
- const int [Nov](#) = 11
- const int [November](#) = 11
- const int [Oct](#) = 10
- const int [October](#) = 10
- const int [Sep](#) = 9
- const int [September](#) = 9

Protected Member Functions

- abstract internal bool [CompileString](#) ()
- internal override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength, [Asn1Tag](#) tag)
- internal override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging, [Asn1Tag](#) tag)
- virtual internal void [Init](#) ()
- virtual internal void [PutInteger](#) (int width, int value)
- virtual internal void [SafeParseString](#) ()

Static Protected Member Functions

- static internal char [CharAt](#) (System.String s, int index)
- static internal int [ParseInt](#) (System.String str, [IntHolder](#) off, int len)

Protected Attributes

- internal int [day](#)
- internal bool [derRules](#)
- internal int [diffHour](#)
- internal int [diffMin](#)
- internal int [hour](#)
- internal int [minute](#)
- internal int [month](#)
- internal bool [parsed](#)
- internal string [secFraction](#)
- internal int [second](#)
- internal bool [utcFlag](#)
- internal int [year](#)

Properties

- virtual bool [\[set\]](#)
- virtual int [Day](#) [get, set]
- virtual int [DiffHour](#) [get, set]
- virtual int [DiffMinute](#) [get]
- virtual string [Fraction](#) [get, set]
- virtual int [Hour](#) [get, set]
- virtual int [Minute](#) [get, set]

- virtual int [Month](#) [get, set]
- virtual int [Second](#) [get, set]
- virtual bool [UTC](#) [get, set]
- virtual int [Year](#) [get, set]

3.48.1 Detailed Description

This is a base class for holding the components of an ASN.1 generalized and universal times string value.

3.48.2 Constructor & Destructor Documentation

3.48.2.1 `Asn1Time` (short *typeCode*, bool *useDerRules*)

This constructor creates an empty time string object.

Parameters

- typeCode* Integer constant from [Asn1Type](#) class ([Asn1Type.GeneralTime](#) or [Asn1Type.UTCtime](#)).
- useDerRules* 'true' if time string should be encoded with DER/PER.

See also

- <seealso cref=Asn1Type.[GeneralTime](#) [GeneralTime](#) code
- <seealso cref=Asn1Type.[UTCtime](#) [UTCtime](#) code

3.48.2.2 `Asn1Time` (System.String *data*, short *typeCode*, bool *useDerRules*)

This constructor creates a time string from String value.

Parameters

- data* String representation of time value
- typeCode* Integer constant from [Asn1Type](#) class ([Asn1Type.GeneralTime](#) or [Asn1Type.UTCtime](#)).
- useDerRules* 'true' if time string should be encoded with DER/PER.

See also

- <seealso cref=Asn1Type.[GeneralTime](#) [GeneralTime](#) code
- <seealso cref=Asn1Type.[UTCtime](#) [UTCtime](#) code

3.48.3 Member Function Documentation

3.48.3.1 `static internal char CharAt` (System.String *s*, int *index*) [**static**, **protected**]

Returns the character at the specified index in the specified string. If index is out of bounds, then '\u0000' character will be returned.

Parameters

- s* String value

index Index of Character in the string

Returns

Character at the specified index. or '\u0000'.

3.48.3.2 virtual void Clear () [virtual]

This method clears time string. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Reimplemented in [Asn1UTCTime](#).

3.48.3.3 virtual int CompareTo (System.Object other) [virtual]

This method compares this object with [Asn1Time](#) class instance or with System.DateTime instance. Returns a negative integer, zero, or a positive integer as this object is less than, equal to, or greater than the specified object. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

other the Object to be compared.

Returns

The difference in Ticks with the specified object.

Reimplemented in [Asn1GeneralizedTime](#), and [Asn1UTCTime](#).

3.48.3.4 abstract internal bool CompileString () [protected, pure virtual]

Compiles new time string according X.680 (clauses 41, 42) and ISO 8601.

Returns

true, if succeed, or false code, if error.

Implemented in [Asn1GeneralizedTime](#), and [Asn1UTCTime](#).

3.48.3.5 override void Decode (Asn1PerDecodeBuffer buffer) [virtual]

This method is the base implementation of the standard Packed Encoding Rules (PER) Decode method. It throws an exception because it should never be invoked by compiler generated code.

Parameters

buffer PER Encode message buffer object

Reimplemented from [Asn18BitCharString](#).

3.48.3.6 internal override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*, Asn1Tag *tag*) [protected, virtual]

This method decodes an ASN.1 Time value including the UNIVERSAL tag value and length if explicit tagging is specified. It is a protected method that can only be accessed by objects subclassed from this type.

Parameters

buffer Decode message buffer object
explicitTagging Flag indicating element is explicitly tagged
implicitLength Length of contents if implicit
tag Universal tag to apply

Reimplemented from [Asn1CharString](#).

3.48.3.7 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes ASN.1 Time type, using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded
attrs Attributes string from element tag

Reimplemented from [Asn1CharString](#).

3.48.3.8 override void Encode (Asn1XmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes ASN.1 time into xsd:dateTime format with element and namespace prefix tag according to the XML Encoding as specified in the XML schema standard(asn2xsd). This is for use with Obj-Sys XML encoding rules.

Parameters

buffer Encode message buffer object
elemName XML element name used to wrap string
nsPrefix XML element namespace value

Reimplemented from [Asn1CharString](#).

3.48.3.9 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes and writes to stream an ASN.1 time string value using the standard Packed Encoding Rules (PER) encode method.

Also throws any exception thrown by the Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn18BitCharString](#).

3.48.3.10 virtual void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*, Asn1Tag *tag*)
[virtual]

This method encodes and writes to the stream an ASN.1 time string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.3.11 override void Encode (Asn1PerEncodeBuffer *buffer*) **[virtual]**

This method is the base implementation of the standard Packed Encoding Rules (PER) encode method. It throws an exception because it should never be invoked by compiler generated code.

Parameters

buffer PER Encode message buffer object

Reimplemented from [Asn18BitCharString](#).

3.48.3.12 internal override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*, Asn1Tag *tag*)
[protected, virtual]

This method encodes ASN.1 time string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified (the universal identifier must be provided by the caller).

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

tag Universal tag to apply

Returns

Length in octets of encoded component

Reimplemented from [Asn1CharString](#).

3.48.3.13 void EncodeXER (Asn1XmlEncoder *buffer*, String *elemName*, String *nsPrefix*)

This method encodes this ASN.1 time according to XER encoding rules. It is used by generated code when compiling for extended-XER.

Parameters

buffer Encode message buffer object

<param name="elemName"> XML element name used to wrap string

<param name="nsPrefix"> Element namespace prefix value

3.48.3.14 virtual void EncodeXMLData (Asn1XmlXerEncoder *buffer*) [virtual]

This method encodes this ASN.1 time string into xsd:dateTime format.

XML dateTime format is YYYY-MM-DDTHH:MM:SS[.SSSS][Z|(+-) HH:MM]

Parameters

buffer String buffer to hold the converted xml time string

Exceptions

Asn1Exception any exception exist in Asn.1 Generalized Time string

3.48.3.15 override bool Equals (System.Object *value*)

This method compares this object with [Asn1Time](#) class instance or with Calendar instance. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1Time](#) or System.DateTime.

Returns

true if the specified Object is equal to the current Object; otherwise, false.

Reimplemented from [Asn1CharString](#).

3.48.3.16 virtual int GetDiff () [virtual]

This method returns the difference between the time zone of the object and Coordinated Universal Time (UTC), in minutes. The UTC time is the sum of the local time and positive or negative time difference. Note that the return value may differentiate for different inherited [Asn1Time](#) classes.

Returns

The negative or positive difference, in minutes, between the time zone of the object and UTC time (-12*60..+12*60) is returned if the operation is successful.

Exceptions

Asn1Exception Thrown, if operation is failed.

3.48.3.17 **override int GetHashCode ()**

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

Reimplemented from [Asn1CharString](#).

3.48.3.18 **virtual System.DateTime GetTime () [virtual]**

This method converts the time string to the System.DateTime value. If time represented as UTC time plus or minus difference time, then the result System.DateTime will ignore zone offset, as it doesn't support it. Note that the return value may differentiate for different inherited [Asn1Time](#) classes.

Returns

The System.DateTime value.

3.48.3.19 **virtual internal void Init () [protected, virtual]**

This method initializes the [Asn1Time](#) class member variables.

Reimplemented in [Asn1UTCTime](#).

3.48.3.20 **static internal int ParseInt (System.String str, IntHolder off, int len) [static, protected]**

Parses integer value from String.

Parameters

- str* string is containing integer to be parsed.
- off* The offset in array at which to begin parse.
- len* number of digits to be parsed.

Returns

Parsed integer value.

3.48.3.21 **abstract void ParseString (System.String data) [pure virtual]**

This method parses passed time string. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

- data* String representation of Time to be parsed.

Exceptions

- [Asn1Exception](#) Thrown, if operation is failed.

Implemented in [Asn1GeneralizedTime](#), and [Asn1UTCTime](#).

3.48.3.22 virtual void ParseXmlString (System.String *data*) [virtual]

This method parses the given time string value. String must be in XML schema dateTime format. It will throw an exception if the string is not in the valid time format.

Parameters

data The time string value to be parsed.

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.3.23 virtual internal void PutInteger (int *width*, int *value*) [protected, virtual]

Puts integer in string buffer

Parameters

width number of digits

value value to be put

3.48.3.24 static void PutInteger (System.Text.StringBuilder *data*, int *width*, int *value*) [static]

Puts integer in string buffer

Parameters

data destination buffer

width number of digits in integer value

value integer value to be added

3.48.3.25 virtual internal void SafeParseString () [protected, virtual]

This method internally calls the ParseString method for this class. But will not throw any exception, if error in string format.

3.48.3.26 virtual void SetDiff (int *inMinutes*) [virtual]

This method sets the difference between the time zone of the object and Coordinated Universal Time (UTC), in minutes. The UTC time is the sum of the local time and positive or negative time difference. Note that the action of this method may differ for different inherited [Asn1Time](#) classes.

Parameters

inMinutes The negative or positive difference, in minutes, between the time zone of the object and UTC time (-12*60..+12*60).

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.3.27 virtual void SetDiff (int *dhour*, int *dminute*) [virtual]

This method sets the hour and minute components of the difference between the time zone of the object and Coordinated Universal Time (UTC). The UTC time is the sum of the local time and positive or negative time difference. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

dhour The negative or positive hour component of the difference between the time zone of the object and UTC time (-12..+12).

dminute The negative or positive minute component of the difference between the time zone of the object and UTC time (-59..+59).

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.3.28 virtual void SetTime (System.DateTime *time*) [virtual]

This method converts the System.DateTime value to time string. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

time The System.DateTime time value.

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented in [Asn1UTCTime](#).

3.48.4 Member Data Documentation

3.48.4.1 const int Apr = 4

Constant to represent April month

3.48.4.2 const int April = 4

Constant to represent April month

3.48.4.3 const int Aug = 8

Constant to represent August month

3.48.4.4 const int August = 8

Constant to represent August month

3.48.4.5 internal int day [protected]

Day of month component. Legal interval is 1..31.

3.48.4.6 const int Dec = 12

Constant to represent December month

3.48.4.7 const int December = 12

Constant to represent December month

3.48.4.8 internal bool derRules [protected]

Indicates DER is used (or CER/PER).

3.48.4.9 internal int diffHour [protected]

Zone offset's hour component. Legal interval is -12..+12.

3.48.4.10 internal int diffMin [protected]

Zone offset's minute component. Legal interval is -59..+59.

3.48.4.11 const int Feb = 2

Constant to represent February month

3.48.4.12 const int February = 2

Constant to represent February month

3.48.4.13 internal int hour [protected]

Hour component. Legal interval is 0..23.

3.48.4.14 const int Jan = 1

Constant to represent January month

3.48.4.15 const int January = 1

Constant to represent January month

3.48.4.16 const int Jul = 7

Constant to represent July month

3.48.4.17 const int July = 7

Constant to represent July month

3.48.4.18 const int Jun = 6

Constant to represent June month

3.48.4.19 const int June = 6

Constant to represent June month

3.48.4.20 const int Mar = 3

Constant to represent March month

3.48.4.21 const int March = 3

Constant to represent March month

3.48.4.22 const int May = 5

Constant to represent May month

3.48.4.23 internal int minute [protected]

Minute component. Legal interval is 0..59.

3.48.4.24 internal int month [protected]

Month component. Legal interval is 1..12.

3.48.4.25 const int Nov = 11

Constant to represent November month

3.48.4.26 const int November = 11

Constant to represent November month

3.48.4.27 const int Oct = 10

Constant to represent October month

3.48.4.28 const int October = 10

Constant to represent October month

3.48.4.29 **internal bool parsed** [protected]

Indicates string parsed or not.

3.48.4.30 **internal string secFraction** [protected]

Second's fraction component. Legal interval is 0..INF.

3.48.4.31 **internal int second** [protected]

Second component. Legal interval is 0..59.

3.48.4.32 **const int Sep = 9**

Constant to represent September month

3.48.4.33 **const int September = 9**

Constant to represent September month

3.48.4.34 **internal bool utcFlag** [protected]

Indicates UTC flag ('Z') set or not.

3.48.4.35 **internal int year** [protected]

Year component. Legal interval is 0..9999.

3.48.5 **Property Documentation**

3.48.5.1 **virtual bool** [set]

Sets the 'use DER' flag which enforces the DER rules when time strings are constructed or parsed.

Value: `true` for DER rule; otherwise `false`

3.48.5.2 **virtual int Day** [get, set]

Gets or Sets the day of month number component of the time value. The number of the first day in month is 1, the number of the last day may be in interval from 28 to 31. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Day of month component (1..31)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.5.3 virtual int DiffHour [get, set]

Gets or Sets the hour component of the difference between the time zone of the object and Coordinated Universal Time (UTC). The UTC time is the sum of the local time and positive or negative time difference. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: The negative or positive hour component of the difference between the time zone of the object and UTC time (-12..+12)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.5.4 virtual int DiffMinute [get]

Gets or Sets the minute component of the difference between the time zone of the object and Coordinated Universal Time (UTC). The UTC time is the sum of the local time and positive or negative time difference. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: The negative or positive minute component of the difference between the time zone of the object and UTC time (-59..+59)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.5.5 virtual string Fraction [get, set]

Gets or Sets the second's decimal fraction component of the time value. Second's decimal fraction is represented by one digit from 0 to 9. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Second's decimal fraction component (0..9)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented in [Asn1UTCTime](#).

3.48.5.6 virtual int Hour [get, set]

Gets or Sets the hour component of the time value. As the ISO 8601 is based on the 24-hour timekeeping system, two digits represent hours from 00 to 23. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Hour component (0..23)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.48.5.7 virtual int Minute [get, set]

Gets or Sets the minute component of the time value. Minutes are represented by two digits from 00 to 59. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Minute component (0..59)

Exceptions

Asn1Exception Thrown, if operation is failed.

3.48.5.8 virtual int Month [get, set]

Gets or Sets the month number component of the time value. The number of January is 1, February - 2, December - 12. You may use enumerating values for months decoding: [Asn1Time.January](#), [Asn1Time.February](#), etc. Also you can use short aliases for months: [Asn1Time.Jan](#), [Asn1Time.Feb](#), etc. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Month component (1..12)

Exceptions

Asn1Exception Thrown, if operation is failed.

3.48.5.9 virtual int Second [get, set]

Gets or Sets the second component of the time value. Seconds are represented by two digits from 00 to 59. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Second component (0..59)

Exceptions

Asn1Exception Thrown, if operation is failed.

3.48.5.10 virtual bool UTC [get, set]

Gets or Sets the UTC flag state. If the UTC flag is true, then the time is an UTC time and symbol 'Z' is added at the end of time string. Otherwise, it is a local time.

Value: UTC flag state.

Exceptions

Asn1Exception Thrown, if operation is failed.

3.48.5.11 virtual int Year [get, set]

Gets or Sets the year component of the time value. Note that the behaviour value may differentiate for different inherited [Asn1Time](#) classes.

Value: Year component (full 4 digits).

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1UTCTime](#).

3.49 Asn1TraceHandler Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1NamedEventHandler](#).

Public Member Functions

- [Asn1TraceHandler](#) (System.IO.StreamWriter ps)
- [Asn1TraceHandler](#) ()
- virtual void [Characters](#) (System.String svalue, short typeCode)
- virtual void [EndElement](#) (System.String name, int index)
- virtual void [StartElement](#) (System.String name, int index)

3.49.1 Detailed Description

This class is a standard named event handler for printing the data in an encoded message in a human-readable format. Note that this handler will work with data encoded using any of the encoding rules (BER, DER, or PER).

3.49.2 Constructor & Destructor Documentation

3.49.2.1 Asn1TraceHandler ()

This constructor sets the output stream to standard output.

3.49.2.2 Asn1TraceHandler (System.IO.StreamWriter ps)

This constructor sets the output stream to the given StreamWriter.

Parameters

ps StreamWriter object

3.49.3 Member Function Documentation

3.49.3.1 virtual void Characters (System.String svalue, short typeCode) [virtual]

The characters callback method is invoked when content (primitive data) is encountered. A stringified representation of the parsed value is returned.

Parameters

svalue Stringified representation of the parsed value. The representation will be in ASN.1 value format.

typeCode Identifier specifying the type of the parsed data variable. The enumerated list of values that might appear here is provided in the the [Asn1Type](#) class (see the documentation on this class for a full list of the names).

Implements [Asn1NamedEventHandler](#).

3.49.3.2 virtual void EndElement (System.String name, int index) [virtual]

The endElement callback method is invoked when the end of an element within a constructed type (SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE) is detected.

Parameters

name Name of the parsed element.

index Index of element in array. Only used for SEQUENCE OF or SET OF elements. Set to -1 for all others.

Implements [Asn1NamedEventHandler](#).

3.49.3.3 virtual void StartElement (System.String name, int index) [virtual]

The StartElement callback method is invoked when the start of an element within a constructed type (SEQUENCE, SET, SEQUENCE OF, SET OF, or CHOICE) is encountered.

Parameters

name Name of the parsed element.

index Index of element in array. Only used for SEQUENCE OF or SET OF elements. Set to -1 for all others.

Implements [Asn1NamedEventHandler](#).

3.50 Asn1Type Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1TypeIF](#).

Inherited by [Asn1BigInteger](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1CharString](#), [Asn1Choice](#), [Asn1Enumerated](#), [Asn1Integer](#), [Asn1Null](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1Real](#), and [Asn1UniversalString](#).

Public Member Functions

- virtual void [Decode](#) (System.Object reader, System.IO.Stream byteStream)
- virtual void [Decode](#) (System.Object reader, System.String xmlURI)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer)
- virtual void [Decode](#) (Asn1BerDecodeBuffer buffer)
- virtual void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXML](#) (String buffer, String attrs)
- virtual void [Encode](#) (Asn1PerOutputStream outs)
- virtual void [Encode](#) (Asn1CerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- virtual void [Encode](#) (Asn1XerEncoder buffer)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer)
- virtual int [Encode](#) (Asn1BerEncodeBuffer buffer)
- virtual int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual bool [Equals](#) ([Asn1Type](#) obj)
- virtual void [Indent](#) (System.IO.TextWriter outs, int level)
- virtual bool [IsOpenType](#) ()
- virtual bool [MatchTypeName](#) (System.String typeName)
- virtual void [Pdiag](#) (System.String s)
- virtual void [Print](#) (System.String varName)
- virtual void [Print](#) (System.IO.TextWriter outs, System.String varName, int level)
- void [SetKey](#) (byte[] rtkey)
- virtual void [SetOpenType](#) ()

Static Public Member Functions

- static System.String [GetTypeNames](#) (short typeCode)
- static void [SetKey2](#) (byte[] rtkey)

Public Attributes

- const short [BIT_STRING](#) = 3
- const short [BMPString](#) = 30
- const short [BOOLEAN](#) = 1
- const short [DATE](#) = 31
- const short [ENUMERATED](#) = 10
- const short [EOC](#) = 0
- const short [EXTERNAL](#) = 8
- const short [GeneralString](#) = 27
- const short [GeneralTime](#) = 24
- const short [GraphicString](#) = 25

- const short [IA5String](#) = 22
- const short [INTEGER](#) = 2
- const short [NULL](#) = 5
- const short [NumericString](#) = 18
- const short [OBJECT_IDENTIFIER](#) = 6
- const short [ObjectDescriptor](#) = 7
- const short [OCTET_STRING](#) = 4
- const short [PrintableString](#) = 19
- const short [REAL](#) = 9
- const short [RelativeOID](#) = 13
- const short [SEQUENCE](#) = 16
- const short [SET](#) = 17
- const short [T61String](#) = [TeletexString](#)
- const short [TeletexString](#) = 20
- const short [TIME](#) = 14
- const short [UniversalString](#) = 28
- const short [UTCTime](#) = 23
- const short [UTF8String](#) = 12
- const short [VideotexString](#) = 21
- const short [VisibleString](#) = 26

Static Public Attributes

- static readonly [Asn1Tag_TAG](#) = new [Asn1Tag](#)([Asn1Tag.UNIV](#), [Asn1Tag.PRIM](#), [Asn1Type.EOC](#))

Protected Member Functions

- virtual internal int [MatchTag](#) ([Asn1BerDecodeBuffer](#) buffer, [Asn1Tag](#) tag)
- virtual internal int [MatchTag](#) ([Asn1BerDecodeBuffer](#) buffer, short tagClass, short tagForm, int tagIDCode)

Properties

- virtual int [Length](#) [get]

3.50.1 Detailed Description

This is the base class for all ASN.1 built-in types.

3.50.2 Member Function Documentation

3.50.2.1 virtual void Decode ([System.Object](#) *reader*, [System.IO.Stream](#) *byteStream*) [virtual]

This method declaration is the signature of the standard XML Encoding Rules (XER) Decode method.

Also throws any IO exception from the parser, possibly from a byte stream or character stream supplied by the application.

Parameters

reader XML reader object

byteStream Input byte stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Implements [Asn1TypeIF](#).

3.50.2.2 virtual void Decode (System.Object reader, System.String xmlURI) [virtual]

This method declaration is the signature of the standard XML Encoding Rules (XER) Decode method.

Also throws any IO exception from the parser, possibly from a byte stream or character stream supplied by the application.

Parameters

reader XML reader object

xmlURI URI of a source

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Implements [Asn1TypeIF](#).

3.50.2.3 virtual void Decode (Asn1PerDecodeBuffer buffer) [virtual]

This method is the base implementation of the standard Packed Encoding Rules (PER) Decode method. It throws an exception because it should never be invoked. Inherited class implements this method in Compiler generated code.

Parameters

buffer PER Encode message buffer object

Exceptions

[Asn1Exception](#) if invoked directly

Implements [Asn1TypeIF](#).

Reimplemented in [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Time](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VarWidthCharString](#), and [Asn1BigInteger](#).

3.50.2.4 virtual void Decode (Asn1BerDecodeBuffer buffer) [virtual]

This method is used to Decode a message that is encoded in BER or DER format. This version of the method sets tagging to explicit ([Asn1Tag.EXPL](#)) and implicit length to zero.

Parameters

buffer Decode message buffer object

3.50.2.5 virtual void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method is used to Decode a message that is encoded in BER or DER format.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating explicit tag should be parsed from the encoded type.

implicitLength Length of the contents field (only required if explicit is false).

Implements [Asn1TypeIF](#).

Reimplemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.50.2.6 virtual void DecodeXML (String *buffer*, String *attrs*) [virtual]

This method decodes the XML content of a simple type.

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.50.2.7 virtual void Encode (Asn1PerOutputStream *outs*) [virtual]

This method is the base implementation of the standard Packed Encoding Rules (PER) encode method using output stream. It throws an exception because it should never be invoked by compiler generated code.

Also throws any exception thrown by the [Asn1PerOutputStream](#).

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Implements [Asn1TypeIF](#).

Reimplemented in [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Integer](#), [Asn1Null](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Time](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VarWidthCharString](#), and [Asn1BigInteger](#).

3.50.2.8 virtual void Encode (Asn1CerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method writes to the stream an encoded ASN.1 type value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Cer Encoding Rules (CER).

Throws, Exception thrown by [C# System.IO.Stream](#) for I/O error

Parameters

outs CER Output Stream object
explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented in [Asn1Real10](#).

3.50.2.9 virtual void Encode (Asn1BerOutputStream outs, bool explicitTagging) [virtual]

This method writes to the stream an encoded ASN.1 type value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object
explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Implements [Asn1TypeIF](#).

Reimplemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.50.2.10 virtual void Encode (Asn1XerEncoder buffer, System.String elemName) [virtual]

This method is the base implementation of the standard XML Encoding Rules (XER) encode method. It throws an exception because it should never be invoked by compiler generated code.

Also throws any exception thrown by the underlying stream.

Parameters

buffer XER Encode message buffer object
elemName XML element name of item

Exceptions

Asn1Exception if invoked directly

Implements [Asn1TypeIF](#).

Reimplemented in [Asn1BitString](#), [Asn1Boolean](#), [Asn1CharString](#), [Asn1Enumerated](#), [Asn1Integer](#), [Asn1Null](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1UniversalString](#), and [Asn1BigInteger](#).

3.50.2.11 virtual void Encode (Asn1XerEncoder *buffer*) [virtual]

This method is the base implementation of the standard XML Encoding Rules (XER) encode method. This method invokes the generated method with element name set to null. This will cause the ASN.1 type name to be used as the top-level element name.

Also throws any exception thrown by the underlying stream.

Parameters

buffer XER Encode message buffer object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Implements [Asn1TypeIF](#).

Reimplemented in [Asn1OpenExt](#).

3.50.2.12 virtual void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method is the base implementation of the standard Packed Encoding Rules (PER) encode method. It throws an exception because it should never be invoked. Inherited class implements this method in Compiler generated code.

Parameters

buffer PER Encode message buffer object

Exceptions

[Asn1Exception](#) if invoked directly

Implements [Asn1TypeIF](#).

Reimplemented in [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Time](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VarWidthCharString](#), and [Asn1BigInteger](#).

3.50.2.13 virtual int Encode (Asn1BerEncodeBuffer *buffer*) [virtual]

This method is used to encode a message in BER or DER format. This version of the method sets tagging to explicit ([Asn1Tag.EXPL](#)).

Parameters

buffer Decode message buffer object

Returns

Length of component or negative status value

3.50.2.14 **virtual int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method is used to encode this data type in BER or DER format.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tag should be added to the encoded type.

Returns

Length of component or negative status value

Implements [Asn1TypeIF](#).

Reimplemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.50.2.15 **virtual bool Equals (Asn1Type *obj*) [virtual]**

Return true if the two objects are equal. /p> Note: in generated code, we will implement [Equals\(Asn1Type\)](#) rather than [Equals\(Object\)](#) to avoid the need to also implement [HashCode](#). The default implementation here is to invoke [Equals\(Object\)](#). This is acceptable for the runtime classes, which have overridden [Equals\(Object\)](#).

3.50.2.16 **static System.String GetTypeName (short *typeCode*) [static]**

This method will convert a type code into a type name as defined in the X.680 standard..

Parameters

typeCode Type code to be converted

Returns

ASN.1 type name

3.50.2.17 **virtual void Indent (System.IO.TextWriter *outs*, int *level*) [virtual]**

This method will indent three spaces in the given print stream. It is used by the print methods to provide a formatted output of an encoded element value.

Parameters

outs Print stream

level Indentation level (no of spaces is 3 x this number)

3.50.2.18 `virtual bool IsOpenType () [virtual]`

Returns open type mode for XML encoding/decoding.

Returns

`true` if open type mode is on.

Implements [Asn1TypeIF](#).

3.50.2.19 `virtual internal int MatchTag (Asn1BerDecodeBuffer buffer, Asn1Tag tag) [protected, virtual]`

This method will compare the next parsed tag with the given tag value. If they do not match, an exception will be thrown.

Parameters

buffer Decode message buffer object

tag Tag value to compare

Returns

Decoded length value

Exceptions

Asn1TagMatchFailedException Tag is not equal to expected value

3.50.2.20 `virtual internal int MatchTag (Asn1BerDecodeBuffer buffer, short tagClass, short tagForm, int tagIDCode) [protected, virtual]`

This method will compare the next parsed tag with the given tag value. If they do not match, an exception will be thrown.

Parameters

buffer Decode message buffer object

tagClass Tag class value (UNIV, APPL, CTXT, or PRIV)

tagForm Tag form value (PRIM or CONS)

tagIDCode Tag identifier code

Returns

Decoded length value

Exceptions

Asn1TagMatchFailedException Tag is not equal to expected value

3.50.2.21 virtual bool MatchTypeName (System.String *typeName*) [virtual]

This method is used to check the outer level tag in an XER message to verify it matches the expected value. This method is overridden by generated code. The default implementation always returns true.

Parameters

typeName Type name to compare.

Returns

True if name matches internal name.

3.50.2.22 virtual void Pdiag (System.String *s*) [virtual]

This is a diagnostics print method. It is a shorthand way to invoke the [Diag](#) object's println method.

Parameters

s diagnostics message to be printed.

3.50.2.23 virtual void Print (System.String *varName*) [virtual]

This method will format and output a primitive value to the standard console output.

Parameters

varName Name of variable

3.50.2.24 virtual void Print (System.IO.TextWriter *outs*, System.String *varName*, int *level*) [virtual]

This method will format and output a primitive value to the given print stream.

Parameters

outs Print output stream

varName Name of variable

level Indentation level

Implements [Asn1TypeIF](#).

3.50.2.25 void SetKey (byte[] *rtkey*)

This method is used with the limited run-time to set a run-time key value generated by the compiler to allow the run-time to operate on the licensed hosts. This is not used in the unlimited redistribution versions.

Parameters

rtkey Run-time key generated by ASN1C

3.50.2.26 `static void SetKey2 (byte[] rtkey) [static]`

This method is used with the limited run-time to set a run-time key value generated by the compiler to allow the run-time to operate on the licensed hosts. This is not used in the unlimited redistribution versions. This is the static version of SetKey.

Parameters

rtkey Run-time key generated by ASN1C

3.50.2.27 `virtual void SetOpenType () [virtual]`

Sets open type mode for XML encoding/decoding.

Implements [Asn1TypeIF](#).

3.50.3 Member Data Documentation

3.50.3.1 `readonly Asn1Tag _TAG = new Asn1Tag(Asn1Tag.UNIV, Asn1Tag.PRIM, Asn1Type.EOC) [static]`

Will hold tag for possible definitions

Reimplemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.50.3.2 `const short BIT_STRING = 3`

BIT_STRING type code = 3

3.50.3.3 `const short BMPString = 30`

BMPString type code = 30

3.50.3.4 `const short BOOLEAN = 1`

BOOLEAN type code = 1

3.50.3.5 `const short DATE = 31`

DATE type code = 31

3.50.3.6 `const short ENUMERATED = 10`

ENUMERATED type code = 10

3.50.3.7 const short EOC = 0

EOC type code = 0

3.50.3.8 const short EXTERNAL = 8

EXTERNAL type code = 8

3.50.3.9 const short GeneralString = 27

GeneralString type code = 27

3.50.3.10 const short GeneralTime = 24

GeneralTime type code = 24

3.50.3.11 const short GraphicString = 25

GraphicString type code = 25

3.50.3.12 const short IA5String = 22

IA5String type code = 22

3.50.3.13 const short INTEGER = 2

INTEGER type code = 2

3.50.3.14 const short NULL = 5

NULL type code = 5

3.50.3.15 const short NumericString = 18

NumericString type code = 18

3.50.3.16 const short OBJECT_IDENTIFIER = 6

OBJECT_IDENTIFIER type code = 6

3.50.3.17 const short ObjectDescriptor = 7

ObjectDescriptor type code = 7

3.50.3.18 const short OCTET_STRING = 4

OCTET_STRING type code = 4

3.50.3.19 const short PrintableString = 19

PrintableString type code = 19

3.50.3.20 const short REAL = 9

REAL type code = 9

3.50.3.21 const short RelativeOID = 13

RELATIVE_OID type code = 13

3.50.3.22 const short SEQUENCE = 16

SEQUENCE type code = 16

3.50.3.23 const short SET = 17

SET type code = 17

3.50.3.24 const short T61String = TeletexString

T61String type code = TeletexString

3.50.3.25 const short TeletexString = 20

TeletexString type code = 20

3.50.3.26 const short TIME = 14

TIME type code = 14

3.50.3.27 const short UniversalString = 28

UniversalString type code = 28

3.50.3.28 const short UTCTime = 23

UTCTime type code = 23

3.50.3.29 const short UTF8String = 12

UTF8String type code = 12

3.50.3.30 const short VideotexString = 21

VideotexString type code = 21

3.50.3.31 const short VisibleString = 26

VisibleString type code = 26

3.50.4 Property Documentation

3.50.4.1 virtual int Length [get]

Gets the length of types that can be bound by a size constraint (BIT STRING, OCTET STRING, character string, and SEQUENCE OF/SET OF). An attempt to invoke it on any other type will cause an exception to be thrown.

Value: Length of item in units (for example, bits for BIT STRING, octets for OCTET STRING, etc.)

Exceptions

Asn1InvalidLengthException if called by type rather than size constrained (BIT STRING, OCTET STRING, character string, or SEQUENCE OF/SET OF)

Reimplemented in [Asn1BitString](#), [Asn1CharString](#), [Asn1OctetString](#), and [Asn1UniversalString](#).

3.51 Asn1TypeIF Interface Reference

Inherited by [Asn1Type](#).

Public Member Functions

- void [Decode](#) (System.Object reader, System.IO.Stream byteStream)
- void [Decode](#) (System.Object reader, System.String xmlURI)
- void [Decode](#) (Asn1PerDecodeBuffer buffer)
- void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- void [Encode](#) (Asn1PerOutputStream outs)
- void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- void [Encode](#) (Asn1XerEncoder buffer)
- void [Encode](#) (Asn1PerEncodeBuffer buffer)
- int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- bool [IsOpenType](#) ()
- void [Print](#) (System.IO.TextWriter outs, System.String varName, int level)
- void [SetOpenType](#) ()

3.51.1 Detailed Description

This is the base interface for all ASN.1 built-in types.

3.51.2 Member Function Documentation

3.51.2.1 void Decode (System.Object reader, System.IO.Stream byteStream)

This method declaration is the signature of the standard XML Encoding Rules (XER) Decode method.

Throws an IO exception from the parser, possibly from a byte stream or character stream supplied by the application.

Parameters

reader XML reader object

byteStream Input byte stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Implemented in [Asn1Type](#).

3.51.2.2 void Decode (System.Object reader, System.String xmlURI)

This method declaration is the signature of the standard XML Encoding Rules (XER) Decode method.

Throws an IO exception from the parser, possibly from a byte stream or character stream supplied by the application.

Parameters

reader XML reader object

xmlURI URI of a source

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1Type](#).

3.51.2.3 void Decode (Asn1PerDecodeBuffer *buffer*)

This method declaration is the signature of the standard Packed Encoding Rules (PER) Decode method.

Parameters

buffer PER Encode message buffer object

Implemented in [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Time](#), [Asn1Type](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VarWidthCharString](#), and [Asn1BigInteger](#).

3.51.2.4 void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*)

This method declaration is the signature of the standard Basic Encoding Rules (BER) or Distinguished Encoding Rules (DER) Decode method.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating explicit tag should be parsed from the encoded type.

implicitLength Length of the contents field (only required if explicit is false).

Implemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1Type](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.51.2.5 void Encode (Asn1PerOutputStream *outs*)

This method declaration is the signature of the streaming oriented PER encode method.

Also throws any exception thrown by the [Asn1PerOutputStream](#).

Parameters

outs PER Output Stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Integer](#), [Asn1Null](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Time](#), [Asn1Type](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VarWidthCharString](#), and [Asn1BigInteger](#).

3.51.2.6 void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*)

This method declaration is the signature of the streaming oriented BER encode method.

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1Type](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.51.2.7 void Encode (Asn1XerEncoder *buffer*, System.String *elemName*)

This method declaration is the signature of the standard XML Encoding Rules (XER) encode method.

Also throws any exception thrown by the underlying stream.

Parameters

buffer XER Encode message buffer object

elemName XML element name of item

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1BitString](#), [Asn1Boolean](#), [Asn1CharString](#), [Asn1Enumerated](#), [Asn1Integer](#), [Asn1Null](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Type](#), [Asn1UniversalString](#), and [Asn1BigInteger](#).

3.51.2.8 void Encode (Asn1XerEncoder *buffer*)

This method declaration is the signature of the standard XML Encoding Rules (XER) encode method. This method invokes the generated method with element name set to null. This will cause the ASN.1 type name to be used as the top-level element name.

Also throws any exception thrown by the underlying stream.

Parameters

buffer XER Encode message buffer object

Exceptions

Asn1Exception Thrown, if operation is failed.

Implemented in [Asn1OpenExt](#), and [Asn1Type](#).

3.51.2.9 void Encode (Asn1PerEncodeBuffer *buffer*)

This method declaration is the signature of the standard Packed Encoding Rules (PER) encode method.

Parameters

buffer PER Encode message buffer object

Implemented in [Asn18BitCharString](#), [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1Time](#), [Asn1Type](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VarWidthCharString](#), and [Asn1BigInteger](#).

3.51.2.10 int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*)

This method declaration is the signature of the standard Basic Encoding Rules (BER) or Distinguished Encoding Rules (DER) encode method.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tag should be added to the encoded type.

Returns

Length of component or negative status value

Implemented in [Asn1BMPString](#), [Asn1BitString](#), [Asn1Boolean](#), [Asn1ChoiceExt](#), [Asn1Enumerated](#), [Asn1GeneralString](#), [Asn1GeneralizedTime](#), [Asn1GraphicString](#), [Asn1IA5String](#), [Asn1Integer](#), [Asn1Null](#), [Asn1NumericString](#), [Asn1ObjectDescriptor](#), [Asn1ObjectIdentifier](#), [Asn1OctetString](#), [Asn1OpenExt](#), [Asn1OpenType](#), [Asn1PrintableString](#), [Asn1Real](#), [Asn1Real10](#), [Asn1RelativeOID](#), [Asn1T61String](#), [Asn1Type](#), [Asn1UTCTime](#), [Asn1UTF8String](#), [Asn1UniversalString](#), [Asn1VideotexString](#), [Asn1VisibleString](#), and [Asn1BigInteger](#).

3.51.2.11 bool IsOpenType ()

Returns open type mode for XML encoding/decoding.

Returns

true if open type mode is on.

Implemented in [Asn1Type](#).

3.51.2.12 void Print (System.IO.TextWriter *outs*, System.String *varName*, int *level*)

This method declaration is the signature of the standard print method used to print the contents of the object representing the ASN.1 type.

Parameters

outs Output print stream

varName Name of the variable being printed

level Indentation level

Implemented in [Asn1Type](#).

3.51.2.13 void SetOpenType ()

Sets open type mode for XML encoding/decoding.

Implemented in [Asn1Type](#).

3.52 Asn1UniversalString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Type](#).

Public Member Functions

- [Asn1UniversalString](#) (System.String value)
- [Asn1UniversalString](#) (int[] value)
- [Asn1UniversalString](#) ()
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, [Asn1CharSet](#) charSet)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [DecodeXER](#) (System.String buffer, System.String attrs)
- override void [DecodeXML](#) (System.String buffer, System.String attrs)
- virtual void [Encode](#) (Asn1PerOutputStream outs, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Encode](#) (Asn1PerOutputStream outs, [Asn1CharSet](#) charSet)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1XmlEncoder buffer, System.String elemName, System.String nsPrefix)
- override void [Encode](#) (Asn1XerEncoder buffer, System.String elemName)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, [Asn1CharSet](#) charSet)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- virtual void [EncodeData](#) (Asn1XmlXerEncoder buffer)
- override bool [Equals](#) (System.Object value)
- override int [GetHashCode](#) ()
- override System.String [ToString](#) ()
- bool [validate](#) ([Asn1CharSet](#) charSet)

Public Attributes

- const int [BITSPERCHAR](#) = 32
- int[] [mValue](#)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

Protected Member Functions

- virtual internal void [Decode](#) (Asn1PerDecodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual internal void [Decode](#) (Asn1PerDecodeBuffer buffer, int nchars, int abpc, int ubpc, [Asn1CharSet](#) charSet, int startIdx)
- virtual internal void [Decode](#) (Asn1PerDecodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet)
- virtual internal void [Encode](#) (Asn1PerOutputStream outs, int abpc, int ubpc, [Asn1CharSet](#) charSet, long lower, long upper)

- virtual internal void [Encode](#) (Asn1PerOutputStream outs, int abpc, int ubpc, [Asn1CharSet](#) charSet)
- virtual internal void [Encode](#) (Asn1PerOutputStream outs, int nchars, int offset, int abpc, int ubpc, [Asn1CharSet](#) charSet)
- virtual internal void [Encode](#) (Asn1PerEncodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet, long lower, long upper)
- virtual internal void [Encode](#) (Asn1PerEncodeBuffer buffer, int abpc, int ubpc, [Asn1CharSet](#) charSet)
- virtual internal void [Encode](#) (Asn1PerEncodeBuffer buffer, int nchars, int offset, int abpc, int ubpc, [Asn1CharSet](#) charSet)

Protected Attributes

- internal System.Text.StringBuilder [mStringBuffer](#)

Properties

- override int [Length](#) [get]

3.52.1 Detailed Description

This is a container class for holding the components of an ASN.1 Universal string value.

3.52.2 Constructor & Destructor Documentation

3.52.2.1 [Asn1UniversalString \(\)](#)

This constructor creates an empty string that can be used in a Decode method call to receive a string value.

3.52.2.2 [Asn1UniversalString \(int\[\] value\)](#)

This constructor initializes the universal string from the given an array of 32-bit integer value.

Parameters

value universal string value as array of 32-bit int

3.52.2.3 [Asn1UniversalString \(System.String value\)](#)

This constructor converts a standard C# string value into a universal string.

Parameters

value universal string value as string

3.52.3 Member Function Documentation

3.52.3.1 virtual internal void Decode (Asn1PerDecodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, long *lower*, long *upper*) [**protected**, **virtual**]

This overloaded version of the Decode method decodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The decoded result is stored in the public `mValue` member variable.

Parameters

- buffer* Decode message buffer object
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing permitted alphabet constraint character set (optional)
- lower* Effective size constraint lower bound
- upper* Effective size constraint upper bound

3.52.3.2 virtual internal void Decode (Asn1PerDecodeBuffer *buffer*, int *nchars*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, int *startIdx*) [**protected**, **virtual**]

This method decodes the contents of a UniversalString. This version of the method assumes a permitted alphabet constraint is in place.

Parameters

- buffer* Decode message buffer object
- nchars* Number of characters
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing the permitted alphabet constraint character set (optional)
- startIdx* Start index to fill in value array

3.52.3.3 virtual internal void Decode (Asn1PerDecodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [**protected**, **virtual**]

This method decodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes that a permitted alphabet constraint has been specified that would reduce the the number of bits-per-character from the default character set. It also assumes a general length determinant is present (i.e. there is not size constraint). The decoded result is stored in the public `mValue` member variable.

Parameters

- buffer* Decode message buffer object
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing the permitted alphabet constraint character set (optional)

3.52.3.4 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the Decode method decodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The decoded result is stored in the public `mValue` member variable.

Parameters

- buffer* Decode message buffer object
- charSet* Object representing permitted alphabet constraint character set (optional)
- lower* Effective size constraint lower bound
- upper* Effective size constraint upper bound

3.52.3.5 virtual void Decode (Asn1PerDecodeBuffer *buffer*, Asn1CharSet *charSet*) [virtual]

This method decodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but allows a permitted alphabet character set to be specified. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable.

Parameters

- buffer* Decode message buffer object
- charSet* Object representing permitted alphabet constraint character set (optional)

3.52.3.6 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable.

Parameters

- buffer* Decode message buffer object

Reimplemented from [Asn1Type](#).

3.52.3.7 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 universal string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

- buffer* Decode message buffer object
- explicitTagging* Flag indicating element is explicitly tagged
- implicitLength* Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.52.3.8 virtual void DecodeXER (System.String *buffer*, System.String *attrs*) [virtual]

This method decodes an ASN.1 Universal String value using the XML encoding rules (XER).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.52.3.9 override void DecodeXML (System.String *buffer*, System.String *attrs*)

This method decodes an ASN.1 Universal String value using the XML schema encoding rules(asn2xsd).

Parameters

buffer String containing data to be decoded

attrs Attributes string from element tag

3.52.3.10 virtual internal void Encode (Asn1PerOutputStream *outs*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, long *lower*, long *upper*) [protected, virtual]

This overloaded version of the encode method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The value to encode is stored in the public `mValue` member variable.

Also throws any exception thrown by the `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

abpc Number of bits per character (aligned)

ubpc Number of bits per character (unaligned)

charSet Object representing the permitted alphabet constraint character set (optional)

lower Effective size constraint lower bound

upper Effective size constraint upper bound

Exceptions

[*Asn1Exception*](#) Thrown, if operation is failed.

3.52.3.11 virtual internal void Encode (Asn1PerOutputStream *outs*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [protected, virtual]

This method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable.

Also throws any exception thrown by the `Asn1PerOutputStream`.

Parameters

- outs* PER Output Stream object
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing the permitted alphabet constraint character set (optional)

Exceptions

- Asn1Exception* Thrown, if operation is failed.

3.52.3.12 virtual internal void Encode (Asn1PerOutputStream *outs*, int *nchars*, int *offset*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [protected, virtual]

This method encodes the contents of a UniversalString type. This version assumes a permitted alphabet constraint was specified.

Also throws any exception thrown by the Asn1PerOutputStream.

Parameters

- outs* PER Output Stream object
- nchars* Number of characters from string to encode
- offset* Offset to first char in string to encode
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing permitted alphabet constraint character set (optional)

Exceptions

- Asn1Exception* Thrown, if operation is failed.

3.52.3.13 virtual void Encode (Asn1PerOutputStream *outs*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the encode method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes both a size constraint and permitted alphabet constraint are present.

The value to encode is stored in the public `mValue` member variable.

Also throws any exception thrown by the Asn1PerOutputStream.

Parameters

- outs* PER Output Stream object
- charSet* Object representing the permitted alphabet constraint character set
- lower* Effective size constraint lower bound
- upper* Effective size constraint upper bound

Exceptions

- Asn1Exception* Thrown, if operation is failed.

3.52.3.14 virtual void Encode (Asn1PerOutputStream *outs*, Asn1CharSet *charSet*) [virtual]

This method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified.

The value to encode is stored in the public `mValue` member variable.

Also throws any exception thrown by the `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

charSet Object representing permitted alphabet constraint character set (optional)

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.52.3.15 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable.

Also throws any exception thrown by the `Asn1PerOutputStream`.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.52.3.16 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 universal string including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.52.3.17 virtual void Encode (AsnXmlEncoder *buffer*, System.String *elemName*, System.String *nsPrefix*) [virtual]

This method encodes an ASN.1 Universal String value with element and namespace prefix name tag using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object
elemName Element name
nsPrefix Element namespace value

3.52.3.18 override void Encode (AsnXerEncoder *buffer*, System.String *elemName*) [virtual]

This method encodes an ASN.1 Universal String value using the XML encoding rules (XER).

Parameters

buffer Encode message buffer object
elemName Element name

Reimplemented from [Asn1Type](#).

3.52.3.19 virtual internal void Encode (Asn1PerEncodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*, long *lower*, long *upper*) [protected, virtual]

This overloaded version of the encode method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present but no permitted alphabet constraint.

The value to encode is stored in the public `mValue` member variable.

Parameters

buffer Encode message buffer object
abpc Number of bits per character (aligned)
ubpc Number of bits per character (unaligned)
charSet Object representing the permitted alphabet constraint character set (optional)
lower Effective size constraint lower bound
upper Effective size constraint upper bound

3.52.3.20 virtual internal void Encode (Asn1PerEncodeBuffer *buffer*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [protected, virtual]

This method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable.

Parameters

- buffer* Encode message buffer object
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing the permitted alphabet constraint character set (optional)

3.52.3.21 virtual internal void Encode (Asn1PerEncodeBuffer *buffer*, int *nchars*, int *offset*, int *abpc*, int *ubpc*, Asn1CharSet *charSet*) [protected, virtual]

This method encodes the contents of a UniversalString type. This version assumes a permitted alphabet constraint was specified.

Parameters

- buffer* Encode message buffer object
- nchars* Number of characters from string to encode
- offset* Offset to first char in string to encode
- abpc* Number of bits per character (aligned)
- ubpc* Number of bits per character (unaligned)
- charSet* Object representing permitted alphabet constraint character set (optional)

3.52.3.22 virtual void Encode (Asn1PerEncodeBuffer *buffer*, Asn1CharSet *charSet*, long *lower*, long *upper*) [virtual]

This overloaded version of the encode method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes both a size constraint and permitted alphabet constraint are present.

The value to encode is stored in the public `mValue` member variable.

Parameters

- buffer* Encode message buffer object
- charSet* Object representing the permitted alphabet constraint character set
- lower* Effective size constraint lower bound
- upper* Effective size constraint upper bound

3.52.3.23 virtual void Encode (Asn1PerEncodeBuffer *buffer*, Asn1CharSet *charSet*) [virtual]

This method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no size constraints but does allow a permitted alphabet character set to be specified.

The value to encode is stored in the public `mValue` member variable.

Parameters

- buffer* Encode message buffer object
- charSet* Object representing permitted alphabet constraint character set (optional)

3.52.3.24 **override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]**

This method encodes an ASN.1 UniversalString value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

3.52.3.25 **override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]**

This method encodes an ASN.1 universal string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.52.3.26 **virtual void EncodeData (Asn1XmlXerEncoder *buffer*) [virtual]**

This method encodes an ASN.1 Universal String value using the XML Encoding as specified in the XML schema standard(asn2xsd).

Parameters

buffer Encode message buffer object

3.52.3.27 **override bool Equals (System.Object *value*)**

This method compares this character string value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [Asn1UniversalString](#).

Returns

`true` if the specified Object is equal to the current Object; otherwise, `false`.

3.52.3.28 **override int GetHashCode ()**

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.52.3.29 **override System.String ToString ()**

This method will return a string representation of the value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

3.52.3.30 **bool validate (Asn1CharSet charSet)**

This method will attempt to validate a string against its internal character set.

Returns

True or False.

3.52.4 **Member Data Documentation**

3.52.4.1 **new readonly Asn1Tag _TAG [static]**

The `_TAG` constant describes the universal tag for this data type (UNIVERSAL 28).

Reimplemented from [Asn1Type](#).

3.52.4.2 **const int BITSPERCHAR = 32**

The `BITSPERCHAR` constant specifies the number of bits per character for PER (aligned or unaligned).

3.52.4.3 **internal System.Text.StringBuilder mStringBuffer [protected]**

Variable holds the string representation of the value

3.52.4.4 **int [] mValue**

The `mValue` public member variable is used to hold the string value to be encoded or the results of a Decode operation. For `UniversalString`, the characters are stored in an array of 32-bit integer values.

3.52.5 Property Documentation

3.52.5.1 override int Length [get]

Gets the length of the character string in characters.

Value: number of characters.

Reimplemented from [Asn1Type](#).

3.53 Asn1UTCTime Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Time](#).

Public Member Functions

- [Asn1UTCTime](#) (System.String data, bool useDerRules)
- [Asn1UTCTime](#) (System.String data)
- [Asn1UTCTime](#) (bool useDerRules)
- [Asn1UTCTime](#) ()
- override void [Clear](#) ()
- override System.Int32 [CompareTo](#) (System.Object obj)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)
- override void [ParseString](#) (System.String data)
- override void [SetTime](#) (System.DateTime time)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

Protected Member Functions

- internal override bool [CompileString](#) ()
- internal override void [Init](#) ()

Properties

- override string [Fraction](#) [get, set]
- override int [Year](#) [get, set]

3.53.1 Detailed Description

This is a container class for holding the components of an ASN.1 UTC time string value.

3.53.2 Constructor & Destructor Documentation

3.53.2.1 Asn1UTCTime ()

The default constructor creates an empty time string object.

3.53.2.2 Asn1UTCTime (bool useDerRules)

This constructor creates an empty UTCTime string object and allows DER encoding rules to be specified.

Parameters

useDerRules 'true' if time string should be encoded with DER/PER.

3.53.2.3 `Asn1UTCTime (System.String data)`

This version of the constructor can be used to set the string `mValue` member variable to the given time string.

Parameters

data UTCTime as string

3.53.2.4 `Asn1UTCTime (System.String data, bool useDerRules)`

This version of the constructor can be used to set the string `mValue` member variable to the given time string and specify DER encoding rules be used to construct the string.

Parameters

data UTCTime as string

useDerRules 'true' if time string should be encoded with DER/PER.

3.53.3 Member Function Documentation

3.53.3.1 `override void Clear () [virtual]`

Clears out time string.

Reimplemented from [Asn1Time](#).

3.53.3.2 `override System.Int32 CompareTo (System.Object obj) [virtual]`

This method compares this object with [Asn1Time](#) class instance or with `System.DateTime` instance. Returns a negative integer, zero, or a positive integer as this object is less than, equal to, or greater than the specified object. Note that the action of this method may differentiate for different inherited [Asn1Time](#) classes.

Parameters

obj the Object to be compared.

Returns

The difference in Ticks with the specified object.

Reimplemented from [Asn1Time](#).

3.53.3.3 `internal override bool CompileString () [protected, virtual]`

Compiles new time string according X.680 (clause 42) and ISO 8601.

Returns

`true` if successful; otherwise `false`.

Implements [Asn1Time](#).

3.53.3.4 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 UTCTime value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

- buffer* Decode message buffer object
- explicitTagging* Flag indicating element is explicitly tagged
- implicitLength* Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.53.3.5 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 UTC time string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

- outs* BER Output Stream object
- explicitTagging* Flag indicating explicit tagging should be done

Exceptions

- [Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.53.3.6 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 UTCTime type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

- buffer* Encode message buffer object
- explicitTagging* Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.53.3.7 internal override void Init () [protected, virtual]

This method initializes the [Asn1UTCTime](#) class member variables.

Reimplemented from [Asn1Time](#).

3.53.3.8 override void ParseString (System.String *data*) [virtual]

This method parses passed UTCTime string.

Parameters

data The UTCTime string value to be parsed.

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Implements [Asn1Time](#).

3.53.3.9 override void SetTime (System.DateTime *time*) [virtual]

This method converts the System.DateTime value to UTCTime string.

Parameters

time The System.DateTime value.

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Time](#).

3.53.4 Member Data Documentation

3.53.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 23).

Reimplemented from [Asn1Type](#).

3.53.5 Property Documentation

3.53.5.1 override string Fraction [get, set]

Gets the Fraction component of the UTC Time. Which is always Zero(i.e. empty string)

Value: Zero or empty string

Exceptions

[Asn1Exception](#) Always thrown for Sets call.

Reimplemented from [Asn1Time](#).

3.53.5.2 override int Year [get, set]

Gets or Sets the year component of the time value. You may pass 'year' parameter either as two last digits of the year (00 - 99) or as full 4 digits (0 - 9999). Note Gets returns year in full 4 digits format.

Value: Year component (full 4 digits).

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Time](#).

3.54 Asn1UTF8String Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1CharString](#).

Inherited by [Asn1Real10](#).

Public Member Functions

- [Asn1UTF8String](#) (System.String data)
- [Asn1UTF8String](#) ()
- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, long upper)
- override void [Encode](#) (Asn1PerOutputStream outs)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.54.1 Detailed Description

This is a container class for holding the components of an ASN.1 UTF-8 string value.

3.54.2 Constructor & Destructor Documentation

3.54.2.1 Asn1UTF8String ()

The default constructor creates an empty time string object.

3.54.2.2 Asn1UTF8String (System.String data)

This constructor can be used to set the UTF8 String `mValue` member variable to the given string value.

Parameters

data UTF8 String value

3.54.3 Member Function Documentation

3.54.3.1 virtual void Decode (Asn1PerDecodeBuffer buffer, long lower, long upper) [virtual]

This method decodes a sized ASN.1 UTF-8 string value using the packed encoding rules (PER).

Parameters

- buffer* Decode message buffer object
- lower* Lower bound (inclusive) of size constraint
- upper* Upper bound (inclusive) of size constraint

3.54.3.2 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 UTF-8 string value using the packed encoding rules (PER). The string is assumed to not contain a size constraint.

Parameters

- buffer* Decode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.54.3.3 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 UTF-8 string value including the UNIVERSAL tag value and length if explicit tagging is specified. This string type uses variable length character encodings.

Parameters

- buffer* Decode message buffer object
- explicitTagging* Flag indicating element is explicitly tagged
- implicitLength* Length of contents if implicit

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.54.3.4 virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, long *upper*) [virtual]

This method encodes a size-constrained ASN.1 UTF-8 string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Also throws any exception thrown by the Asn1PerOutputStream.

Parameters

- outs* PER Output Stream object
- lower* Lower bound (inclusive) of size constraint
- upper* Upper bound (inclusive) of size constraint

Exceptions

- [Asn1Exception](#) Thrown, if operation is failed.

3.54.3.5 override void Encode (Asn1PerOutputStream *outs*) [virtual]

This method encodes an unconstrained ASN.1 UTF-8 string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Also throws any exception thrown by the Asn1PerOutputStream.

Parameters

outs PER Output Stream object

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.54.3.6 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 UTF8 string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.54.3.7 virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This method encodes a size-constrained ASN.1 UTF-8 string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Parameters

buffer Encode message buffer object

lower Lower bound (inclusive) of size constraint

upper Upper bound (inclusive) of size constraint

3.54.3.8 override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]

This method encodes an unconstrained ASN.1 UTF-8 string value using the packed encoding rules (PER). The value to be encoded is stored in the 'mValue' public member variable within this class.

Parameters

buffer Encode message buffer object

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.54.3.9 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 UTF8 string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.54.4 Member Data Documentation

3.54.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 12).

Reimplemented from [Asn1Type](#).

Reimplemented in [Asn1Real10](#).

3.55 Asn1Util Class Reference

Static Public Member Functions

- static System.String [BCDToString](#) (byte[] bcd)
- static byte[] [DecodeBase64Array](#) (byte[] srcArray)
- static byte[] [EncodeBase64Array](#) (byte[] srcArray)
- static byte[] [GetAddressBytes](#) (string ipAddress)
- static int [GetBytesCount](#) (long val)
- static int [GetUlongBytesCount](#) (long val)
- static byte[] [StringToBCD](#) (System.String str)
- static byte[] [StringToTBCD](#) (System.String str)
- static System.String [TBCDToString](#) (byte[] bcd)
- static void [ToArray](#) (System.Collections.ICollection c, System.Object[] objects)
- static byte[] [ToByteArray](#) (System.String sourceString)
- static char[] [ToCharArray](#) (byte[] byteArray)
- static System.String [ToHexString](#) (byte[] b, int offset, int nbytes)
- static System.String [ToHexString](#) (byte b)
- static long [URShift](#) (long number, long bits)
- static long [URShift](#) (long number, int bits)
- static int [URShift](#) (int number, long bits)
- static int [URShift](#) (int number, int bits)
- static void [WriteStackTrace](#) (System.Exception throwable, System.IO.TextWriter stream)

3.55.1 Detailed Description

This class contains some general purpose static utility functions.

3.55.2 Member Function Documentation

3.55.2.1 static System.String [BCDToString](#) (byte[] *bcd*) [**static**]

Translates a BCD string to an ASCII string. The 0xF half-byte is assumed as end of string indicator.

Parameters

bcd the source BCD string

Returns

the ASCII string.

3.55.2.2 static byte [] [DecodeBase64Array](#) (byte[] *srcArray*) [**static**]

Translates the specified Base64 array into byte array. The resulting array could be converted to the String by new String (byte[]) constructor.

Parameters

srcArray Base64 byte array to be translated

Returns

decoded byte array

3.55.2.3 static byte [] EncodeBase64Array (byte[] *srcArray*) [static]

Translates the specified byte array to Base64 byte array. The resulting array could be converted to the String by new String (byte[]) constructor.

Parameters

srcArray byte array to be translated

Returns

Base64 encoded byte array

3.55.2.4 static byte [] GetAddressBytes (string *ipaddress*) [static]

Converts an IPAddress to byte array

Parameters

ipaddress String representation of IP Address

Returns

The byte array(size 4) representation of IP address

3.55.2.5 static int GetBytesCount (long *val*) [static]

Calculate the number of bytes necessary to represent a signed long value.

Parameters

val signed long value.

Returns

the number of bytes.

3.55.2.6 static int GetUlongBytesCount (long *val*) [static]

Calculate the number of bytes necessary to represent an unsigned long value.

Parameters

val unsigned long value.

Returns

the number of bytes.

3.55.2.7 static byte [] StringToBCD (System.String *str*) [static]

Translates an ASCII string to a BCD string. The ASCII string must contain only characters in the range [0..9] & ([A..F] | [a..f]). If the length of the source string is not even, the unused part of the last byte will be set to 0xF.

Parameters

str the source ASCII string

Returns

the BCD string as a byte array.

Exceptions

[AsnIValueParseException](#) If invalid characters are in the source string.

3.55.2.8 static byte [] StringToTBCD (System.String *str*) [static]

Translates an ASCII string to a TBCD string. The ASCII string must contain only characters in the range [0..9] & ([A..F] | [a..f]). If the length of the source string is not even, the unused part of the last byte will be set to 0xF. TBCD strings differ from BCD strings in that the least significant nibble is set in the upper four bits; so the string "12345" would be translated "0x2143f5".

Parameters

str the source ASCII string

Returns

the TBCD string as a byte array.

Exceptions

[AsnIValueParseException](#) If invalid characters are in the source string.

3.55.2.9 static System.String TBCDToString (byte[] *bcd*) [static]

Translates a TBCD string to an ASCII string. The 0xF half-byte is assumed as end of string indicator.

Parameters

bcd the source TBCD string

Returns

the ASCII string.

3.55.2.10 static void ToArray (System.Collections.ICollection *c*, System.Object[] *objects*) [static]

Obtains an array containing all the elements of the collection.

Parameters

c The Collection instance, which contains the elements.

objects The array into which the elements of the collection will be stored.

Returns

The array containing all the elements of the collection.

3.55.2.11 static byte [] ToByteArray (System.String *sourceString*) [static]

Converts a string to an array of bytes

Parameters

sourceString The string to be converted

Returns

The new array of bytes

3.55.2.12 static char [] ToCharArray (byte[] *byteArray*) [static]

Converts an array of bytes to an array of chars

Parameters

byteArray The array of bytes to convert

Returns

The new array of chars

3.55.2.13 static System.String ToHexString (byte[] *b*, int *offset*, int *nbytes*) [static]

Convert a array of bytes into a hex string.

Parameters

b byte array to be converted to hex string

offset start position in byte array

nbytes no. of bytes to be converted

Returns

Hex String value

3.55.2.14 `static System.String ToHexString (byte b) [static]`

Convert a byte value to a hex string. Unlike the C# built-in function, this will:

- a. not sign extend the byte value out to 32 bits if the MSB is set, and
 - b. put a zero padding byte in front if less than 0xf
- In other words, a character string of length 2 is always returned.

Parameters

b byte value

Returns

Hex String value

3.55.2.15 `static long URShift (long number, long bits) [static]`

Performs an unsigned bitwise right shift with the specified number. The low-order bits of number are discarded, the remaining bits are shifted right, and the high-order empty bit positions are set to zero.

Parameters

number Number to operate on

bits Ammount of bits to shift

Returns

The resulting number from the shift operation

3.55.2.16 `static long URShift (long number, int bits) [static]`

Performs an unsigned bitwise right shift with the specified number. The low-order bits of number are discarded, the remaining bits are shifted right, and the high-order empty bit positions are set to zero.

Parameters

number Number to operate on

bits Ammount of bits to shift

Returns

The resulting number from the shift operation

3.55.2.17 `static int URShift (int number, long bits) [static]`

Performs an unsigned bitwise right shift with the specified number. The low-order bits of number are discarded, the remaining bits are shifted right, and the high-order empty bit positions are set to zero.

Parameters

number Number to operate on

bits Ammount of bits to shift

Returns

The resulting number from the shift operation

3.55.2.18 `static int URShift (int number, int bits) [static]`

Performs an unsigned bitwise right shift with the specified number. The low-order bits of number are discarded, the remaining bits are shifted right, and the high-order empty bit positions are set to zero.

Parameters

number Number to operate on

bits Ammount of bits to shift

Returns

The resulting number from the shift operation

3.55.2.19 `static void WriteStackTrace (System.Exception throwable, System.IO.TextWriter stream) [static]`

Writes the exception stack trace to the received stream

Parameters

throwable Exception to obtain information from

stream Output sream used to write to

3.56 Asn1Value Class Reference

Static Public Member Functions

- static byte[] [ParseString](#) (System.String data)
- static byte[] [ParseString](#) (System.String data, [IntHolder](#) numbits)

3.56.1 Detailed Description

This class provides methods for parsing and formatting text in ASN.1 value notation.

3.56.2 Member Function Documentation

3.56.2.1 static byte [] ParseString (System.String data) [static]

This overloaded version of the ParseString method sets the numbits holder value to null.

Parameters

data The ASN.1 value specification text

Returns

byte array value

3.56.2.2 static byte [] ParseString (System.String data, IntHolder numbits) [static]

This static method parses the given ASN.1 value text (either a binary or hex data string) and returns the value in a binary byte array. The number of bits is also returned.

Examples of valid value formats are as follows:

Binary string: '11010010111001'B

Hex string: '0fa56920014abc'H

Char string: 'abcdefg'

Parameters

data The ASN.1 value specification text

numbits Holder to receive number of bits in string

Returns

byte array value

3.57 Asn1ValueParseException Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1Exception](#).

Public Member Functions

- [Asn1ValueParseException](#) (System.String text, int offset)
- [Asn1ValueParseException](#) (System.String text)

3.57.1 Detailed Description

This class defines the 'ASN.1 value Parse' exception that is thrown when a string containing an ASN.1 value cannot be parsed.

3.57.2 Constructor & Destructor Documentation

3.57.2.1 Asn1ValueParseException (System.String text)

This constructor creates an exception object with a textual message describing the expected and parsed tag values.

Parameters

text The value string that could not be parsed

3.57.2.2 Asn1ValueParseException (System.String text, int offset)

This constructor creates an exception object with a textual message describing the expected and parsed tag values. This version allows the offset in the string to also be specified.

Parameters

text The value string that could not be parsed

offset Offset to error location in string

3.58 Asn1VarWidthCharString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1CharString](#).

Inherited by [Asn1GeneralString](#), [Asn1GraphicString](#), [Asn1ObjectDescriptor](#), [Asn1T61String](#), and [Asn1VideotexString](#).

Public Member Functions

- virtual void [Decode](#) (Asn1PerDecodeBuffer buffer, long lower, long upper)
- override void [Decode](#) (Asn1PerDecodeBuffer buffer)
- virtual void [Encode](#) (Asn1PerOutputStream outs, long lower, long upper)
- override void [Encode](#) (Asn1PerOutputStream outs)
- virtual void [Encode](#) (Asn1PerEncodeBuffer buffer, long lower, long upper)
- override void [Encode](#) (Asn1PerEncodeBuffer buffer)

Public Attributes

- const int [BITSPERCHAR_A](#) = 8
- const int [BITSPERCHAR_U](#) = 8

Protected Member Functions

- internal [Asn1VarWidthCharString](#) (System.String data, short typeCode)
- internal [Asn1VarWidthCharString](#) (short typeCode)

3.58.1 Detailed Description

This is an abstract base class for holding the ASN.1 variable width character string types (GraphicString, GeneralString, TeletexString, T61String, VideotexString, ObjectDescriptor).

3.58.2 Constructor & Destructor Documentation

3.58.2.1 internal Asn1VarWidthCharString (short typeCode) [protected]

The default constructor creates an empty string object.

Parameters

typeCode Universal ID code for ASN.1 character string

3.58.2.2 internal Asn1VarWidthCharString (System.String data, short typeCode) [protected]

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data Character string

typeCode Universal ID code for ASN.1 character string

3.58.3 Member Function Documentation

3.58.3.1 virtual void Decode (Asn1PerDecodeBuffer *buffer*, long *lower*, long *upper*) [virtual]

This overloaded version of the Decode method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present. A permitted alphabet may be passed, but it will be ignored.

The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.58.3.2 override void Decode (Asn1PerDecodeBuffer *buffer*) [virtual]

This method decodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints. Decoded characters are assigned as-is to the output string. The decoded result is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Parameters

buffer Decode message buffer object

Reimplemented from [Asn1Type](#).

3.58.3.3 virtual void Encode (Asn1PerOutputStream *outs*, long *lower*, long *upper*) [virtual]

This overloaded version of the encode method encodes an ASN.1 character string value directly into the stream, in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present. A permitted alphabet may be passed, but it will be ignored.

The value to encode is stored in the public `mValue` member variable in the [Asn1CharString](#) base class.

Also throws any exception thrown by the [Asn1PerOutputStream](#).

Parameters

outs PER Encode message stream object

lower Effective size constraint lower bound

upper Effective size constraint upper bound

Exceptions

[Asn1Exception](#) Thrown, if operation is failed.

3.58.3.4 **override void Encode (Asn1PerOutputStream *outs*) [virtual]**

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER) directly into the stream. This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the `Asn1CharString` base class.

Also throws any exception thrown by the `Asn1PerOutputStream`.

Parameters

outs PER Encode message stream object

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from `Asn1Type`.

3.58.3.5 **virtual void Encode (Asn1PerEncodeBuffer *buffer*, long *lower*, long *upper*) [virtual]**

This overloaded version of the encode method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes a size constraint is present. A permitted alphabet may be passed, but it will be ignored.

The value to encode is stored in the public `mValue` member variable in the `Asn1CharString` base class.

Parameters

buffer Encode message buffer object

lower Effective size constraint lower bound

upper Effective size constraint upper bound

3.58.3.6 **override void Encode (Asn1PerEncodeBuffer *buffer*) [virtual]**

This method encodes an ASN.1 character string value in accordance with the packed encoding rules (PER). This version of the method assumes no permitted alphabet or size constraints.

The value to encode is stored in the public `mValue` member variable in the `Asn1CharString` base class.

Parameters

buffer Encode message buffer object

Reimplemented from `Asn1Type`.

3.58.4 **Member Data Documentation**

3.58.4.1 **const int BITSPERCHAR_A = 8**

The `BITSPERCHAR_A` constant specifies the number of bits per character for PER (aligned).

3.58.4.2 **const int BITSPERCHAR_U = 8**

The `BITSPERCHAR_U` constant specifies the number of bits per character for PER (unaligned).

3.59 Asn1VideotexString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString](#).

Public Member Functions

- [Asn1VideotexString](#) (System.String data)
- [Asn1VideotexString](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.59.1 Detailed Description

This is a container class for holding the components of an ASN.1 videotex string value.

3.59.2 Constructor & Destructor Documentation

3.59.2.1 Asn1VideotexString ()

The default constructor creates an empty string object.

3.59.2.2 Asn1VideotexString (System.String data)

This version of the constructor can be used to set the string `mValue` member variable to the given string.

Parameters

data string representation of videotex string

3.59.3 Member Function Documentation

3.59.3.1 override void Decode (Asn1BerDecodeBuffer *buffer*, bool *explicitTagging*, int *implicitLength*) [virtual]

This method decodes an ASN.1 Videotex string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.59.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 videotex string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Reimplemented from [Asn1Type](#).

3.59.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 Videotex String type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.59.4 Member Data Documentation

3.59.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 21).

Reimplemented from [Asn1Type](#).

3.60 Asn1VisibleString Class Reference

Inherits [Com::Objsys::Asn1::Runtime::Asn18BitCharString](#).

Public Member Functions

- [Asn1VisibleString](#) (System.String data)
- [Asn1VisibleString](#) ()
- override void [Decode](#) (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength)
- override void [Encode](#) (Asn1BerOutputStream outs, bool explicitTagging)
- override int [Encode](#) (Asn1BerEncodeBuffer buffer, bool explicitTagging)

Static Public Attributes

- static new readonly [Asn1Tag_TAG](#)

3.60.1 Detailed Description

This is a container class for holding the components of an ASN.1 Visible string value.

3.60.2 Constructor & Destructor Documentation

3.60.2.1 Asn1VisibleString ()

The default constructor creates an empty string object.

3.60.2.2 Asn1VisibleString (System.String data)

This version of the constructor can be used to set the Visible string `mValue` member variable to the given string.

Parameters

data string representation of visible string

3.60.3 Member Function Documentation

3.60.3.1 override void Decode (Asn1BerDecodeBuffer buffer, bool explicitTagging, int implicitLength) [virtual]

This method decodes an ASN.1 Visible string value including the UNIVERSAL tag value and length if explicit tagging is specified.

Parameters

buffer Decode message buffer object

explicitTagging Flag indicating element is explicitly tagged

implicitLength Length of contents if implicit

Reimplemented from [Asn1Type](#).

3.60.3.2 override void Encode (Asn1BerOutputStream *outs*, bool *explicitTagging*) [virtual]

This method encodes and writes to the stream an ASN.1 visible string value including the UNIVERSAL tag value and length if explicit tagging is specified. This overloaded version uses the Basic Encoding Rules (BER).

Throws, Exception thrown by C# System.IO.Stream for I/O error

Parameters

outs BER Output Stream object

explicitTagging Flag indicating explicit tagging should be done

Exceptions

Asn1Exception Thrown, if operation is failed.

Reimplemented from [Asn1Type](#).

3.60.3.3 override int Encode (Asn1BerEncodeBuffer *buffer*, bool *explicitTagging*) [virtual]

This method encodes an ASN.1 Visible string type. The UNIVERSAL tag value and length is also encoded if explicit tagging is specified.

Parameters

buffer Encode message buffer object

explicitTagging Flag indicating explicit tagging should be done

Returns

Length in octets of encoded component

Reimplemented from [Asn1Type](#).

3.60.4 Member Data Documentation

3.60.4.1 new readonly Asn1Tag _TAG [static]

The _TAG constant describes the universal tag for this data type (UNIVERSAL 26).

Reimplemented from [Asn1Type](#).

3.61 BigInteger Class Reference

Public Member Functions

- [BigInteger](#) (System.String value, int radix)
- [BigInteger](#) (System.Int64 value)
- [BigInteger](#) (System.String value)
- [BigInteger](#) (byte[] value, int sign)
- [BigInteger](#) ()
- override bool [Equals](#) (System.Object value)
- virtual bool [Equals](#) (long value)
- byte[] [GetData](#) ()
- override int [GetHashCode](#) ()
- void [Init](#) (System.String val, int radix)
- bool [IsNegative](#) ()
- void [SecureDelete](#) ()
- void [SetData](#) (byte[] ivalue)
- override System.String [ToString](#) ()
- System.String [ToString](#) (int radix)

Static Public Member Functions

- static implicit [operator BigInteger](#) (long value)

3.61.1 Detailed Description

This class represents an ASN.1 INTEGER built-in type. In this case, the values can be greater than 64 bits in size. This class is used in generated source code if the <BigInteger> qualifier is specified in a compiler configuration file.

3.61.2 Constructor & Destructor Documentation

3.61.2.1 BigInteger ()

The default constructor sets the big integer value object reference to null.

3.61.2.2 BigInteger (byte[] value, int sign)

This constructor creates a new big integer object and sets it to the byte[] value passed in.

Parameters

value String value

sign Can be -1 for negative, 0 for zero, or 1 for positive.

3.61.2.3 **BigInteger** (System.String *value*)

This constructor creates a new big integer object and sets it to the string value passed in. String value may contain the prefix that describes the radix: 0x - hexadecimal, 0o - octal, 0b - binary. The string value without prefix assumes decimal value. The optional sign '-' may be specified at the beginning of the string to specify the negative value.

Parameters

value String value

3.61.2.4 **BigInteger** (System.Int64 *value*)

This constructor creates a new big integer object and sets it to the int value passed in.

Parameters

value Integer value

3.61.2.5 **BigInteger** (System.String *value*, int *radix*)

This constructor creates a new big integer object and sets it to the string value passed in. String value may contain the prefix that describes the radix: 0x - hexadecimal, 0o - octal, 0b - binary. The string value without prefix assumes decimal value. The optional sign '-' may be specified at the beginning of the string to specify the negative value.

Parameters

value String value

radix Can be 16 for hexadecimal, 8 for octal, 2 for binary or 10 for decimal

3.61.3 Member Function Documentation

3.61.3.1 override bool Equals (System.Object *value*)

This method compares this integer value to the given value for equality.

Parameters

value The Object to compare with the current Object. Object should be instance of [BigInteger](#).

Returns

true if the specified Object is equal to the current Object; otherwise, false.

3.61.3.2 virtual bool Equals (long *value*) [virtual]

This method compares this integer value to the given value for equality.

Parameters

value The long value to compare with the current Object.

Returns

true if the specified long value is equal to the current Object; otherwise, false.

3.61.3.3 `byte [] GetData ()`

This method provides the byte array representation of the integer value

Returns

byte array for integer value

3.61.3.4 `override int GetHashCode ()`

Serves as a hash function for a particular type, suitable for use in hashing algorithms and data structures like a hash table.

Returns

A hash code for the current Object.

3.61.3.5 `void Init (System.String val, int radix)`

Translates the String representation of a Integer in the specified radix into a [BigInteger](#). The String representation consists of an optional minus sign followed by a sequence of one or more digits in the specified radix. The String may not contain any extraneous Characters (whitespace, for example).

Parameters

val String representation of Integer.

radix radix to be used in interpreting string value.

Exceptions

System.FormatException *val* is not a valid representation of a [BigInteger](#) in the specified radix, or invalid value of radix.

3.61.3.6 `bool IsNegative ()`

This method checks the Integer value is negative.

Returns

true if negative; otherwise false

3.61.3.7 `static implicit operator BigInteger (long value) [static]`

Overloaded implicit conversion operator for long to [BigInteger](#) value

3.61.3.8 `void SecureDelete ()`

This function clears the current value (by overwriting with zeros). Then sets the value to zero, and passes the old value to garbage collector.

3.61.3.9 void SetData (byte[] *ivalue*)

This method sets the Integer value from byte array.

Parameters

ivalue byte array of the integer value

Returns

Decoded integer value

See also

<seealso cref=GetData To retrieve Byte Array

3.61.3.10 override System.String ToString ()

This method will return a string representation of the integer value. The format is the ASN.1 value format for this type..

Returns

Stringified representation of the value

3.61.3.11 System.String ToString (int *radix*)

Returns the String representation of this [BigInteger](#) in the given radix. If the radix is invalid, it will default to 10 (as is the case for `Int32.ToString`). The a minus sign is prepended if appropriate. This method is compatible with `BigInteger(String, int)` constructor.

Parameters

radix radix of the String representation.

Returns

String representation of this [BigInteger](#) in the given radix.

See also

<seealso cref=System.Int32.ToString Integer [ToString](#) methods

3.62 BooleanHolder Class Reference

Public Member Functions

- [BooleanHolder](#) (bool value)
- [BooleanHolder](#) ()

Public Attributes

- bool [mValue](#)

3.62.1 Detailed Description

A Holder class for a `Boolean` that is used to store "out" and "inout" parameters in methods. If a method has a `boolean` as an "out" or "inout" parameter, the programmer must pass an instance of [BooleanHolder](#) as the corresponding parameter in the method invocation; for "inout" parameters, the programmer must also fill the "in" value.

If `myBooleanHolder` is an instance of `BooleanHolder`,

the value stored in its `value` field can be accessed with `myBooleanHolder.mValue`.

3.62.2 Constructor & Destructor Documentation

3.62.2.1 `BooleanHolder` ()

The default constructor for [BooleanHolder](#) class

3.62.2.2 `BooleanHolder (bool value)`

This constructor will initialize [BooleanHolder](#) class with specified boolean value.

Parameters

value `Boolean` value

3.62.3 Member Data Documentation

3.62.3.1 `bool mValue`

This member variable is where the boolean value is stored.

3.63 Diag Class Reference

Public Member Functions

- virtual bool [IsEnabled](#) (int traceLevel)
- virtual bool [IsEnabled](#) ()
- virtual void [Println](#) (System.String s, int traceLevel)
- virtual void [Println](#) (System.String s)
- virtual bool [SetEnabled](#) (bool data)
- virtual int [SetTraceLevel2](#) (int level)

Static Public Member Functions

- static void [HexDump](#) (System.IO.Stream istrm, System.IO.StreamWriter ostrm)
- static void [HexDump](#) (byte[] bytes, int traceLevel)
- static void [HexDump](#) (byte[] bytes)
- static [Diag Instance](#) ()
- static void [Prtln](#) (byte[] b, int offset, int nbytes)
- static void [Prtln](#) (byte[] b, int offset, int nbytes, int tl)
- static void [Prtln](#) (System.String s, int traceLevel)
- static void [Prtln](#) (System.String s)
- static int [SetTraceLevel](#) (int level)

Properties

- virtual System.IO.StreamWriter [PrintStream](#) [set]

3.63.1 Detailed Description

This class is used for printing diagnostic messages for debugging the run-time components. It allows messages to be easily switched on and off.

3.63.2 Member Function Documentation

3.63.2.1 static void [HexDump](#) (System.IO.Stream *istrm*, System.IO.StreamWriter *ostrm*) [static]

This method prints a formatted hex dump for the contents of the given input stream to the given output stream.

Parameters

istrm Input Stream containing data to be dumped

ostrm Output Stream to which formatted data is to be written

3.63.2.2 `static void HexDump (byte[] bytes, int traceLevel) [static]`

This method prints a formatted hex dump for the contents of the given byte array to the standard output stream, if the given trace level is enabled.

Parameters

bytes Byte array containing data to be dumped

traceLevel Trace level

3.63.2.3 `static void HexDump (byte[] bytes) [static]`

This method prints a formatted hex dump for the contents of the given byte array to the standard output stream.

Parameters

bytes Byte array containing data to be dumped

3.63.2.4 `static Diag Instance () [static]`

This method provides the current instance of the [Diag](#) Class

Returns

Current instance of the [Diag](#) class

3.63.2.5 `virtual bool IsEnabled (int traceLevel) [virtual]`

This method checks that given trace level message will be printed.

Parameters

traceLevel Trace Level

Returns

true if enabled, else false

3.63.2.6 `virtual bool IsEnabled () [virtual]`

This method will enable the diagnostic message printing.

Returns

true if enabled, else false

3.63.2.7 `virtual void Println (System.String s, int traceLevel) [virtual]`

This method prints a the diagnostic message, if given trace level is enabled

Parameters

s diagnostic message

traceLevel Trace Level

3.63.2.8 virtual void Println (System.String *s*) [virtual]

This method prints a the diagnsotic message

Parameters

s diagnsotic message

3.63.2.9 static void Prtln (byte[] *b*, int *offset*, int *nbytes*) [static]

This method prints a the hex dump of the given byte array to current [Diag](#) class instance

Parameters

b byte array containing data

offset start offset in the byte array

nbytes no of bytes to be printed

3.63.2.10 static void Prtln (byte[] *b*, int *offset*, int *nbytes*, int *tl*) [static]

This method prints a the hex dump of the given byte array to current [Diag](#) class instance, if given trace level is enabled

Parameters

b byte array containing data

offset start offset in the byte array

nbytes no of bytes to be printed

tl trace level

3.63.2.11 static void Prtln (System.String *s*, int *traceLevel*) [static]

This method prints a the diagnsotic message to current [Diag](#) class instance, if given trace level is enabled

Parameters

s diagnsotic message

traceLevel Trace Level

3.63.2.12 static void Prtln (System.String *s*) [static]

This method prints a the diagnsotic message to current [Diag](#) class instance.

Parameters

s diagnsotic message

3.63.2.13 **virtual bool SetEnabled (bool *data*) [virtual]**

This method enables or disables the diagnostic message printing.

Parameters

data true for enabling printing; otherwise false

Returns

The stat before setting this stat

3.63.2.14 **static int SetTraceLevel (int *level*) [static]**

This method sets the trace level for the current instance of the [Diag Class](#)

Parameters

level Trace Level

Returns

Set trace level

3.63.2.15 **virtual int SetTraceLevel2 (int *level*) [virtual]**

This method sets the trace level for this class

Parameters

level Trace Level

Returns

Set trace level

3.63.3 **Property Documentation**

3.63.3.1 **virtual System.IO.StreamWriter PrintStream [set]**

Sets the System.IO.StreamWriter object to which the diagnostic messages should be written.

Value: Output stream for diagnostic messages

3.64 IntHolder Class Reference

Public Member Functions

- [IntHolder](#) (int value)
- [IntHolder](#) ()

Public Attributes

- int [mValue](#)

3.64.1 Detailed Description

A Holder class for an `int` that is used to store "out" and "inout" parameters in methods. If a method has an `int` as an "out" or "inout" parameter, the programmer must pass an instance of [IntHolder](#) as the corresponding parameter in the method invocation; for "inout" parameters, the programmer must also fill the "in" value.

If myIntHolder is an instance of IntHolder,

the value stored in its value field can be accessed with `myIntHolder.mValue`.

3.64.2 Constructor & Destructor Documentation

3.64.2.1 IntHolder ()

The default constructor for [IntHolder](#) class

3.64.2.2 IntHolder (int value)

This constructor will initialize [IntHolder](#) class with specified int value.

Parameters

value int value

3.64.3 Member Data Documentation

3.64.3.1 int mValue

This member variable is where the int value is stored.

3.65 StringBufferExt Class Reference

Static Public Member Functions

- static `StringBuilder` [Replace](#) (`StringBuilder sbuf`, `int start`, `int end`, `String str`)

3.65.1 Detailed Description

This class provides the additional functionality to `StringBuilder` class

3.65.2 Member Function Documentation

3.65.2.1 static `StringBuilder` `Replace` (`StringBuilder sbuf`, `int start`, `int end`, `String str`) [`static`]

Replaces the characters in a substring of given `StringBuilder` with characters in the specified `String`. The substring begins at the specified `start` and extends to the character at index `end - 1` or to the end of the `StringBuilder` if no such character exists. First the characters in the substring are removed and then the specified `String` is inserted at `start`. (The specified `StringBuilder` will be lengthened to accommodate the specified `String` if necessary.)

Parameters

- sbuf* `StringBuilder` that will have contents.
- start* The beginning index, inclusive.
- end* The ending index, exclusive.
- str* `String` that will replace previous contents.

Returns

The replaced string builder.

3.66 Tokenizer Class Reference

Public Member Functions

- bool [HasMoreTokens](#) ()
- bool [MoveNext](#) ()
- System.String [NextToken](#) (System.String delimiters)
- System.String [NextToken](#) ()
- string [RemainingString](#) ()
- void [Reset](#) ()
- [Tokenizer](#) (System.String source, System.String delimiters, bool includeDelims)
- [Tokenizer](#) (System.String source, System.String delimiters)
- [Tokenizer](#) (System.String source)

Properties

- int [Count](#) [get]
- System.Object [Current](#) [get]

3.66.1 Detailed Description

The class performs token processing in strings

3.66.2 Constructor & Destructor Documentation

3.66.2.1 [Tokenizer](#) (System.String *source*)

Initializes a new class instance with a specified string to process

Parameters

source String to tokenize

3.66.2.2 [Tokenizer](#) (System.String *source*, System.String *delimiters*)

Initializes a new class instance with a specified string to process and the specified token delimiters to use

Parameters

source String to tokenize

delimiters String containing the delimiters

3.66.2.3 [Tokenizer](#) (System.String *source*, System.String *delimiters*, bool *includeDelims*)

Initializes a new class instance with a specified string to process, the specified token delimiters to use, and whether the delimiters must be included in the results.

Parameters

source String to tokenize

delimiters String containing the delimiters

includeDelims Determines if delimiters are included in the results.

3.66.3 Member Function Documentation

3.66.3.1 bool HasMoreTokens ()

Determines if there are more tokens to return from the source string

Returns

True or false, depending if there are more tokens

3.66.3.2 bool MoveNext ()

Performs the same action as HasMoreTokens.

Returns

True or false, depending if there are more tokens

3.66.3.3 System.String NextToken (System.String *delimiters*)

Returns the next token from the source string, using the provided token delimiters

Parameters

delimiters String containing the delimiters to use

Returns

The string value of the token

3.66.3.4 System.String NextToken ()

Returns the next token from the token list

Returns

The string value of the token

3.66.3.5 string RemainingString ()

Returns the rest of the string from current position.

Returns

rest of the string

3.66.3.6 void Reset ()

Does nothing.

3.66.4 Property Documentation

3.66.4.1 int Count [get]

Remaining tokens count

3.66.4.2 System.Object Current [get]

Performs the same action as NextToken.

Index

- `_TAG`
 - `Com::Objsys::Asn1::Runtime::Asn1BigInteger`, 15
 - `Com::Objsys::Asn1::Runtime::Asn1BitString`, 24
 - `Com::Objsys::Asn1::Runtime::Asn1BMPString`, 30
 - `Com::Objsys::Asn1::Runtime::Asn1Boolean`, 36
 - `Com::Objsys::Asn1::Runtime::Asn1Enumerated`, 74
 - `Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime`, 79
 - `Com::Objsys::Asn1::Runtime::Asn1GeneralString`, 81
 - `Com::Objsys::Asn1::Runtime::Asn1GraphicString`, 83
 - `Com::Objsys::Asn1::Runtime::Asn1IA5String`, 85
 - `Com::Objsys::Asn1::Runtime::Asn1Integer`, 98
 - `Com::Objsys::Asn1::Runtime::Asn1Null`, 113
 - `Com::Objsys::Asn1::Runtime::Asn1NumericString`, 116
 - `Com::Objsys::Asn1::Runtime::Asn1ObjectDescriptor`, 118
 - `Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier`, 123
 - `Com::Objsys::Asn1::Runtime::Asn1OctetString`, 132
 - `Com::Objsys::Asn1::Runtime::Asn1PrintableString`, 149
 - `Com::Objsys::Asn1::Runtime::Asn1Real`, 154
 - `Com::Objsys::Asn1::Runtime::Asn1Real10`, 159
 - `Com::Objsys::Asn1::Runtime::Asn1RelativeOID`, 163
 - `Com::Objsys::Asn1::Runtime::Asn1T61String`, 167
 - `Com::Objsys::Asn1::Runtime::Asn1Type`, 200
 - `Com::Objsys::Asn1::Runtime::Asn1UniversalString`, 219
 - `Com::Objsys::Asn1::Runtime::Asn1UTCTime`, 224
 - `Com::Objsys::Asn1::Runtime::Asn1UTF8String`, 229
 - `Com::Objsys::Asn1::Runtime::Asn1VideotexString`, 242
 - `Com::Objsys::Asn1::Runtime::Asn1VisibleString`, 244
- `AddCaptureBuffer`
 - `Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer`, 56
- `AddNamedEventHandler`
 - `Com::Objsys::Asn1::Runtime::Asn1MessageBuffer`, 104
- `Append`
 - `Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier`, 120
- `APPL`
 - `Com::Objsys::Asn1::Runtime::Asn1Tag`, 170
- `Apr`
 - `Com::Objsys::Asn1::Runtime::Asn1Time`, 182
- `April`
 - `Com::Objsys::Asn1::Runtime::Asn1Time`, 182
- `Asn18BitCharString`
 - `Com::Objsys::Asn1::Runtime::Asn18BitCharString`, 6
- `Asn1BigInteger`
 - `Com::Objsys::Asn1::Runtime::Asn1BigInteger`, 10, 11
- `Asn1BitString`
 - `Com::Objsys::Asn1::Runtime::Asn1BitString`, 17, 18
- `Asn1BMPString`
 - `Com::Objsys::Asn1::Runtime::Asn1BMPString`, 26
- `Asn1Boolean`
 - `Com::Objsys::Asn1::Runtime::Asn1Boolean`, 31
- `Asn1CharRange`
 - `Com::Objsys::Asn1::Runtime::Asn1CharRange`, 37
- `Asn1CharSet`
 - `Com::Objsys::Asn1::Runtime::Asn1CharSet`, 40
- `Asn1CharString`
 - `Com::Objsys::Asn1::Runtime::Asn1CharString`, 44
- `Asn1Choice`
 - `Com::Objsys::Asn1::Runtime::Asn1Choice`, 49
- `Asn1ConsVioException`
 - `Com::Objsys::Asn1::Runtime::Asn1ConsVioException`, 54
- `Asn1DiscreteCharSet`
 - `Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet`, 61
- `Asn1EndOfBufferException`
 - `Com::Objsys::Asn1::Runtime::Asn1EndOfBufferException`, 68
- `Asn1Enumerated`
 - `Com::Objsys::Asn1::Runtime::Asn1Enumerated`, 69
- `Asn1Exception`
 - `Com::Objsys::Asn1::Runtime::Asn1Exception`, 75

Asn1GeneralizedTime	Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 76, 77	Asn1Real10	Com::Objsys::Asn1::Runtime::Asn1Real10, 155
Asn1GeneralString	Com::Objsys::Asn1::Runtime::Asn1GeneralString, 80	Asn1RelativeOID	Com::Objsys::Asn1::Runtime::Asn1RelativeOID, 160
Asn1GraphicString	Com::Objsys::Asn1::Runtime::Asn1GraphicString, 82	Asn1SeqOrderException	Com::Objsys::Asn1::Runtime::Asn1SeqOrderException, 164
Asn1IA5String	Com::Objsys::Asn1::Runtime::Asn1IA5String, 84	Asn1T61String	Com::Objsys::Asn1::Runtime::Asn1T61String, 166
Asn1Integer	Com::Objsys::Asn1::Runtime::Asn1Integer, 89	Asn1Tag	Com::Objsys::Asn1::Runtime::Asn1Tag, 169
Asn1InvalidArgException	Com::Objsys::Asn1::Runtime::Asn1InvalidArgException, 99	Asn1Time	Com::Objsys::Asn1::Runtime::Asn1Time, 175
Asn1InvalidChoiceOptionException	Com::Objsys::Asn1::Runtime::Asn1InvalidChoiceOptionException, 100	Asn1TraceHandler	Com::Objsys::Asn1::Runtime::Asn1TraceHandler, 189
Asn1InvalidEnumException	Com::Objsys::Asn1::Runtime::Asn1InvalidEnumException, 101	Asn1UniversalString	Com::Objsys::Asn1::Runtime::Asn1UniversalString, 210
Asn1InvalidLengthException	Com::Objsys::Asn1::Runtime::Asn1InvalidLengthException, 102	Asn1UTCTime	Com::Objsys::Asn1::Runtime::Asn1UTCTime, 221, 222
Asn1InvalidObjectIDException	Com::Objsys::Asn1::Runtime::Asn1InvalidObjectIDException, 103	Asn1UTF8String	Com::Objsys::Asn1::Runtime::Asn1UTF8String, 226
Asn1MissingRequiredException	Com::Objsys::Asn1::Runtime::Asn1MissingRequiredException, 107	Asn1ValueParseException	Com::Objsys::Asn1::Runtime::Asn1ValueParseException, 237
Asn1NumericString	Com::Objsys::Asn1::Runtime::Asn1NumericString, 114	Asn1VarWidthCharString	Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString, 238
Asn1ObjectDescriptor	Com::Objsys::Asn1::Runtime::Asn1ObjectDescriptor, 117	Asn1VideotexString	Com::Objsys::Asn1::Runtime::Asn1VideotexString, 241
Asn1ObjectIdentifier	Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 119	Asn1VisibleString	Com::Objsys::Asn1::Runtime::Asn1VisibleString, 243
Asn1OctetString	Com::Objsys::Asn1::Runtime::Asn1OctetString, 125	Aug	Com::Objsys::Asn1::Runtime::Asn1Time, 182
Asn1OpenType	Com::Objsys::Asn1::Runtime::Asn1OpenType, 138, 139	August	Com::Objsys::Asn1::Runtime::Asn1Time, 182
Asn1OutputStream	Com::Objsys::Asn1::Runtime::Asn1OutputStream, 142	Available	Com::Objsys::Asn1::Runtime::Asn1InputStream, 86
Asn1PrintableString	Com::Objsys::Asn1::Runtime::Asn1PrintableString, 148	BCDToString	Com::Objsys::Asn1::Runtime::Asn1Util, 230
Asn1Real	Com::Objsys::Asn1::Runtime::Asn1Real, 150	BigInteger	Com::Objsys::Asn1::Runtime::BigInteger, 245, 246
		BinDump	Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 64, 65
		Bit8Mask	

Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 BIT_STRING
 Com::Objsys::Asn1::Runtime::Asn1Type, 200
 BITSPERCHAR
 Com::Objsys::Asn1::Runtime::Asn1BMPString, 30
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 219
 BITSPERCHAR_A
 Com::Objsys::Asn1::Runtime::Asn18BitCharString, 9
 Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString, 240
 BITSPERCHAR_U
 Com::Objsys::Asn1::Runtime::Asn18BitCharString, 9
 Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString, 240
 BMPString
 Com::Objsys::Asn1::Runtime::Asn1Type, 200
 bool
 Com::Objsys::Asn1::Runtime::Asn1Time, 185
 BOOLEAN
 Com::Objsys::Asn1::Runtime::Asn1Type, 200
 BooleanHolder
 Com::Objsys::Asn1::Runtime::BooleanHolder, 249
 ByteCount
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 60
 CanRead
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 146
 CanSeek
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 146
 CanWrite
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 146
 Capture
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 56
 Century
 Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 79
 Characters
 Com::Objsys::Asn1::Runtime::Asn1NamedEventHandler, 108
 Com::Objsys::Asn1::Runtime::Asn1TraceHandler, 189
 CharAt
 Com::Objsys::Asn1::Runtime::Asn1Time, 175
 CheckSize
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 65
 ChoiceID
 Com::Objsys::Asn1::Runtime::Asn1Choice, 50
 choiceID
 Com::Objsys::Asn1::Runtime::Asn1Choice, 50
 choiceIndex
 Com::Objsys::Asn1::Runtime::Asn1ChoiceExt, 53
 ClassMask
 Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 Clear
 Com::Objsys::Asn1::Runtime::Asn1BitString, 18
 Com::Objsys::Asn1::Runtime::Asn1Time, 176
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, 222
 Close
 Com::Objsys::Asn1::Runtime::Asn1InputStream, 86
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 143
 Com.Objsys.Asn1.Runtime, 3
 Com::Objsys::Asn1::Runtime::Asn18BitCharString, 5
 Asn18BitCharString, 6
 BITSPERCHAR_A, 9
 BITSPERCHAR_U, 9
 Decode, 6
 Encode, 7, 8
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 10
 _TAG, 15
 Asn1BigInteger, 10, 11
 Decode, 11
 DecodeValue, 12
 DecodeXER, 12
 DecodeXML, 12
 Encode, 12, 13
 EncodeValue, 14
 Equals, 14
 GetHashCode, 14
 mValue, 15
 ToString, 15
 Com::Objsys::Asn1::Runtime::Asn1BitString, 16
 _TAG, 24
 Asn1BitString, 17, 18
 Clear, 18
 Decode, 18, 19
 DecodeXER, 19
 DecodeXML, 19
 Encode, 19–22
 Equals, 22
 Get, 23
 GetHashCode, 23
 IsNamedBitStr, 23
 Length, 25
 mStringFormat, 24
 mValue, 25
 numbits, 25
 Set, 23, 24

- StringFormat, 17
- this, 25
- ToBoolArray, 24
- ToHexString, 24
- ToString, 24
- trimZeroBits, 25
- Com::Objsys::Asn1::Runtime::Asn1BMPString, 26
 - _TAG, 30
 - Asn1BMPString, 26
 - BITSPERCHAR, 30
 - Decode, 27
 - Encode, 28–30
- Com::Objsys::Asn1::Runtime::Asn1Boolean, 31
 - _TAG, 36
 - Asn1Boolean, 31
 - Decode, 32
 - DecodeXER, 32
 - DecodeXML, 33
 - Encode, 33–35
 - EncodeAttribute, 35
 - Equals, 35
 - FALSE_VALUE, 36
 - GetHashCode, 35
 - mValue, 36
 - setTrueEncodedByte, 36
 - ToString, 36
 - TRUE_VALUE, 36
- Com::Objsys::Asn1::Runtime::Asn1CharRange, 37
 - Asn1CharRange, 37
 - GetCharAtIndex, 38
 - GetCharIndex, 38
 - Max Value, 39
 - mLower, 39
 - mUpper, 39
 - validate, 38
- Com::Objsys::Asn1::Runtime::Asn1CharSet, 40
 - Asn1CharSet, 40
 - GetCharAtIndex, 40
 - GetCharIndex, 41
 - GetNumBitsPerChar, 41
 - mABitsPerChar, 42
 - Max Value, 42
 - mUBitsPerChar, 42
 - validate, 41
- Com::Objsys::Asn1::Runtime::Asn1CharString, 43
 - Asn1CharString, 44
 - Decode, 44, 45
 - DecodeXER, 45
 - DecodeXML, 45
 - Encode, 45, 46
 - Equals, 47
 - GetHashCode, 47
 - Length, 48
 - mStringBuffer, 48
 - mValue, 48
 - ToString, 47
 - validate, 48
- Com::Objsys::Asn1::Runtime::Asn1Choice, 49
 - Asn1Choice, 49
 - ChoiceID, 50
 - choiceID, 50
 - element, 50
 - ElemName, 50
 - Equals, 49
 - GetElement, 49
 - GetHashCode, 50
 - SetElement, 50
- Com::Objsys::Asn1::Runtime::Asn1ChoiceExt, 52
 - choiceIndex, 53
 - Decode, 52
 - Encode, 52, 53
- Com::Objsys::Asn1::Runtime::Asn1ConsVioException, 54
 - Asn1ConsVioException, 54
- Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 55
 - AddCaptureBuffer, 56
 - ByteCount, 60
 - Capture, 56
 - DecodeIntValue, 56
 - DecodeOIDContents, 56
 - DecodeRelOIDContents, 56
 - GetInputStream, 57
 - HexDump, 57
 - Init, 57
 - LazyOpenTypeDecode, 60
 - Mark, 57
 - mByteCount, 59
 - Read, 57, 58
 - Read2Bytes, 58
 - Read4Bytes, 58
 - ReadByte, 58
 - RemoveCaptureBuffer, 59
 - Reset, 59
 - SetInputStream, 59
 - Skip, 59
- Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet, 61
 - Asn1DiscreteCharSet, 61
 - GetCharAtIndex, 61
 - GetCharIndex, 62
 - helpValidate, 62
 - Max Value, 63
 - validate, 62
- Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 64
 - BinDump, 64, 65
 - CheckSize, 65
 - Copy, 65
 - HexDump, 65
 - InitBuffer, 65

- mByteIndex, 66
- mData, 66
- MsgCopy, 66
- MsgLength, 66
- mSizeIncrement, 66
- Reset, 66
- SIZE_INCREMENT, 66
- Write, 66
- Com::Objsys::Asn1::Runtime::Asn1EndOfBufferException, 68
 - Asn1EndOfBufferException, 68
- Com::Objsys::Asn1::Runtime::Asn1Enumerated, 69
 - _TAG, 74
 - Asn1Enumerated, 69
 - Decode, 70
 - DecodeXER, 70
 - DecodeXML, 70
 - Encode, 71, 72
 - Equals, 73
 - GetHashCode, 73
 - mValue, 74
 - ParseValue, 73
 - ToString, 73
 - UNDEFINED, 74
- Com::Objsys::Asn1::Runtime::Asn1Exception, 75
 - Asn1Exception, 75
- Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 76
 - _TAG, 79
 - Asn1GeneralizedTime, 76, 77
 - Century, 79
 - CompareTo, 77
 - CompileString, 77
 - Decode, 77
 - Encode, 78
 - ParseString, 78
- Com::Objsys::Asn1::Runtime::Asn1GeneralString, 80
 - _TAG, 81
 - Asn1GeneralString, 80
 - Decode, 80
 - Encode, 80, 81
- Com::Objsys::Asn1::Runtime::Asn1GraphicString, 82
 - _TAG, 83
 - Asn1GraphicString, 82
 - Decode, 82
 - Encode, 82, 83
- Com::Objsys::Asn1::Runtime::Asn1IA5String, 84
 - _TAG, 85
 - Asn1IA5String, 84
 - Decode, 84
 - Encode, 84, 85
- Com::Objsys::Asn1::Runtime::Asn1InputStream, 86
 - Available, 86
 - Close, 86
 - Mark, 86
 - MarkSupported, 86
 - Reset, 86
 - Skip, 87
- Com::Objsys::Asn1::Runtime::Asn1Integer, 88
 - _TAG, 98
 - Asn1Integer, 89
 - Decode, 89, 90
 - Decode16Bit, 90
 - Decode32Bit, 91
 - Decode8Bit, 91
 - DecodeValue, 91
 - DecodeXER, 91
 - DecodeXML, 91
 - Encode, 92–95
 - Encode16Bit, 95
 - Encode32Bit, 95
 - Encode8Bit, 95
 - EncodeAttribute, 95
 - EncodeValue, 96
 - Equals, 96
 - GetBitCount, 96
 - GetHashCode, 97
 - GetUnsignedBitCount, 97
 - mValue, 98
 - ToString, 97
- Com::Objsys::Asn1::Runtime::Asn1InvalidArgException, 99
 - Asn1InvalidArgException, 99
- Com::Objsys::Asn1::Runtime::Asn1InvalidChoiceOptionException, 100
 - Asn1InvalidChoiceOptionException, 100
- Com::Objsys::Asn1::Runtime::Asn1InvalidEnumException, 101
 - Asn1InvalidEnumException, 101
- Com::Objsys::Asn1::Runtime::Asn1InvalidLengthException, 102
 - Asn1InvalidLengthException, 102
- Com::Objsys::Asn1::Runtime::Asn1InvalidObjectIDException, 103
 - Asn1InvalidObjectIDException, 103
- Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, 104
 - AddNamedEventHandler, 104
 - Context, 106
 - EventHandlerList, 106
 - GetInputStream, 104
 - HexDump, 104, 105
 - InvokeCharacters, 105
 - InvokeEndElement, 105
 - InvokeStartElement, 105
 - SetKey, 105
 - SetPermanentKey, 106
 - TypeCode, 106
- Com::Objsys::Asn1::Runtime::Asn1MissingRequiredException, 107

- Asn1MissingRequiredException, 107
- Com::Objsys::Asn1::Runtime::Asn1NamedEventHandler, 108
 - Characters, 108
 - EndElement, 108
 - StartElement, 108
- Com::Objsys::Asn1::Runtime::Asn1Null, 110
 - _TAG, 113
 - Decode, 110
 - DecodeXER, 111
 - DecodeXML, 111
 - Encode, 111, 112
 - Equals, 112
 - NULL_VALUE, 113
 - ToString, 113
- Com::Objsys::Asn1::Runtime::Asn1NumericString, 114
 - _TAG, 116
 - Asn1NumericString, 114
 - Decode, 114, 115
 - Encode, 115, 116
- Com::Objsys::Asn1::Runtime::Asn1ObjectDescriptor, 117
 - _TAG, 118
 - Asn1ObjectDescriptor, 117
 - Decode, 117
 - Encode, 117, 118
- Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 119
 - _TAG, 123
 - Append, 120
 - Asn1ObjectIdentifier, 119
 - Decode, 120
 - DecodeXER, 120
 - DecodeXML, 120
 - Encode, 121, 122
 - Equals, 122
 - GetHashCode, 123
 - MAXSUBIDS, 123
 - mValue, 123
 - ToString, 123
- Com::Objsys::Asn1::Runtime::Asn1OctetString, 124
 - _TAG, 132
 - Asn1OctetString, 125
 - CompareTo, 126
 - Decode, 126
 - DecodeXER, 127
 - DecodeXML, 127
 - Encode, 127–130
 - EncodeAttribute, 130
 - EncodeBase64Binary, 130
 - Equals, 131
 - GetHashCode, 131
 - GetMderLength, 131
 - Length, 132
 - mValue, 132
 - toInputStream, 131
 - ToString, 132
- Com::Objsys::Asn1::Runtime::Asn1OpenExt, 133
 - Decode, 133
 - DecodeComponent, 134
 - DecodeEventComponent, 134
 - DecodeOpenType, 134
 - Encode, 134–136
 - EncodeExtBits, 136
 - mValue, 137
 - SetOpenType, 136
 - ShrinkArray, 136
 - ToString, 136
- Com::Objsys::Asn1::Runtime::Asn1OpenType, 138
 - Asn1OpenType, 138, 139
 - Decode, 139
 - Encode, 139, 140
 - encode, 140
 - mEncodeBuffer, 141
 - mLength, 141
 - ToString, 141
- Com::Objsys::Asn1::Runtime::Asn1OutputStream, 142
 - Asn1OutputStream, 142
 - CanRead, 146
 - CanSeek, 146
 - CanWrite, 146
 - Close, 143
 - Context, 146
 - Flush, 143
 - Length, 146
 - os, 146
 - Position, 147
 - Read, 143
 - Seek, 143
 - SetLength, 144
 - Write, 144
 - Write2Bytes, 145
 - Write4Bytes, 145
 - WriteByte, 145
- Com::Objsys::Asn1::Runtime::Asn1PrintableString, 148
 - _TAG, 149
 - Asn1PrintableString, 148
 - Decode, 148
 - Encode, 148, 149
- Com::Objsys::Asn1::Runtime::Asn1Real, 150
 - _TAG, 154
 - Asn1Real, 150
 - Decode, 151
 - DecodeXER, 151
 - DecodeXML, 151
 - Encode, 151–153
 - EncodeAttribute, 153
 - EncodeValue, 153
 - Equals, 153, 154

- GetHashCode, 154
- mValue, 154
- ToString, 154
- Com::Objsys::Asn1::Runtime::Asn1Real10, 155
 - _TAG, 159
 - Asn1Real10, 155
 - ConvertToDecimal, 156
 - ConvertToNR3Form, 156
 - Decode, 156
 - Encode, 156–158
 - EncodeAttribute, 158
 - GetNumberForm, 158, 159
- Com::Objsys::Asn1::Runtime::Asn1RelativeOID, 160
 - _TAG, 163
 - Asn1RelativeOID, 160
 - Decode, 160, 161
 - DecodeXER, 161
 - DecodeXML, 161
 - Encode, 161–163
- Com::Objsys::Asn1::Runtime::Asn1SeqOrderException, 164
 - Asn1SeqOrderException, 164
- Com::Objsys::Asn1::Runtime::Asn1Status, 165
 - INDEFLEN, 165
- Com::Objsys::Asn1::Runtime::Asn1T61String, 166
 - _TAG, 167
 - Asn1T61String, 166
 - Decode, 166
 - Encode, 166, 167
- Com::Objsys::Asn1::Runtime::Asn1Tag, 168
 - APPL, 170
 - Asn1Tag, 169
 - Bit8Mask, 170
 - ClassMask, 170
 - CONS, 170
 - Constructed, 172
 - CTXT, 170
 - ENUM, 170
 - EOC, 170
 - Equals, 169
 - EXPL, 170
 - EXTIDCODE, 170
 - FormMask, 170
 - IDMask, 171
 - IMPL, 171
 - IsEOC, 169
 - L7BitsMask, 171
 - mClass, 171
 - mForm, 171
 - mIDCode, 171
 - PRIM, 171
 - PRIV, 171
 - SEQUENCE, 171
 - SET, 171
 - ToString, 169
 - UNIV, 171
- Com::Objsys::Asn1::Runtime::Asn1Time, 173
 - Apr, 182
 - April, 182
 - Asn1Time, 175
 - Aug, 182
 - August, 182
 - bool, 185
 - CharAt, 175
 - Clear, 176
 - CompareTo, 176
 - CompileString, 176
 - Day, 185
 - day, 182
 - Dec, 183
 - December, 183
 - Decode, 176
 - DecodeXML, 177
 - derRules, 183
 - DiffHour, 185
 - diffHour, 183
 - diffMin, 183
 - DiffMinute, 186
 - Encode, 177, 178
 - EncodeXER, 178
 - EncodeXMLData, 179
 - Equals, 179
 - Feb, 183
 - February, 183
 - Fraction, 186
 - GetDiff, 179
 - GetHashCode, 179
 - GetTime, 180
 - Hour, 186
 - hour, 183
 - Init, 180
 - Jan, 183
 - January, 183
 - Jul, 183
 - July, 183
 - Jun, 184
 - June, 184
 - Mar, 184
 - March, 184
 - May, 184
 - Minute, 186
 - minute, 184
 - Month, 187
 - month, 184
 - Nov, 184
 - November, 184
 - Oct, 184
 - October, 184

parsed, 184
 ParseInt, 180
 ParseString, 180
 ParseXmlString, 180
 PutInteger, 181
 SafeParseString, 181
 secFraction, 185
 Second, 187
 second, 185
 Sep, 185
 September, 185
 SetDiff, 181
 SetTime, 182
 UTC, 187
 utcFlag, 185
 Year, 187
 year, 185
 Com::Objsys::Asn1::Runtime::Asn1TraceHandler, 189
 Asn1TraceHandler, 189
 Characters, 189
 EndElement, 189
 StartElement, 190
 Com::Objsys::Asn1::Runtime::Asn1Type, 191
 _TAG, 200
 BIT_STRING, 200
 BMPString, 200
 BOOLEAN, 200
 DATE, 200
 Decode, 192, 193
 DecodeXML, 194
 Encode, 194–196
 ENUMERATED, 200
 EOC, 200
 Equals, 197
 EXTERNAL, 201
 GeneralString, 201
 GeneralTime, 201
 GetTypeNames, 197
 GraphicString, 201
 IA5String, 201
 Indent, 197
 INTEGER, 201
 IsOpenType, 197
 Length, 203
 MatchTag, 198
 MatchTypeName, 198
 NULL, 201
 NumericString, 201
 OBJECT_IDENTIFIER, 201
 ObjectDescriptor, 201
 OCTET_STRING, 201
 Pdiag, 199
 Print, 199
 PrintableString, 201
 REAL, 202
 RelativeOID, 202
 SEQUENCE, 202
 SET, 202
 SetKey, 199
 SetKey2, 199
 SetOpenType, 200
 T61String, 202
 TeletexString, 202
 TIME, 202
 UniversalString, 202
 UTCTime, 202
 UTF8String, 202
 VideotexString, 202
 VisibleString, 202
 Com::Objsys::Asn1::Runtime::Asn1TypeIF, 204
 Decode, 204, 205
 Encode, 205–207
 IsOpenType, 207
 Print, 207
 SetOpenType, 207
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 209
 _TAG, 219
 Asn1UniversalString, 210
 BITSPERCHAR, 219
 Decode, 211, 212
 DecodeXER, 212
 DecodeXML, 213
 Encode, 213–218
 EncodeData, 218
 Equals, 218
 GetHashCode, 218
 Length, 220
 mStringBuffer, 219
 mValue, 219
 ToString, 219
 validate, 219
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, 221
 _TAG, 224
 Asn1UTCTime, 221, 222
 Clear, 222
 CompareTo, 222
 CompileString, 222
 Decode, 222
 Encode, 223
 Fraction, 224
 Init, 223
 ParseString, 223
 SetTime, 224
 Year, 224
 Com::Objsys::Asn1::Runtime::Asn1UTF8String, 226
 _TAG, 229
 Asn1UTF8String, 226
 Decode, 226, 227

- Encode, 227–229
- Com::Objsys::Asn1::Runtime::Asn1Util, 230
 - BCDToString, 230
 - DecodeBase64Array, 230
 - EncodeBase64Array, 231
 - GetAddressBytes, 231
 - GetBytesCount, 231
 - GetUlongBytesCount, 231
 - StringToBCD, 231
 - StringToTBCD, 232
 - TBCDToString, 232
 - ToArray, 232
 - ToByteArray, 233
 - ToCharArray, 233
 - ToHexString, 233
 - URShift, 234
 - WriteStackTrace, 235
- Com::Objsys::Asn1::Runtime::Asn1Value, 236
 - ParseString, 236
- Com::Objsys::Asn1::Runtime::Asn1ValueParseException, 237
 - Asn1ValueParseException, 237
- Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString, 238
 - Asn1VarWidthCharString, 238
 - BITSPERCHAR_A, 240
 - BITSPERCHAR_U, 240
 - Decode, 239
 - Encode, 239, 240
- Com::Objsys::Asn1::Runtime::Asn1VideotexString, 241
 - _TAG, 242
 - Asn1VideotexString, 241
 - Decode, 241
 - Encode, 242
- Com::Objsys::Asn1::Runtime::Asn1VisibleString, 243
 - _TAG, 244
 - Asn1VisibleString, 243
 - Decode, 243
 - Encode, 243, 244
- Com::Objsys::Asn1::Runtime::BigInteger, 245
 - BigInteger, 245, 246
 - Equals, 246
 - GetData, 246
 - GetHashCode, 247
 - Init, 247
 - IsNegative, 247
 - operator BigInteger, 247
 - SecureDelete, 247
 - SetData, 247
 - ToString, 248
- Com::Objsys::Asn1::Runtime::BooleanHolder, 249
 - BooleanHolder, 249
 - mValue, 249
- Com::Objsys::Asn1::Runtime::Diag, 250
 - HexDump, 250, 251
 - Instance, 251
 - IsEnabled, 251
 - Println, 251
 - PrintStream, 253
 - Prtln, 252
 - SetEnabled, 252
 - SetTraceLevel, 253
 - SetTraceLevel2, 253
- Com::Objsys::Asn1::Runtime::IntHolder, 254
 - IntHolder, 254
 - mValue, 254
- Com::Objsys::Asn1::Runtime::StringBufferExt, 255
 - Replace, 255
- Com::Objsys::Asn1::Runtime::Tokenizer, 256
 - Count, 258
 - Current, 258
 - HasMoreTokens, 257
 - MoveNext, 257
 - NextToken, 257
 - RemainingString, 257
 - Reset, 257
 - Tokenizer, 256
- CompareTo
 - Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 77
 - Com::Objsys::Asn1::Runtime::Asn1OctetString, 126
 - Com::Objsys::Asn1::Runtime::Asn1Time, 176
 - Com::Objsys::Asn1::Runtime::Asn1UTCTime, 222
- CompileString
 - Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 77
 - Com::Objsys::Asn1::Runtime::Asn1Time, 176
 - Com::Objsys::Asn1::Runtime::Asn1UTCTime, 222
- CONS
 - Com::Objsys::Asn1::Runtime::Asn1Tag, 170
- Constructed
 - Com::Objsys::Asn1::Runtime::Asn1Tag, 172
- Context
 - Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, 106
 - Com::Objsys::Asn1::Runtime::Asn1OutputStream, 146
- ConvertToDecimal
 - Com::Objsys::Asn1::Runtime::Asn1Real10, 156
- ConvertToNR3Form
 - Com::Objsys::Asn1::Runtime::Asn1Real10, 156
- Copy
 - Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 65
- Count
 - Com::Objsys::Asn1::Runtime::Tokenizer, 258
- CTXT

Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 Current
 Com::Objsys::Asn1::Runtime::Tokenizer, 258
 DATE
 Com::Objsys::Asn1::Runtime::Asn1Type, 200
 Day
 Com::Objsys::Asn1::Runtime::Asn1Time, 185
 day
 Com::Objsys::Asn1::Runtime::Asn1Time, 182
 Dec
 Com::Objsys::Asn1::Runtime::Asn1Time, 183
 December
 Com::Objsys::Asn1::Runtime::Asn1Time, 183
 Decode
 Com::Objsys::Asn1::Runtime::Asn18BitCharString, 6
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 11
 Com::Objsys::Asn1::Runtime::Asn1BitString, 18, 19
 Com::Objsys::Asn1::Runtime::Asn1BMPString, 27
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 32
 Com::Objsys::Asn1::Runtime::Asn1CharString, 44, 45
 Com::Objsys::Asn1::Runtime::Asn1ChoiceExt, 52
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, 70
 Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 77
 Com::Objsys::Asn1::Runtime::Asn1GeneralString, 80
 Com::Objsys::Asn1::Runtime::Asn1GraphicString, 82
 Com::Objsys::Asn1::Runtime::Asn1IA5String, 84
 Com::Objsys::Asn1::Runtime::Asn1Integer, 89, 90
 Com::Objsys::Asn1::Runtime::Asn1Null, 110
 Com::Objsys::Asn1::Runtime::Asn1NumericString, 114, 115
 Com::Objsys::Asn1::Runtime::Asn1ObjectDescriptor, 117
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 120
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 126
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, 133
 Com::Objsys::Asn1::Runtime::Asn1OpenType, 139
 Com::Objsys::Asn1::Runtime::Asn1PrintableString, 148
 Com::Objsys::Asn1::Runtime::Asn1Real, 151
 Com::Objsys::Asn1::Runtime::Asn1Real10, 156
 Com::Objsys::Asn1::Runtime::Asn1RelativeOID, 160, 161
 Com::Objsys::Asn1::Runtime::Asn1T61String, 166
 Com::Objsys::Asn1::Runtime::Asn1Time, 176
 Com::Objsys::Asn1::Runtime::Asn1Type, 192, 193
 Com::Objsys::Asn1::Runtime::Asn1TypeIF, 204, 205
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 211, 212
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, 222
 Com::Objsys::Asn1::Runtime::Asn1UTF8String, 226, 227
 Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString, 239
 Com::Objsys::Asn1::Runtime::Asn1VideotexString, 241
 Com::Objsys::Asn1::Runtime::Asn1VisibleString, 243
 Decode16Bit
 Com::Objsys::Asn1::Runtime::Asn1Integer, 90
 Decode32Bit
 Com::Objsys::Asn1::Runtime::Asn1Integer, 91
 Decode8Bit
 Com::Objsys::Asn1::Runtime::Asn1Integer, 91
 DecodeBase64Array
 Com::Objsys::Asn1::Runtime::Asn1Util, 230
 DecodeComponent
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, 134
 DecodeEventComponent
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, 134
 DecodeIntValue
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 56
 DecodeOIDContents
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 56
 DecodeOpenType
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, 134
 DecodeRelOIDContents
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 56
 DecodeValue
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 12
 Com::Objsys::Asn1::Runtime::Asn1Integer, 91
 DecodeXER
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 12
 Com::Objsys::Asn1::Runtime::Asn1BitString, 19
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 32
 Com::Objsys::Asn1::Runtime::Asn1CharString, 45
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, 70
 Com::Objsys::Asn1::Runtime::Asn1Integer, 91
 Com::Objsys::Asn1::Runtime::Asn1Null, 111
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 120
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 127
 Com::Objsys::Asn1::Runtime::Asn1Real, 151
 Com::Objsys::Asn1::Runtime::Asn1RelativeOID, 161

Com::Objsys::Asn1::Runtime::Asn1UniversalString, 212

DecodeXML

- Com::Objsys::Asn1::Runtime::Asn1BigInteger, 12
- Com::Objsys::Asn1::Runtime::Asn1BitString, 19
- Com::Objsys::Asn1::Runtime::Asn1Boolean, 33
- Com::Objsys::Asn1::Runtime::Asn1CharString, 45
- Com::Objsys::Asn1::Runtime::Asn1Enumerated, 70
- Com::Objsys::Asn1::Runtime::Asn1Integer, 91
- Com::Objsys::Asn1::Runtime::Asn1Null, 111
- Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 120
- Com::Objsys::Asn1::Runtime::Asn1OctetString, 127
- Com::Objsys::Asn1::Runtime::Asn1Real, 151
- Com::Objsys::Asn1::Runtime::Asn1RelativeOID, 161
- Com::Objsys::Asn1::Runtime::Asn1Time, 177
- Com::Objsys::Asn1::Runtime::Asn1Type, 194
- Com::Objsys::Asn1::Runtime::Asn1UniversalString, 213

derRules

- Com::Objsys::Asn1::Runtime::Asn1Time, 183

DiffHour

- Com::Objsys::Asn1::Runtime::Asn1Time, 185

diffHour

- Com::Objsys::Asn1::Runtime::Asn1Time, 183

diffMin

- Com::Objsys::Asn1::Runtime::Asn1Time, 183

DiffMinute

- Com::Objsys::Asn1::Runtime::Asn1Time, 186

element

- Com::Objsys::Asn1::Runtime::Asn1Choice, 50

ElemName

- Com::Objsys::Asn1::Runtime::Asn1Choice, 50

Encode

- Com::Objsys::Asn1::Runtime::Asn18BitCharString, 7, 8
- Com::Objsys::Asn1::Runtime::Asn1BigInteger, 12, 13
- Com::Objsys::Asn1::Runtime::Asn1BitString, 19–22
- Com::Objsys::Asn1::Runtime::Asn1BMPString, 28–30
- Com::Objsys::Asn1::Runtime::Asn1Boolean, 33–35
- Com::Objsys::Asn1::Runtime::Asn1CharString, 45, 46
- Com::Objsys::Asn1::Runtime::Asn1ChoiceExt, 52, 53
- Com::Objsys::Asn1::Runtime::Asn1Enumerated, 71, 72
- Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, 78

- Com::Objsys::Asn1::Runtime::Asn1GeneralString, 80, 81
- Com::Objsys::Asn1::Runtime::Asn1GraphicString, 82, 83
- Com::Objsys::Asn1::Runtime::Asn1IA5String, 84, 85
- Com::Objsys::Asn1::Runtime::Asn1Integer, 92–95
- Com::Objsys::Asn1::Runtime::Asn1Null, 111, 112
- Com::Objsys::Asn1::Runtime::Asn1NumericString, 115, 116
- Com::Objsys::Asn1::Runtime::Asn1ObjectDescriptor, 117, 118
- Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 121, 122
- Com::Objsys::Asn1::Runtime::Asn1OctetString, 127–130
- Com::Objsys::Asn1::Runtime::Asn1OpenExt, 134–136
- Com::Objsys::Asn1::Runtime::Asn1OpenType, 139, 140
- Com::Objsys::Asn1::Runtime::Asn1PrintableString, 148, 149
- Com::Objsys::Asn1::Runtime::Asn1Real, 151–153
- Com::Objsys::Asn1::Runtime::Asn1Real10, 156–158
- Com::Objsys::Asn1::Runtime::Asn1RelativeOID, 161–163
- Com::Objsys::Asn1::Runtime::Asn1T61String, 166, 167
- Com::Objsys::Asn1::Runtime::Asn1Time, 177, 178
- Com::Objsys::Asn1::Runtime::Asn1Type, 194–196
- Com::Objsys::Asn1::Runtime::Asn1TypeIF, 205–207
- Com::Objsys::Asn1::Runtime::Asn1UniversalString, 213–218
- Com::Objsys::Asn1::Runtime::Asn1UTCTime, 223
- Com::Objsys::Asn1::Runtime::Asn1UTF8String, 227–229
- Com::Objsys::Asn1::Runtime::Asn1VarWidthCharString, 239, 240
- Com::Objsys::Asn1::Runtime::Asn1VideotexString, 242
- Com::Objsys::Asn1::Runtime::Asn1VisibleString, 243, 244

encode

- Com::Objsys::Asn1::Runtime::Asn1OpenType, 140

Encode16Bit

- Com::Objsys::Asn1::Runtime::Asn1Integer, 95

Encode32Bit

- Com::Objsys::Asn1::Runtime::Asn1Integer, 95

Encode8Bit

- Com::Objsys::Asn1::Runtime::Asn1Integer, 95

EncodeAttribute

- Com::Objsys::Asn1::Runtime::Asn1Boolean, 35

Com::Objsys::Asn1::Runtime::Asn1Integer, 95
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 130
 Com::Objsys::Asn1::Runtime::Asn1Real, 153
 Com::Objsys::Asn1::Runtime::Asn1Real10, 158
 EncodeBase64Array
 Com::Objsys::Asn1::Runtime::Asn1Util, 231
 EncodeBase64Binary
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 130
 EncodeData
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 218
 EncodeExtBits
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, 136
 EncodeValue
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 14
 Com::Objsys::Asn1::Runtime::Asn1Integer, 96
 Com::Objsys::Asn1::Runtime::Asn1Real, 153
 EncodeXER
 Com::Objsys::Asn1::Runtime::Asn1Time, 178
 EncodeXMLData
 Com::Objsys::Asn1::Runtime::Asn1Time, 179
 EndElement
 Com::Objsys::Asn1::Runtime::Asn1NamedEventHandler, 108
 Com::Objsys::Asn1::Runtime::Asn1TraceHandler, 189
 ENUM
 Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 ENUMERATED
 Com::Objsys::Asn1::Runtime::Asn1Type, 200
 EOC
 Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 Com::Objsys::Asn1::Runtime::Asn1Type, 200
 Equals
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 14
 Com::Objsys::Asn1::Runtime::Asn1BitString, 22
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 35
 Com::Objsys::Asn1::Runtime::Asn1CharString, 47
 Com::Objsys::Asn1::Runtime::Asn1Choice, 49
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, 73
 Com::Objsys::Asn1::Runtime::Asn1Integer, 96
 Com::Objsys::Asn1::Runtime::Asn1Null, 112
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 122
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 131
 Com::Objsys::Asn1::Runtime::Asn1Real, 153, 154
 Com::Objsys::Asn1::Runtime::Asn1Tag, 169
 Com::Objsys::Asn1::Runtime::Asn1Time, 179
 Com::Objsys::Asn1::Runtime::Asn1Type, 197
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 218
 Com::Objsys::Asn1::Runtime::BigInteger, 246
 EventHandlerList
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, 106
 EXPL
 Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 EXTERNAL
 Com::Objsys::Asn1::Runtime::Asn1Type, 201
 EXTIDCODE
 Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 FALSE_VALUE
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 36
 Feb
 Com::Objsys::Asn1::Runtime::Asn1Time, 183
 February
 Com::Objsys::Asn1::Runtime::Asn1Time, 183
 Flush
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 143
 FormMask
 Com::Objsys::Asn1::Runtime::Asn1Tag, 170
 Fraction
 Com::Objsys::Asn1::Runtime::Asn1Time, 186
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, 224
 GeneralString
 Com::Objsys::Asn1::Runtime::Asn1Type, 201
 GeneralTime
 Com::Objsys::Asn1::Runtime::Asn1Type, 201
 Get
 Com::Objsys::Asn1::Runtime::Asn1BitString, 23
 GetAddressBytes
 Com::Objsys::Asn1::Runtime::Asn1Util, 231
 GetBitCount
 Com::Objsys::Asn1::Runtime::Asn1Integer, 96
 GetBytesCount
 Com::Objsys::Asn1::Runtime::Asn1Util, 231
 GetCharAtIndex
 Com::Objsys::Asn1::Runtime::Asn1CharRange, 38
 Com::Objsys::Asn1::Runtime::Asn1CharSet, 40
 Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet, 61
 GetCharIndex
 Com::Objsys::Asn1::Runtime::Asn1CharRange, 38
 Com::Objsys::Asn1::Runtime::Asn1CharSet, 41
 Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet, 62
 GetData
 Com::Objsys::Asn1::Runtime::BigInteger, 246
 GetDiff
 Com::Objsys::Asn1::Runtime::Asn1Time, 179
 GetElement
 Com::Objsys::Asn1::Runtime::Asn1Choice, 49

[GetHashCode](#)
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, [14](#)
 Com::Objsys::Asn1::Runtime::Asn1BitString, [23](#)
 Com::Objsys::Asn1::Runtime::Asn1Boolean, [35](#)
 Com::Objsys::Asn1::Runtime::Asn1CharString, [47](#)
 Com::Objsys::Asn1::Runtime::Asn1Choice, [50](#)
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, [73](#)
 Com::Objsys::Asn1::Runtime::Asn1Integer, [97](#)
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, [123](#)
 Com::Objsys::Asn1::Runtime::Asn1OctetString, [131](#)
 Com::Objsys::Asn1::Runtime::Asn1Real, [154](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [179](#)
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, [218](#)
 Com::Objsys::Asn1::Runtime::BigInteger, [247](#)

[GetInputStream](#)
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [57](#)
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [104](#)

[GetMderLength](#)
 Com::Objsys::Asn1::Runtime::Asn1OctetString, [131](#)

[GetNumberForm](#)
 Com::Objsys::Asn1::Runtime::Asn1Real10, [158](#), [159](#)

[GetNumBitsPerChar](#)
 Com::Objsys::Asn1::Runtime::Asn1CharSet, [41](#)

[GetTime](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [180](#)

[GetTypeNames](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [197](#)

[GetUlongBytesCount](#)
 Com::Objsys::Asn1::Runtime::Asn1Util, [231](#)

[GetUnsignedBitCount](#)
 Com::Objsys::Asn1::Runtime::Asn1Integer, [97](#)

[GraphicString](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

[HasMoreTokens](#)
 Com::Objsys::Asn1::Runtime::Tokenizer, [257](#)

[helpValidate](#)
 Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet, [62](#)

[HexDump](#)
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [57](#)
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, [65](#)
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [104](#), [105](#)
 Com::Objsys::Asn1::Runtime::Diag, [250](#), [251](#)

[Hour](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [186](#)

[hour](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [183](#)

[IA5String](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

[IDMask](#)
 Com::Objsys::Asn1::Runtime::Asn1Tag, [171](#)

[IMPL](#)
 Com::Objsys::Asn1::Runtime::Asn1Tag, [171](#)

[INDEFLEN](#)
 Com::Objsys::Asn1::Runtime::Asn1Status, [165](#)

[Indent](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [197](#)

[Init](#)
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [57](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [180](#)
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, [223](#)
 Com::Objsys::Asn1::Runtime::BigInteger, [247](#)

[InitBuffer](#)
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, [65](#)

[Instance](#)
 Com::Objsys::Asn1::Runtime::Diag, [251](#)

[INTEGER](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

[IntHolder](#)
 Com::Objsys::Asn1::Runtime::IntHolder, [254](#)

[InvokeCharacters](#)
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [105](#)

[InvokeEndElement](#)
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [105](#)

[InvokeStartElement](#)
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [105](#)

[IsEnabled](#)
 Com::Objsys::Asn1::Runtime::Diag, [251](#)

[IsEOC](#)
 Com::Objsys::Asn1::Runtime::Asn1Tag, [169](#)

[IsNamedBitStr](#)
 Com::Objsys::Asn1::Runtime::Asn1BitString, [23](#)

[IsNegative](#)
 Com::Objsys::Asn1::Runtime::BigInteger, [247](#)

[IsOpenType](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [197](#)
 Com::Objsys::Asn1::Runtime::Asn1TypeIF, [207](#)

[Jan](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [183](#)

[January](#)

Com::Objsys::Asn1::Runtime::Asn1Time, 183
 Jul
 Com::Objsys::Asn1::Runtime::Asn1Time, 183
 July
 Com::Objsys::Asn1::Runtime::Asn1Time, 183
 Jun
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 June
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 L7BitsMask
 Com::Objsys::Asn1::Runtime::Asn1Tag, 171
 LazyOpenTypeDecode
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 60
 Length
 Com::Objsys::Asn1::Runtime::Asn1BitString, 25
 Com::Objsys::Asn1::Runtime::Asn1CharString, 48
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 132
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 146
 Com::Objsys::Asn1::Runtime::Asn1Type, 203
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 220
 mABitsPerChar
 Com::Objsys::Asn1::Runtime::Asn1CharSet, 42
 Mar
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 March
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 Mark
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 57
 Com::Objsys::Asn1::Runtime::Asn1InputStream, 86
 MarkSupported
 Com::Objsys::Asn1::Runtime::Asn1InputStream, 86
 MatchTag
 Com::Objsys::Asn1::Runtime::Asn1Type, 198
 MatchTypeName
 Com::Objsys::Asn1::Runtime::Asn1Type, 198
 MAXSUBIDS
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 123
 MaxValue
 Com::Objsys::Asn1::Runtime::Asn1CharRange, 39
 Com::Objsys::Asn1::Runtime::Asn1CharSet, 42
 Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet, 63
 May
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 mByteCount
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, 59
 mByteIndex
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 66
 mClass
 Com::Objsys::Asn1::Runtime::Asn1Tag, 171
 mData
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 66
 mEncodeBuffer
 Com::Objsys::Asn1::Runtime::Asn1OpenType, 141
 mForm
 Com::Objsys::Asn1::Runtime::Asn1Tag, 171
 mIDCode
 Com::Objsys::Asn1::Runtime::Asn1Tag, 171
 Minute
 Com::Objsys::Asn1::Runtime::Asn1Time, 186
 minute
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 mLength
 Com::Objsys::Asn1::Runtime::Asn1OpenType, 141
 mLower
 Com::Objsys::Asn1::Runtime::Asn1CharRange, 39
 Month
 Com::Objsys::Asn1::Runtime::Asn1Time, 187
 month
 Com::Objsys::Asn1::Runtime::Asn1Time, 184
 MoveNext
 Com::Objsys::Asn1::Runtime::Tokenizer, 257
 MsgCopy
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 66
 MsgLength
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 66
 mSizeIncrement
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 66
 mStringBuffer
 Com::Objsys::Asn1::Runtime::Asn1CharString, 48
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 219
 mStringFormat
 Com::Objsys::Asn1::Runtime::Asn1BitString, 24
 mUBitsPerChar
 Com::Objsys::Asn1::Runtime::Asn1CharSet, 42
 mUpper
 Com::Objsys::Asn1::Runtime::Asn1CharRange, 39
 mValue
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 15
 Com::Objsys::Asn1::Runtime::Asn1BitString, 25
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 36

Com::Objsys::Asn1::Runtime::Asn1CharString, [48](#)
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, [74](#)
 Com::Objsys::Asn1::Runtime::Asn1Integer, [98](#)
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, [123](#)
 Com::Objsys::Asn1::Runtime::Asn1OctetString, [132](#)
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, [137](#)
 Com::Objsys::Asn1::Runtime::Asn1Real, [154](#)
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, [219](#)
 Com::Objsys::Asn1::Runtime::BooleanHolder, [249](#)
 Com::Objsys::Asn1::Runtime::IntHolder, [254](#)

NextToken
 Com::Objsys::Asn1::Runtime::Tokenizer, [257](#)

Nov
 Com::Objsys::Asn1::Runtime::Asn1Time, [184](#)

November
 Com::Objsys::Asn1::Runtime::Asn1Time, [184](#)

NULL
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

NULL_VALUE
 Com::Objsys::Asn1::Runtime::Asn1Null, [113](#)

numbits
 Com::Objsys::Asn1::Runtime::Asn1BitString, [25](#)

NumericString
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

OBJECT_IDENTIFIER
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

ObjectDescriptor
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

Oct
 Com::Objsys::Asn1::Runtime::Asn1Time, [184](#)

OCTET_STRING
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

October
 Com::Objsys::Asn1::Runtime::Asn1Time, [184](#)

operator BigInteger
 Com::Objsys::Asn1::Runtime::BigInteger, [247](#)

os
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, [146](#)

parsed
 Com::Objsys::Asn1::Runtime::Asn1Time, [184](#)

ParseInt
 Com::Objsys::Asn1::Runtime::Asn1Time, [180](#)

ParseString
 Com::Objsys::Asn1::Runtime::Asn1GeneralizedTime, [78](#)
 Com::Objsys::Asn1::Runtime::Asn1Time, [180](#)
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, [223](#)
 Com::Objsys::Asn1::Runtime::Asn1Value, [236](#)

ParseValue
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, [73](#)

ParseXmlString
 Com::Objsys::Asn1::Runtime::Asn1Time, [180](#)

Pdiag
 Com::Objsys::Asn1::Runtime::Asn1Type, [199](#)

Position
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, [147](#)

PRIM
 Com::Objsys::Asn1::Runtime::Asn1Tag, [171](#)

Print
 Com::Objsys::Asn1::Runtime::Asn1Type, [199](#)
 Com::Objsys::Asn1::Runtime::Asn1TypeIF, [207](#)

PrintableString
 Com::Objsys::Asn1::Runtime::Asn1Type, [201](#)

Println
 Com::Objsys::Asn1::Runtime::Diag, [251](#)

PrintStream
 Com::Objsys::Asn1::Runtime::Diag, [253](#)

PRIV
 Com::Objsys::Asn1::Runtime::Asn1Tag, [171](#)

Prtln
 Com::Objsys::Asn1::Runtime::Diag, [252](#)

PutInteger
 Com::Objsys::Asn1::Runtime::Asn1Time, [181](#)

Read
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [57, 58](#)
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, [143](#)

Read2Bytes
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [58](#)

Read4Bytes
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [58](#)

ReadByte
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [58](#)

REAL
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)

RelativeOID
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)

RemainingString
 Com::Objsys::Asn1::Runtime::Tokenizer, [257](#)

RemoveCaptureBuffer
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [59](#)

Replace
 Com::Objsys::Asn1::Runtime::StringBufferExt, [255](#)

Reset

Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [59](#)
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, [66](#)
 Com::Objsys::Asn1::Runtime::Asn1InputStream, [86](#)
 Com::Objsys::Asn1::Runtime::Tokenizer, [257](#)
 SafeParseString
 Com::Objsys::Asn1::Runtime::Asn1Time, [181](#)
 secFraction
 Com::Objsys::Asn1::Runtime::Asn1Time, [185](#)
 Second
 Com::Objsys::Asn1::Runtime::Asn1Time, [187](#)
 second
 Com::Objsys::Asn1::Runtime::Asn1Time, [185](#)
 SecureDelete
 Com::Objsys::Asn1::Runtime::BigInteger, [247](#)
 Seek
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, [143](#)
 Sep
 Com::Objsys::Asn1::Runtime::Asn1Time, [185](#)
 September
 Com::Objsys::Asn1::Runtime::Asn1Time, [185](#)
 SEQUENCE
 Com::Objsys::Asn1::Runtime::Asn1Tag, [171](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)
 SET
 Com::Objsys::Asn1::Runtime::Asn1Tag, [171](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)
 Set
 Com::Objsys::Asn1::Runtime::Asn1BitString, [23](#), [24](#)
 SetData
 Com::Objsys::Asn1::Runtime::BigInteger, [247](#)
 SetDiff
 Com::Objsys::Asn1::Runtime::Asn1Time, [181](#)
 SetElement
 Com::Objsys::Asn1::Runtime::Asn1Choice, [50](#)
 SetEnabled
 Com::Objsys::Asn1::Runtime::Diag, [252](#)
 SetInputStream
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [59](#)
 SetKey
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [105](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [199](#)
 SetKey2
 Com::Objsys::Asn1::Runtime::Asn1Type, [199](#)
 SetLength
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, [144](#)
 SetOpenType
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, [136](#)
 Com::Objsys::Asn1::Runtime::Asn1Type, [200](#)
 Com::Objsys::Asn1::Runtime::Asn1TypeIF, [207](#)
 SetPermanentKey
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, [106](#)
 SetTime
 Com::Objsys::Asn1::Runtime::Asn1Time, [182](#)
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, [224](#)
 SetTraceLevel
 Com::Objsys::Asn1::Runtime::Diag, [253](#)
 SetTraceLevel2
 Com::Objsys::Asn1::Runtime::Diag, [253](#)
 setTrueEncodedByte
 Com::Objsys::Asn1::Runtime::Asn1Boolean, [36](#)
 ShrinkArray
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, [136](#)
 SIZE_INCREMENT
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, [66](#)
 Skip
 Com::Objsys::Asn1::Runtime::Asn1DecodeBuffer, [59](#)
 Com::Objsys::Asn1::Runtime::Asn1InputStream, [87](#)
 StartElement
 Com::Objsys::Asn1::Runtime::Asn1NamedEventHandler, [108](#)
 Com::Objsys::Asn1::Runtime::Asn1TraceHandler, [190](#)
 StringFormat
 Com::Objsys::Asn1::Runtime::Asn1BitString, [17](#)
 StringToBCD
 Com::Objsys::Asn1::Runtime::Asn1Util, [231](#)
 StringToTBCD
 Com::Objsys::Asn1::Runtime::Asn1Util, [232](#)
 T61String
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)
 TBCDToString
 Com::Objsys::Asn1::Runtime::Asn1Util, [232](#)
 TeletexString
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)
 this
 Com::Objsys::Asn1::Runtime::Asn1BitString, [25](#)
 TIME
 Com::Objsys::Asn1::Runtime::Asn1Type, [202](#)
 ToArray
 Com::Objsys::Asn1::Runtime::Asn1Util, [232](#)
 ToBoolArray
 Com::Objsys::Asn1::Runtime::Asn1BitString, [24](#)
 ToByteArray
 Com::Objsys::Asn1::Runtime::Asn1Util, [233](#)

ToCharArray
 Com::Objsys::Asn1::Runtime::Asn1Util, 233
 ToHexString
 Com::Objsys::Asn1::Runtime::Asn1BitString, 24
 Com::Objsys::Asn1::Runtime::Asn1Util, 233
 toInputStream
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 131
 Tokenizer
 Com::Objsys::Asn1::Runtime::Tokenizer, 256
 ToString
 Com::Objsys::Asn1::Runtime::Asn1BigInteger, 15
 Com::Objsys::Asn1::Runtime::Asn1BitString, 24
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 36
 Com::Objsys::Asn1::Runtime::Asn1CharString, 47
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, 73
 Com::Objsys::Asn1::Runtime::Asn1Integer, 97
 Com::Objsys::Asn1::Runtime::Asn1Null, 113
 Com::Objsys::Asn1::Runtime::Asn1ObjectIdentifier, 123
 Com::Objsys::Asn1::Runtime::Asn1OctetString, 132
 Com::Objsys::Asn1::Runtime::Asn1OpenExt, 136
 Com::Objsys::Asn1::Runtime::Asn1OpenType, 141
 Com::Objsys::Asn1::Runtime::Asn1Real, 154
 Com::Objsys::Asn1::Runtime::Asn1Tag, 169
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 219
 Com::Objsys::Asn1::Runtime::BigInteger, 248
 trimZeroBits
 Com::Objsys::Asn1::Runtime::Asn1BitString, 25
 TRUE_VALUE
 Com::Objsys::Asn1::Runtime::Asn1Boolean, 36
 TypeCode
 Com::Objsys::Asn1::Runtime::Asn1MessageBuffer, 106

 UNDEFINED
 Com::Objsys::Asn1::Runtime::Asn1Enumerated, 74
 UNIV
 Com::Objsys::Asn1::Runtime::Asn1Tag, 171
 UniversalString
 Com::Objsys::Asn1::Runtime::Asn1Type, 202
 URShift
 Com::Objsys::Asn1::Runtime::Asn1Util, 234
 UTC
 Com::Objsys::Asn1::Runtime::Asn1Time, 187
 utcFlag
 Com::Objsys::Asn1::Runtime::Asn1Time, 185
 UTCTime
 Com::Objsys::Asn1::Runtime::Asn1Type, 202
 UTF8String
 Com::Objsys::Asn1::Runtime::Asn1Type, 202

 validate
 Com::Objsys::Asn1::Runtime::Asn1CharRange, 38
 Com::Objsys::Asn1::Runtime::Asn1CharSet, 41
 Com::Objsys::Asn1::Runtime::Asn1CharString, 48
 Com::Objsys::Asn1::Runtime::Asn1DiscreteCharSet, 62
 Com::Objsys::Asn1::Runtime::Asn1UniversalString, 219
 VideotexString
 Com::Objsys::Asn1::Runtime::Asn1Type, 202
 VisibleString
 Com::Objsys::Asn1::Runtime::Asn1Type, 202

 Write
 Com::Objsys::Asn1::Runtime::Asn1EncodeBuffer, 66
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 144
 Write2Bytes
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 145
 Write4Bytes
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 145
 WriteByte
 Com::Objsys::Asn1::Runtime::Asn1OutputStream, 145
 WriteStackTrace
 Com::Objsys::Asn1::Runtime::Asn1Util, 235

 Year
 Com::Objsys::Asn1::Runtime::Asn1Time, 187
 Com::Objsys::Asn1::Runtime::Asn1UTCTime, 224
 year
 Com::Objsys::Asn1::Runtime::Asn1Time, 185